GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELLIF HEAD QUARTERS. DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

NOF & DES MS (2011 GH /2224

Dated 12/08/11

FIRE SAFETY CERTIFICATE

Certified that the Hotel Ganga Azure located at E 58 Greater Kailash-1. New Delhi comprised of Basement, Ground + 3 upper floors was granted NOC by this department vide letter No F 6 / DFS / MS / 2008 / 2376 dated 21 08 2008. The premise was re-inspected by the officer concerned of this department on 15 08 2011 and found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with. Rule 33 of the Delhi Fire Service Rules, 2010. and that the premises is fit for occupancy class Sub-Division A-L Lodging or Rooming House of Group A with effect from 12/59/11 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010

Issued on 12/69/11 at New Delhi

Yours faithfully

CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to :=

- The Addl Commissioner of Police (Lie)1" Floor, Police Station Defense Colons New Delho
- Hotel Ganga Azure located at E 58 Greater Kailash-1 New Delhi

Conditions for the validity of fire safety certificate

- All the means of escape/entry/exit shall be kept free from any obstruction
- All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3 All the staff members must know the correct method operation of fire fighting system
- 4. Any lapse rendering fire tighting system/equipment non-functional shall be risk and responsibility of the management
- 3 This inspection report may not in any way be treated as regularization of unauthorized construction, if any
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nie in

	_11	NSPECTION	ON REPORT			
3 3	Details of previous NOC Fire Safety directives letter No The Safety directives letter No The Safety directive No The	Revident New Case Letter No.	Renewal -	E,58 Gyealin K. Lockging or Roomin 14H/2008/2376 Date	y House	
8	 Name of the Inspecting Officers: Name and designation of officers from the building side Year of Construction 	:	S. Kaush asement + 4son esh Pal 1 983	Manager	Mich	
S. No.	Applicant's letter No. Minimum Standards on fir- prevention and fire safety U/R	e	Addl <u>CP/he ()</u> NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building					
	 Road width Gate width Width of internal road 		13mhr MA	3 cm lin	mr.	
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases • Upper Floors • Basements			Two Stargeans	mr.	
	b. Width of staircases • Upper Floors • Basements	-	12 Scmsaspe		MK	
	Protection of exits Fire check door Pressurization		MR MR		6.77	
	e. No. of continuous staircases to te g. Width of Corridor h. Door Size	errace	MM	2 Time	MI	

				1				
	Compartmentation.	. 1	A14					
	 Fire check door 	HR	74/1					
	 Sealing of electrical shafts 	MI	NI					
	 Fire Rating of shaft door 	HR	M					
	Water Curtain	MM	MA					
	Fire Dampers							
	Smoke Management System.	Smoke Management System.						
1	 Basements 	30 a/c per hour	Exchant fan	mil				
	Upper floors	12 a/c per hour	MG	NA				
5.	Fire Extinguishers							
	Total numbers	2	12					
	• Types	4	COZTYPELABL	mn				
	IS marking	ISI marked	yes.					
6	First-Aid Hose Reels.							
	Total numbers on each floor		one at each flow you mist sout	n md				
	 Length of hose reel hose 	30 m	30 mb each	men				
	Nozzle diameter	5 mm	Smmeach	mi				
7	Automatic fire detection and alarming system.							
	Type of detectors	- NR	NR					
	Location of Main Panel	MR	NK					
	Location of Repeater Panel	MR	NR					
	Alternate source of power	NIL	MK					
5	Hooters' Location	NN	NR					
8	MOEFA	Regurd	horided	MN				
9	Public Address System,	HR	N-P					
10	Automatic Sprinkler System.		PAT	IIIVERA				
7	Basement	Regursel	fronded	MR				

	Upper Floor Sprinkler above false ceiling	HR	MP	NL		
		HR.	HP	INR		
11	Internal Hydrants					
	Size of riser/down-comer	MR	MY	NK		
	Number of hydrants per floor Hose Box	MR	MP	MR		
		HR	MP	NR		
12	Yard Hydrants.					
	Total number of hydrants	HK .	NO	MK		
	Hose Box	MM	MP	MR		
13	Pumping Arrangements.					
	Ground Level			15		
	➤ Discharge of main Pump	Required	4 solpm			
	➤ Head of Main pump	Regulard	4 solpm Ao mhr			
	Number of main pumps	one	one			
	> Jockey Pump out put		180 LPM			
	> Jockey pump head		9.21 255			
	Standby Pump out put	Ma	MP	NR		
	 Standby Pump Head Auto Starting/ Manual stopping 	MA	MP	M		
		N N N N				
		Auto Slanky	Yes.	MIL		
	➤ Pump House Access		\2			
	Terrace level	1.0.0	SWS CONTRACTOR			
1	. > Discharge of pump	As fiven	As given	ml		
	➤ Head of the pump	asive	above.	Truc		
	Power Supply					
	> Auto Starting of pump					
14	Captive Water Storage for fire fighting.					
	Underground tank capacity	MR	MP	MI		
	> Draw-off connection	MM	MP	MP		

	➢ Fire service inlet				
	> Access to tank	and the state of	* * * * * * * * * * * * * * * * * * * *	-	
	Overhead Tank capacity	10,000 dkm	10,000 ali	mo	
15	Exit Signage.	Required	Gronded		
16	Provision of Lifts.	NB.	4		
	Pressurization of Lift Shaft	00	NP		
	Pressurization of Lift lobby	MI	NP.		
	Communication In lift Car	1	NI		
	Fireman's Grounding Switch	MP	MP.		
	Lift Signage	Lip	NP		
17	Standby power supply	Repuirsel	& honded	MR	
18	Refuge Area.				
	> Total Area	HA	MK	MZ	
	> Location	MR	MR	MN	
19	Fire Control Room				
	Detector System Panel	NR	MK		
	 Flow Switch Panel 	MR	MR		
	PA System Panel	NR			
	Batter backup	MA			
	Building Floor Plans	NA			
20	Special Fire Protection Systems for Protection of special Risks, if any:	NR	MR	M	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of the Inspection Citizer

Name

Designation

Maushy Signature of the Inspecting Officer

Name

S-S-Kaushul

Designation ASSHOW Afrey