GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADOUARTERS: DELHI FIRE SERVICE: NEW DELHI-110 001

No. F6/DFS/MS/2011/2256

Dated:

16/9/2011

FIRE SAFETY CERTIFICATE

Certified that the building at plot no. J-23, located at Udyog Nagar, Peera Garhi, Delhi, is comprised of basement, ground floor, mezzanine and first floor only was issued NOC vided letter no. 75 (U/DFS/2006, 59 deted '4-02-2006. The premises was re-inspected by the officer concerned of this department along with Sh. O.P. Monga, and observed that the owner/occupier have deemed compiled with the fire prevention and fire safety requirements under Rule 33 of the Delhi Fire Service Rules 2010 and found that all the fire prevention and fire safety requirements are maintained in good working condition and there is no additional construction and therefore, the premises is fit for occupancy class Group G (a) (ii) hence, NOC is renewed with Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued on ... 16/9/11 at New Delhi by.

Chief Fire Officer Delhi Fire Service

QC NW

Copy to :-

Sh. O.P. Monga, J-23, Udyog Nagar, Rohtak Road, New Delhi.
 CONDITIONS FOR THE VALIDITY OF FIRE SAFETY CERTIFICATE

- All the fire safety arrangement provided their in shall be maintained in good working conditions at all time. The owner/occupier shall submit a declaration every year in form 'K' provided in the first shedule of Delhi Fire Service Rule 2010. This is available on www.dfs.delhigovt.nic.in.
- Any loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3 The trained fire fighting staff should be available round the clock.
- Any deviation, with regards to construction etc shall be verified the concerned building sanctioning agency.
- 5. The basement shell be used strictly as per the provision of building Bye-Laws.
- This certificate connot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.

May kindly peruse letter no. dated received J-23, Udyog Nagar, Peera Garhi, Delhi where in renewal of NOC is requested this restaurant has already been issued NOC's number of types hence the recommendation are made on old lines. Accordingly, inspection was carried out by D.O. (Moti Nagar) of the restaurant was also present at the time of inspection.

1. Name &address of the building

: J-23, Udyog Nagar, Peera Garhi, Delhi Bagh, New Delhi

2. Type of Occupancy

Industrial (G-19)ii)

3. Type of Case

Renewal

4. Details of previous NOC

Letter no. F5/J/DFS/2006/59 dated 14/2/2006

5. Fire Safety directives letter No.

: F-5(J) DFS/2005/491 dated 12/10/2005

6. Date of inspection

: 14/08/2011

7. Name of the Inspecting Officers

: Division Officer Sunil Chowdhary

8. Name and designation of officers

From the building side

: Sh. O.P. Monga Owner

9. Year of Construction

: No record available

10.

Applicant's letter No.: Nil

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

Access to building							
			Access to building				
 Road width 	03 mtrs	45 feet	Recommended				
 Gate width 	5 mtr	5 mtr	Recommended				
Width of internal road		Set back	Recommended				
	Gate widthWidth of internal road	Gate width O3 mtrs 5 mtr	• Gate width 03 mtrs 5 mtr 5 mtr • Width of internal road				

	a. Number of staircases				
	Upper Floors	Two	Two	Recommended	
	Basement	Two	Two	Recommended	
	b. Width of staircases				
	 Upper Floors 	1.5 mtr each	1.5 mtr each	Recommended	
	Basement	1.5 mtr each	1.5 mtr each	Recommended	
	c. Protection of exits				
	Fire check door	N/ID	Provided	Recommended	
	 Pressurization 	N/R N/R	N/R		
	d. No. of continuous staircases				
	to terrace	1.5 mtrs	N.A	Recommended	
	e. Width of Corridor		700		
	f. Door size	1 mtrs	1.25 mtr	Recommended	
3.	Compartmentation.				
	Fire check door	Basement	Provided	Recommended	
	 Sealing of electrical shafts 	N.A.	No Shafts	Recommended	
	Fire Rating of shaft door	N.A.	N.R.	Recommended	
	Water Curtain	N.A.	N/R	Recommended	
	Fire Dampers	N.A.	N/R	Recommended	
4.	Smoke Management System.				
	Basements	30 a/c per hour 12 a/c per hour N.R.	Exhaust Fan	Recommended	
	Upper floors		Exhaust Fan		
5.	Fire Extinguishers				
	Total numbers	A.B.C.	10	Recommended	

	• Types					
	POST PROTECTION OF	ISI marked	ABC Type			
	IS marking		ISI marked			
6.	First-Aid Hose Rees.					
	Total numbers on each floor		707	Recommended		
	Length of hose reel hose	30 m	01 30 m			
	Nozzle diameter	5 mm	5			
7,	Automatic fire detection and alarming system.					
		N/R	N.R.			
	Type of detectors	100000	IN.R.	Recommended		
	Location of Main Panel	N/R	N.R.	Recommended		
	Location of Repeater Panel	N/R	N.R.	Recommended		
	Alternate source of power	N/R	N.R.	Recommended		
	 Hooter's Location 	N/R	Duo id d			
			Provided on each Each floor	Recommended		
3.	MOEFA		N/R			
,	Public Address System.		XI N			
0.	Automatic Sprinkler system		N.R.			
A107 11	ALL SAME					
	Basement	_	Provided			
	Upper Floor	N/R	N/R	Recommended		
	Sprinkler above false ceiling	N.A.	N/R	Recommended		
1.	Internal Hydrants					
	Size of riser/down-comer	N/R	N/R	Recommended		

	Number of hydrants per floor	N/R	N/R			
	Hose Box	N/R	N/R			
12.	Yard Hydrants.					
	Total number of hydrants	N/R	N/R	Recommended		
	Hose Box	N/R	N/R	-do-		
13,	Pumping Arrangements.					
	Ground Level					
	➢ Discharge of main pump	B.B.L. do not safety pump capacity	1620 LPM	Recommended being old case		
	➤ Head of Main pump	B.B.L. do not safety pump capacity	65 mtr	A A A A A A A A A A A A A A A A A A A		
	 Number of main pumps 	B.B.L. do not safety pump capacity	one			
	➢ Jockey Pump out put	B.B.L. do not safety pump capacity.	180 L.P.M.			
	 Jockey pump head 	B.B.L. do not safety pump capacity	65 mtr			
	 Standby pump out put 	B.B.L. do not safety pump capacity	N/R			
	 Standby pump Head 	B.B.L. do not safety pump capacity,	N/R			
	Auto Starting/Manual stopping	B.B.L. do not safety pump capacity	Manual			
	Pump Hose Access	B.B.L. do not safety pump capacity	Accessible	Recommended		
	Terrace level					
	 Discharge of pump 	N/R	N/R	Recommended		
	➢ Head of the pump	N/R	N/R	Recommended		
	> Power supply	N.R.	N/R	Recommended		
	 Auto Starting of pump 	N.R.				

	Captive Water Storage for fire fig					
	Underground tank capacity	B.B.L. do not safety tank capacity	25000 105	recommended		
		B.B.L. do not safety tank capacity	N/R			
	> Draw -off connection	N/R	N/P	recommended		
	➤ Fire service inlet	Accessible	Accessible	recommended		
	 Access to tank Overhead Tank Capacity 	Do not specify	15,000 ltrs	recommended		
15	Exit Signage.	136 Hot specify				
16.	 Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	N.A	Not available	Recommended		
		N.R.	Not available	recommended		
		N.R.	Not available	recommended		
		N.R.	Not available	recommended		
		N.R.	Not available	recommended		
17.	Standby power supply	N.R	Provided 65 K.V.A	recommended		
18.	Refuge Area		N.R.			
10.		Not applicable	N.R.	recommended		
	> Total Area	Not applicable	N.R.	recommended		
19.	. Fire Control Room					
	> Detector System Panel	N.A.	N/R	recommende		
	> Flow Switch Panel	N.A.	N/R	recommende		
	> PA system Panel	N.A.	N/R	recommende		
	> Batter backup	N.A.	N/R	recommende		

Building Floor plans	N.D.	recommended
Special Fire Protection Systems for Protection of special Risks, if any:	N.R.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial number.

Signature of the Inspection Officer

WW

Signature of the Inspection Officer

Name Swil Chawdhary

Name

Designation D. O. (M.N) M.

Designation

10/0 July

010

ME CLOS