GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2011/EH/ 1294

Dated: 23/09/11

FIRE SAFETY CERTIFICATE

Leth 7 comprised of Ground Flor only occupi	
della 7 located at Kamla Nogar	
Comprised of Ground + box only Occupi	ec
I thankhole Syndicalelyas issued NOT wish this office I was	1
Dated 12 1 The premises was re-inspected by the	58
nicer concerned of this department on	iro
prevention and fire safety arrangements as provided in the premises found in good works	n B
ondition. The premises have therefore, deemed complied with the requirement under Rule of the Delhi Fire Service rule 2010 and the building/premises is fit for occupancy Cla	33
A Securely Sub-Div. D. 5 with effect from 23/09/11 for a period	155
23.78 in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled und	01
rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Servi	50
Rules, 2010	1010
Issued on 2-3/09/1/	
(M ₁ , 2)	

Chief Fire Officer Delhi Fire Service

Copy to: Dq. Health officer

MCD Civil lines 2 tone

RoJ Pro Ro-d

Delin

2. The Manager

Dwarks Restaurant

2-F. Kamle ropon

Lelin 7.

1. All the means of escape shall be kept free of all type of obstruction all the time (3)

All the employees shall be acquainted with the use and maintenance of a fire
equipments and method of smooth and speedy safe evacuation of occupants in case of
emergency.

 All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non - functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

Basement shall be used as per №0¢.

41 4

5. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.

The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT Name & address of the building: DWARKA RESTAURANT, 3F KAMLA WAGAR DELA Restaurant. 3 Type of Case : New Case/ Renewal - Details of previous NOC : Letter No. F6 10F5 | mS/EH/0 8 /3003 Dated: 3/11/2008 5. Fire Safety directives letter No 6. Date of inspection 579/11 7 Name of the Inspecting Officers : VIPIN KENTAL 8. Name and designation of officers from the building side -sn-Asay manager. 9. Year of Construction 10 Applicant's letter No. Mi st mil. S. Minimum Standards on fire NBC Provided at site Remarks No. prevention and fire safety U/R 33 Requirement MR/NMR Access to building Road width motorable road MIR Gate width N.A Width of internal road NA Number, Width, Type & Arrangement of Exits a. Number of staircases Located on GF only · Upper Floors · Basements b. Width of staircases

NA being old case.

1

2

 Upper Floors Basements

· Fire check door

Pressurization

e. No. of continuous staircases to terrace

c. Protection of exits

g. Width of Corridor

h. Door Size

				1	
3	Compartmentation.				
	Fire check door Sealing of electrical shafts	Not require	eèd /		
	 Fire Rating of shaft door Water Curtain Fire Dampers 				
4	Smoke Management System.				
	BasementsUpper floors	30 a/c per hour 12 a/c per hour	N.A being	e over case	
5	Fire Extinguishers				
	Total numbersTypesIS marking	ISI marked	3 Cortype 5 1cg	in m. R	
6	First-Aid Hose Reels.				
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m 5 mm	1 on 9. F	m·R	
7	Automatic fire detection and alarming system.				
2	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	Not requir			
8	MOEFA	Required	Prouded	m/R.	
9	Public Address System.	Not segund			
10	Automatic Sprinkler System.		No basemen	K	
	Basement		/	N'A.	

	 Upper Floor Sprinkler above false ceiling 		N.A	
11	Internal Hydrants			
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	Not requi	ncid /	/
12	Yard Hydrants.			
	 Total number of hydrants Hose Box 			
13	Pumping Arrangements.	/		1
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level 	Not roque	red.	
35	 Discharge of pump Head of the pump 	275 L.PM	125 LPM	mm
	➢ Power Supply➢ Auto Starting of pump	yet yet	Prosuded.	MIR
4	Captive Water Storage for fire fighting.	oft scene	and a	11 10
	 Underground tank capacity Draw-off connection 	Not requir	29.	

	 Fire service inlet Access to tank Overhead Tank capacity 	N.R		
5	Exit Signage.	poqued.		
6	Provision of Lifts.	poguned.	(doe) .	
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car 			
	 Fireman's Grounding Switch Lift Signage 			
17	Standby power supply	Required	Monday 63.5 kvA	M/R.
18	Refuge Area.	NOT requ	used ,	
	> Total Area > Location			
19	Fire Control Room	Not requ	med.	
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup 	1		
	Building Floor Plans	10 MA 8	ISh exiett oil	es sevitchen.
20	Special Fire Protection Systems for Protection of special Risks, if any:	110 /9/470	DCP type fine GXI- moveday	MIR.

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

· (3)

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name VIPIN KENTAL

Designation DO NW