GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI

No: F6/DFS MS GH 2011 2382

Dated: 30/09/11

FIRE SAFETY CERTIFICATE

Certified that the guest house building in the name and style of M/s. Aricia Sourcing (P) Ltd., located at A-1/23, Safdarjung Enclave, New Delhi – 110029 comprised of basement (storage), stilt (parking), ground floor (9 guest rooms), first floor (9 guest rooms), second floor (9 guest rooms) and third floor (9 guest rooms) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service rules, 2010 and verified by the officer concerned of fire service on 09-08-2011 in the presence of Mr. T.P. Singh, General Manager and that the building is fit for occupancy class of residential with effect from 3.0./.0.9././..... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules-2010.

Issued on 30/09/11 at New Delhi by.

CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to :-

- The Addl. Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi - 110049
- M/s. Aricia Sourcing (P) Ltd., A-1/23, Safdarjung Enclave, New Delhi - 110029

Note* :- For general fire safety directives please see overleaf.

Following fire safety directives must be adhered to :-

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

		CTION REPORT	Sourcing(P)	276.	
	Details of previous NOC Letter Fire Safety directives letter No Date of inspection Name of the Inspecting Officers Name and designation of officers from the building side	Case/ Renewal TNO. N.R NO S. Kaushik &	Date	ed: N.R	
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/38L Requirement	Provided at site	Remarks MR/NMR	
	Access to building				
ł	 Road width 	18 mtes	MOSE THEN 20 MES M. R		
	 Gate width Width of internal road 	4-5 M.	6 mtes	M.R	
	Number, Width, Type & Arrangement		N.R	-	
	a. Number of staircases	of Exits			
	 Upper Floors 	700	Two	M. R	
1	Basements Width of staircases	Two	TWO	M. R	
17	Upper Floors Basements	1.25	1.25 M & .80 M	M-R	
17	c. Protection of exits	-11 -	1.25 M& 1.25M	M.R.	
	Fire check door Pressurization	Reguised	Provided in	-N. R	
		Nº R.		M.R.	
	e. No. of continuous staircases to terrace	Two	Two "	M. R.	
U.,	g. Width of Corridor h. Door Size	1.25	1.25	MR	
=	ii. Door Size	onemin	one mia	M-R	

Contd -

				,	
3	Compartmentation.				
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 	Required in Basement N.R. N.R.	Provided in the Basement N.R N.R	# M.R.	
	Smoke Management System.	N.R.	N. R		
	Basements Upper floors	30 a/c per hour 12 a/c per hour	Provided for Provided Extraction	rs M. A	
	Fire Extinguishers				
	 Total numbers Types IS marking 	6+6=12 co2 & w. co2 ISI marked	6+6=12 cox & w.co2		
	First-Aid Hose Reels,	151 marked	ISI Marked	M-R	
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	/ No · 30 m	1 No ateach	M-R M-R	
	Automatic fire detection and alarming		SMM	MR	
	Type of detectors Location of Main Panel	smoke detector	Vice to Tark	m.R	
	Location of Repeater Panel Alternate source of power	stilt flog.	Provided.	M·R	
*5	Hooters' Location	N.R.	N. R N. R		
	MOEFA	Regard.	privided.	M. B	
	Public Address System.	N. R	N.R	-	
0	Automatic Sprinkler System.				
	Basement	Required.	Provided	M.R.	

	 Upper Floor Sprinkler above false ceiling 	Not Esque		M. R
11		Not require	4	
1.0	Internal Hydrants		7 11	
8	 Size of riser/down-comer Number of hydrants per floor 	not requise	of 63 mm	
	Hose Box	-0 -	one No.	7
12	Yard Hydrants.	-11-	one wat	1
	 Total number of hydrants Hose Box 	Not loguese		
3	Pumping Arrangements.	-11-	Two Nor	7
	Ground Level			
	➤ Discharge of main Pump	N.R.	N. R	
	➤ Head of Main pump	N.R.	N.R	
	> Number of main pumps	N.R.	N. K	
	> Jockey Pump out put	N.R	N. P	
	Jockey pump head	N.R.	N.R.	
	> Standby Pump out put	N.R.	N.R.	
1	Standby Pump Head	N. R.	N.R.	
H	> Auto Starting/ Manual	N.R.	N. R.	-
	stopping	N.R.	N. R.	
	> Pump House Access	The second secon	· ·	
	Terrace level	2		_
	➤ Discharge of pump	Required	per vided.	_
	➤ Head of the pump	900 LPM	900 LAM ,	MR
	➢ Power Supply➢ Auto Starting of pump	provided -	providet	m R
C		Auto	Auto street	M. R.
1	Captive Water Storage for fire fighting.			
	 Underground tank capacity Draw-off connection 	Not Equipm	Not forced	

costd.

	> Fire service inlet	Required.	Provioled.			
	➢ Access to tank	-11 -	Provided.	m.R/		
	Overhead Tank capacity			M. R. 1		
15	Exit Signage.	Required.		M. R.		
16	Provision of Lifts.	REFUCIES.	Provided.	M. R.		
	 Pressurization of Lift Shaft 	Not beguin	NR	M.R.		
	 Pressurization of Lift lobby 	N. R.	N.R.	M.R.		
	 Communication In lift Car 	N.R.	N.R.	M. R		
	 Fireman's Grounding Switch 	Required.	Provided.	W 12.02.0		
	 Lift Signage 			m. R.		
2000		-11-	Provided-	M.R.		
17	Standby power supply	_1/	D.G. Set 160K	n m-R.		
18	Refuge Area.					
	➤ Total Area	N.R.	N. R			
	> Location	N.R.	N.R.			
19	Fire Control Room					
	Detector System Panel	N.R	N.R	/		
	 Flow Switch Panel 	N.R.	N.R.	_ (
	PA System Panel	N.R.	N. K	-		
	Batter backup	N.R.	N.R			
	Building Floor Plans	N.R.	N.R.			
20	Special Fire Protection Systems for Protection of special Risks, if any:	N.R.	N.A.			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

contd:

A1/23, Safderjung toclore new action-1/029 (5)

Signature of the Inspecting Officer

Signature of the Inspecting Office

Name

Name

Designation

Designation