GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6 / DFS / MS / 2011 / 5 H/ 2350

Dated 28/09/11

FIRE SAFETY CERTIFICATE

Certified that the Guest house Sarah Lodge, at 2370, Ballimaran, Delhi - 06 comprised of, Ground + 1 upper floor was granted NOC by this department vide letter No F 6 / DFS / MS / 2008 / 1790 dated 27.06.2008. The premises was re-inspected by the officer concerned of this department on 21.09.2011 in the presence of Manager Walli Ullah and found that the said building have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" with effect from 2.8 / 9.9 / 1/... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .2.8/2.9./..... at New Delhi by.

CHIEF FIRE FFICER
DELHI FIRE SERVICE

Copy to: -

1. The Deputy Health Officer (MCD), City Zone, Asaf Ali Road, Delhi-06

2. The Manager, Sarah Lodge, 2370, Ballimaran, Delhi-06

Conditions for the validity of fire safety certificate

1. All the means of escape/entry/exit shall be kept free from any obstruction.

All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.

3. All the staff members must know the correct method operation of fire fighting system.

 Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.

This inspection report may not in any way be treated as regularization of unauthorized construction, if any.

6 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

500001

SADIDA BALG.

BARAH LODGG.

Ballmaren Delli & B.

Building Covered under Special area No. F6/ms/DFs/2001/1795 dt. 29-8-2001

INSPECTION REPORT

1	Name & address of the building . So	arrah Lodge, 2370	Ballimaran 3	Dollis-6.			
2	2 Type of Occupancy : Group A-1 Residential.						
Type of Case New Case/ Renewal Details of previous NOC							
						5. Fire Safety directives letter No F-6/rs/DES/6H/2000/1999 dt. 2 1/2000 2 F-6/rs/DES/6H/01/2920 6. Date of inspection 8. F-6/rs/DES/6H/2001/1218 dt. 25-6-200).	
6		(1-7-2011		4.4.1) = 13/11.			
7	Name of the Inspecting Officers: 1	ADO-SHVAM ZA	, "				
8	Name and designation of officers w	Manuaca Malli	110-1				
	from the building side	GI+1) ZE ROOMS	Owan.				
9	Van Co	1970					
1	0. Applicant's letter No.						
S. Na	Minimum Standa on fice prevention and fire safety U/R 3:	Greelor	Provided at site	Remarks MR/NMR			
	Access to building						
	Road width		04.25 mbs.	MR Spenn			
	Gate width	NIA	01.60 mbg.	, , , , , , , , , , , , , , , , , , ,			
	Width of internal road	NA					
2	Number, Width, T. pe & A rangement F.Exits						
	a. Number of staircases	1	one				
	 Upper Floors 	2	One				
	* Basements	NIA	·NIL				
	b. Width of staircases	1.25	95 cms -	MR 86			
	 Upper Floors 	71	95cm	mik II			
	 Basements 	NIA	NIC	0100			
	c. Protection of exits	Two est	777	-			
	 Fire check door 	N/A	0/10	4/10			
	 Pressurization 	N/A-	NA	NIA			
	c. No. of continuous staticases to terra	100	one	Deided			
	g. Width of Carridor	MA		bugar			
	to Paper Silve	NIA	NIA	NIL			

ď	Compartmentation.			
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 	N/A		
74	Smoke Management System.			
	Basements Upper floors	30 a/c per hour 12 a/c per hour	MA	
5	Fire Extinguishers			/
6	Total numbers Types IS marking First-Aid Hose Reels.	ISI marked	6 Nois W.COZ = 2 ABC =1, COZ = 3 Yes	MR MR
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m 5 mm	1 44 45	m R ys
7	Automatic fire detection and alarmin	g system.		1
E III	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	N/A		
8	MOEFA	P/n		
9	Lublic Address System.		provided.	
10	Automatic Sprinkler System. Basement	NIA		

	Upper Floor	
	 Sprinkler above false ceiling 	NA
11	Internal Hydrants	NIA
	Size of riser/down-comer	
	 Number of hydrants per floor 	
	 Hose Box 	
12	Yard Hydrants.	A / / /
		14/14
	 Total number of hydrants Hose Box 	
13		
- Mitte	Pumping Arran Trents. • Ground Leel	
	➤ Discha ge of mair Pump	
	➤ Head of Main pump	1110
	 Number of main pumps 	D/H
	 Jockey Pump out put Jockey pump head 	
	> Standby Pump out put	
	Standby Pump Hend	
	Auto Starting/ Manual	
	stopping	
	Pump House Access	
	 Terrace level 	
	 Discharge of pump 	225 2ts/minit MR 40m Belgalden
	Head of the pump	40m Beljalden
	Power Supply	
	 Auto Starting of pump 	
151	Captive Water Storage for fire fighting	
	 Underground tank capacity Draw-off connection 	- W/n

	 Fire service inlet Access to tank 		Provided	,
	Overhead Tank capacity	76-24	2500 145.	
15	Exit Signage.		Provide of	
16	Provision of Lifts.	N/	SA	
	Pressurization of Lift Shaft Pressurization of Lift lobby			
	 Communication In lift Car Fireman's Grounding Switch Lift Signage 			
17	Standby power supply		_	
18	Refuge Area.	N	114	
	Total AreaLocation			
fφ	Fire Control Room	Ŋ	JA.	
	 Detector System Panel Flow Switch Panel PA System Panel 			
-	Building Floor Plans		-	
29	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	WID	

The fire protection systems provided in the building were test checked and found functional at the tol inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sa required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Dire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name SHYAM LAL

Designation Assit. Divn. Officer