GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFs/ms/school/2011/2422

Date 04/10/11

FIRE SAFETY CERTIFICATE

Issued on O.Y. / L.D./at New Delhi by

Chief Fire Officer Delhi Fire Service

To,

Principal
Govt. Girls Sr. Sec. School
Vivek Vihar PH-II, Delhi-92
Copy to:-.
The Joint Director of Education
(Land & Estate)
Directorate of Education,
Lucknow Road, Delhi -54.

CONDITIONS:

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire
 equipments and method of smooth and speedy safe evacuation of occupants in case
 of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

	5. Fire Safety directives letter No : £ / 6. Date of inspection : 9 7. Name of the Inspecting Officers : 18 8. Name and designation of officers	ter No. 16) Estate CC 1 9 2011 Do Shresh	Da Fire Setety 12011 / 3398 detect /	ted:
	from the building side 9. Year of Construction	irs Sandhya	Character Pa	***************************************
i	Year of Construction Applicant's letter No.	1978	A STATE AND A	incipe
S.	O. Applicant's letter No. : Go of Minimum Standards on fire	355/VX 11/54	8 dated 22.2	0.4
No.	prevention and fire safety U/R 33		Provided at site	Ren
	Access to building			MR
	Road width		10.5	8.0
	 Gate width Width of internal road 		5 M	M
			+-	
	Number, Width, Type & Arrangement a. Number of staircases	of Exits	-	
	Upper Floors	2	2	M
	Basements		2	
b	D. Width of staircases	~		M
- 1	Upper Floors	1.57	1.5 M	MA
1-	Basements	1.54	1.57	
c. Protection of exits				M
	Fire check door	-		
	Pressurization		#	
e.	No. of continuous staircases to terrace			-
g.	Width of Corridor	•	No	
	Door Size	1.5 4	2 M	MR
		1 F/	1 +1	MR

13	Compartmentation.				
	 Fire check door 		Provided	2	
	 Sealing of electrical shafts 				
	 Fire Rating of shaft door 				
	Water Curtain Fire D		~		
1	The Dampers				
4	Smoke Management System.	5110			
	• Basements	30.0/0			
	• Upper floors	30 a/c per ho	our		
5_	Fire Extinguishers		1		
	 Total numbers 				
	• Types	Required 7 m	/6 /2	7	
	IS marking	TOT	MBC - Co2	7	
6	First-Aid Hose Reels.	ISI marked	151	1	
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m	-	T	
7 /	Automatic fire detection and	5 mm	e	1	
	Automatic fire detection and alarming system. Type of detectors				
	Location of Main Panel	-	• -		
	Location of Repeater Panel			Ī	
	 Alternate source of power 			-	
	 Hooters' Location 			-	
M	OEFA	-	-		
Pul	blic Address System	HIA			
Aut	tomatic Sprinkler System.		Provided		
1 5	Basement	MIA			

	 Upper Floor Sprinkler above false ceiling 	-		
1.1				
	 Size of riser/down-comer 	NIQ		
	 Number of hydrants per floor Hose Box 			
12	Yard Hydrants.			
	Total number of hydrants	1111	-	
13	Hose Box	39/1		
	Pumping Arrangements. • Ground Level	NIA		
	Discharge of main Pump			
	Head of Main pump			
	➤ Number of main pumps ➤ Jockey Pump	_	***	
	 Jockey Pump out put Jockey pump head 			
	Standby Pump out put			
	Standby Pump Head		-	
	> Auto Starting/ Manual stopping			
	➤ Pump House Access			
	Terrace level	<u> </u>		
	 ➢ Discharge of pump ➢ Head of the pump 			
	➤ Power Supply	-		
C	➤ Auto Starting of pump			
	otive Water Storage for fire fighting.	1-114		
	Underground tank capacity Draw-off connection	_	-	
	off connection	-		

	 Fire service inlet Access to tank Overhead Tank capacity 			-
15				
16		11/17		
	Pressurization of Lift Shaft	-		
	Pressurization of Lift lobby Communication to the	_	-	
	 Communication In lift Car Fireman's Grounding Switch Lift Signage 			-
		-		
17	Standby power supply	×11 #		
18	Refuge Area.	7111		
	➤ Total Area ➤ Location			
9	Fire Control Room	MIA		
	Detector System Panel		-	
	 Flow Switch Panel PA System Panel 	-	-	
	Batter backup		-	
1	Building Floor Plans		-	-
P	pecial Fire Protection Systems for rotection of special Risks, if any:	11/4		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Stuph

Signature of the Inspecting Officer

Name Suresh Singh

Designation 400

Signature of the Inspecting Office

Name

Designation