GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2011/4H/2402

Dated 63/10/11

FIRE SAFETY CERTIFICATE

Certified that the O.K Guest house at 129, Gali Jatwara, Pul Mithai Delhi - 06 comprised of, Ground + 04 upper floors was granted NOC by this department vide letter No F 6 / DFS / MS / 2008 / 3072 dated 11.11.2008. The premises was re-inspected by the officer concerned of this department on 23.09.2011 in the presence of Manager Sh. Mahender Kumar and found that the said building have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 10.3 / 10/11... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .93././....... at New Delhi by.

CHIEF FIRE ÓFFICER DELHI FIRE SERVICE

11(14

Copy to: -

- 1. The Addl. Comm. of Police (Lic) First Floor, Police Station, Defence Colony, New Delhi.
- 2. The Manager, O.K Guest house, at 129, Gali Jatwara, Pul Mithai Delhi 06

Conditions for the validity of fire safety certificate

- All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in



Building-Covered under special area L. No. F-6/ms/DFS/2001/1795 dated 29-8-2001

INSPECTION REPORT

3 4 5 6 7 8	Details of previous NOC Fire Safety directives letter No F-6/2 Date of inspection Name of the Inspecting Officers Name and designation of officers of the building side Year of Construction Applicant's letter No.	New Case/ Renewal Letter No F 6/ms/Drs/c /ms/Drs/GH/2000/199 F 6/ms/Drs/GH/2000/199 F 6/ms/Drs/GH/2000/199 ADO-SHYA Manager-Sh. M	64/08/3072 D 99 dt 2 2000 & f. 6/10 11218 dt - 25 6	Dated 11-11-2 oc ms/DPs/GH/01/20 GH
S. No.	Minimum Standards on fire prevention and fire safety U/R 33 Access to building	Circulars	Provided at site	211
	Road width			
	Gate width		01-25 mts	
	Width of internal road		01.25 mbs.	m R
1	Number, Width, Type & Arrangeme			
а	Number of staircases	ent of Exits		
	Upper Floors		072	me dela
	Basements		one	mr alin
ь	Width of staircases		. NIL	
	Upper Floors		87 to 97 cms,	mr 2
1975	Basements		87 to 97 cms.	me reiged
G.	Protection of exits	N/A	NIL	resque
	Fire check door			
	Pressurization	WIT	MA	
e.]	No. of continuous staircases to terrace			
9 1	Width of Corridor		one	
	Door Size	NM		ald a
10.70	2001.3126	WM_	NIN	ald cer

	*				
3	Compartmentation.	WA			
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 				
4	Smoke Management System.				
	Basements Upper floors	30 a/c per hour 12 a/c per hour	NA		
5	Fire Extinguishers				
	 Total numbers Types IS marking 		7 W. COZ=4, ABC-2 CO2 2Kg=3	MIR	
	First-Aid Hose Reels.	ISI marked	yes		
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m	one Ind flow frovided.		
	Automatic fire detection and alarmin				
	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	W/ A	N/A.		
	MOEFA	AVIA		N/W	
	Public Address System.	Ne	Provided.	mI	
	Automatic Sprinkler System.		Provided.	1115	
	Basement	WID	1		

	Upper Floor Sprinkler above false ceiling	N7P
11	Internal Hydrants	NIA
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	1:47.17
12	Yard Hydrants.	NA
	Total number of hydrants Hose Box	74)//
13	Pumping Arrangements.	
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	N/A 225 Hs. Iminit MR 40 m ald as
14	Captive Water Storage for fire fighting.	
	Underground tank capacity Draw-off connection	NA

	 Fire service inlet Access to tank Overhead Tank capacity 		
1:	San Signage.	2500 Hs.	
16	Provision of Lifts.	Provioled	
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	NIA	
17	Standby power supply		
18	Refuge Area.		
	➤ Total Area ➤ Location	N/19.	
19	Fire Control Room		
	Detector System Panel	MM	
	 Flow Switch Panel 		
1	PAl System Panel Batter backup		
	Building Floor Plans		
S	pecial Fire Protection Systems for rotection of special Risks, if any:	N/A.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

(3)

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

SHYAM LAL

Name

Designation Assitt. Dirni officer.