GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DLEHI-110 001.

No. F6/DF5/ms/Achael/2011/26/3 Dated: 19/10/11

FIRE SAFETY CERTIFICATE

Certified that the Manay Sthali School located at R-Block, New Rajinder Nagar. New Delhi-110060 having three blocks (Main block, office block & auditorium block). Main block comprised of basement, ground floor plus two upper floors. Office block comprised of basement, ground floor plus three upper floors and auditorium block comprised of basement, ground plus one upper floors. Owned/occupied by Management of Manay Sthali School have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of fire service on 30.9.2011 in the presence of Sh. Ranjit Rautela Estate Officer and that the building / premises is fit for occupancy class educational w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 subject to conditions printed overleaf.

Issued on ______ at New Delhi.

CHIEF FIRE OFFICER
FOR DIRECTOR
DELHI FIRE SERVICE

Copy to:-

- Director (Govt of N.C.T Delhi)
 Directorate of Education,
 Old Secretariat, Delhi,
- The Director.
 Manay Sthali School.

 R-Block. New Rajinder Nagar, New Delhi-60 (Ref. No. MSS/NRN/5360, Dated 18.07.2011)

Following fire safety directives must be adhered to -

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- The trained staff should be available round the clock.
- Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

	CTION REPORT	1.1.000	V 4 4 0 1 4					
 Name & address of the building Type of Occupancy 	3: Manay Sthall	Ochool, K- Blo	ck, New Kajenda					
Type of Occupancy Type of Case	: Educatio							
Details of Previous NOC	: New Case/Renew		2					
5. Fire Safety directives letter No	: Letter No.	N/A	Date					
6. Date of inspection		I A						
7. Name of Inspecting Officer	30_0		0 1 1 1					
	8. Name and designation of officers							
From the building side								
9. Year of Construction	: 1979 8 1º	NOUTER EX	nate Officer					
10. Applicant's letter No.		5360 dated	0 - 0 - 1					
Minimum Standards on fire	NBC/BBL	Provided at						
o. prevention and fire safety U/R 33	Requirement	site	Remarks					
Access to building	The second secon		MR/NMR					
Road width	Required.	Provided	MR-					
Gate width	05 mtr	Previoled	mr -					
Width of Internal road	06mtr	Provided	mr_					
	Number, Width, Type & Arrangement of Exits							
a. Number of staircases		rsoriaen	mR /					
• Upper Floors	- do -	Provided	m.R					
Basements	Two	Provided	mR -					
b. Width of staircases								
Upper Floor	& Staircape in	m Previded	Being Old Building					
Basements	-do-	-do -	- do - 1					
c. Protection of exits			4					
Fire check door	NIR	NIR	MIR					
 pressurization 	NIR	MIR	- /					
d. No. of continuous staircases to	One in each	Provided	m g					
terrace	Block		11					
e. Width of Corridor	06 ineach	Provided	me					
f. Door Size	Wielth - Innets	La Control Control						
. Compartmentation	Height - 2 mtr	- Provided	mr.					
Fire check door	NIR	NIR	-					
 Sealing of electrical shafts 	MIR	NIR	2					
 Fire Rating of shaft door 	MIR	MIR						
Water Curtain	NIR							
 Fire Dampers 	NIR	NIR	~					
. Smoke Management System	N/K	/M/K	-					
Basements	30 3/2 202	Exhoust Fan						
Upper floors	30 a/c per	Provided.	mr.					
* OUDEL HOURS	11001	172 71 11 11 115	ion MR					

ogr

		12 a/c per hour					
j.	Fire Extinguishers						
	 Total numbers Types IS marking 	2 in each block/Phor Co2, WaterCo2, ABC	- dq -	mr.			
5.	First-Aid Hose Reels	is marked	Yes	MR			
	Total numbers on each floor Length of hose reel hose Nozzle diameter	30 m 5 mm	Provided - do - - da -	MR MR			
7.	Automatic fire detection and alarming system						
1	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	NIA NIA NIA	NIA NIA Provided	mR/			
3.	MOEFA	Required	Provided	mR			
9.	Public Address System	Reguired	Provioled.				
10.	Automatic Sprinkler System						
	Basement Upper Floor Sprinkler above false ceiling	Required NIR NIR	Provided NIP Provided	MR MR			
11.	Internal Hydrants	TAID	7 8 0V) 00x.01	1111			
	Size of riser/down-comer Number of hydrants per floor Hose Box	Required -	Provided, Total-12 Provided, Total-12 Provided	mR mR/			
12.	Yard Hydrants	- Previded mg					
	Total number of hydrants Hose Box		Provided Provided	mR mR			
13.	Pumping Arrangements	-	1 / 001/000	N/A			
8	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual stopping 	NIR NIR NIR NIR NIR NIR NIR	NIP NIP NIP NIP NIP NIP	7			

	 Pump House Access Terrace level 	NIR	NIP					
	> Discharge of pump	0	63 Nos / 900/ Pm	40.0040.00				
	➢ Head of the pump➢ Power Supply	900 LPM	450LPM, USOLPM)	MR				
		30m	44m,38m,38m	MR				
	Auto Starting of pump	Tara T	-do -	MR				
14.	Captive Water Storage for fire fighting							
	 Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity 	NIR	NIP	-				
		NIR	NIP	-				
		Required	Provided	mR				
		Required	Previded	MR				
		15000 Ltr	30000 Ltr	mR				
15.	Exit Signage.	Required	Provided	MR				
16.	Provision of Lifts.							
	Pressurization of Lift Shaft	NIR	NIP	-				
	 Pressurization of Lift lobby 	N/R	NIP					
	 Communication In lift Car Fireman's Grounding Switch Lift Signage 	NIR	NIP					
		NIR	NIP	-				
		NIR	NIP	-				
17.	Standby power supply	-	Provided	mR				
18.	Refuge Area.							
16.	> Total Area							
	> Location	MA	NIA	77				
	Electricity of the Control of the Co	NIA	NIA	-				
19.	Fire Control Room							
	Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans	MIR	NIP					
		_	(to the second	-				
			-					
			Provided	mR				
		-4						
20.	Special Fire Protection System for Protection of special Risks, if any:	No	7	5				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Name H.L. Aneja

Designation Divisional Officer

Name P.S. Dahiya

Designation Asst. Divisional Officer.