GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : NEW DELHI-110 001.

Nof6/085/015/1chael/2011/2655

Dated: 21/10/11

FIRE SAFETY CERTIFICATE

Certified that the MC Primary Boys School located at Madanpur Dabas, Delhi-110081 comprised of two blocks. First Block is consist of ground plus one upper floor only and second block is consist of ground floor only and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Director of Education circular dated 01.03.2001 and verified by the officer concerned of fire service on 29.09.2011 in the presence of Shri Yashpal Singh Dabas and that the building/ premises is fit for occupancy class Educational class with effect from \(\frac{1}{2} \rightarrow \frac{1}{10} \) for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 2.1. / ./ ./ ./ ... at New Delhi by

Chief Fire Officer Delhi Fire Service

ole

SHRI YASHPAL SINGH DABAS, PRINCIPAL, MC Primary Boys School, Madanpur Dabas, Delhi-110 081

Copy to :

The Director, Kashmiri Gate, Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

| | | NSPEC | TION REPORT | | | |
|--|---|-------------------|--|---------------------|-------------------|--|
| 1. No | ame & address of the building | M.C | Primary B | oys School, Mac | dayow Da | |
| 4 1 J | pe of Occupancy | school | | | | |
| | pe of Case | New Case/ Renewal | | | | |
| 4 Details of previous NOC N.A : Letter N | | | | | | |
| E Ei | re Safety directives letter No | F-16 | Estate cc File Se | afety 2011 3298-379 | 8 St. 1.3.2 | |
| 0_ 13; | ate of inspection | 29.9.11 | | | | |
| 7. Na | ame of the Inspecting Officers | SA | In R. K. Dahiy | A ADO | | |
| 8. N | ame and designation of office | S | U | | | |
| | om the building side | . N. | A | | | |
| | ar of Construction | | 6 2011 | | | |
| | plicant's letter No. | | 1 24.05.20 | 11 | | |
| So. J | Minimum Standards on fi prevention and fire safety U | 0.00 | Six the col | Provided at site | Remarks MR/NMR | |
| Acc | cess to building | | | | | |
| | Road width | | Accessible | 9 Meters | MIR | |
| 1 | Gate width | | | 6 Melers | | |
| 1 | Width of internal road | | | 9 Meters | | |
| Nur | nber, Width, Type & Arran | gement | of Exits | 1 Meleva | | |
| | umber of staircases | 0 | 2 | 2 | MIR | |
| | e Upper Floors | | - 1 | | 501 11 25 | |
| 1 | Basements | | | - | | |
| b Width of staircases • Upper Floors | | | 150 cm each | 00.0 | | |
| | | | W. The second se | MIR | | |
| 4.7 | Basements | | | banne as above | | |
| c. Protection of exits | | | | | | |
| | Fire check door | | | - | | |
| | Pressurization | | | | | |
| e No of continuous staircases to terrace | | I | | | | |
| | | | 2 | | | |
| | Vidth of Corridor | | | e Melis | 200 | |
| 111 | Joor Size | | First Bolick hould | Boor 100 aus each | MR | |

C35850

| | Upper Floor Sprinkler above false ceiling | |
|-----|--|------|
| 1.1 | Internal Hydrants | N.A. |
| | Size of riser/down-comer Number of hydrants per floor Hose Box | |
| 12 | Yard Hydrants. | N.A. |
| | Total number of hydrants Hose Box | |
| 13 | Pumping Arrangements. | M.A. |
| | Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access | |
| 3 | Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump | |
| 14 | Captive Water Storage for fire fighting. | N.A. |
| | Underground tank capacity Draw-off connection | |

| | Fire service inlet Access to tank Overhead Tank capacity | | | | |
|----|--|-----|-------------------|---|--|
| 5 | Overhead Tank capacity Exit Signage. | MIR | Provided | | |
| 6 | Provision of Lifts. | | | | |
| | Pressurization of Lift Shaft | | - | | |
| | Pressurization of Lift lobby | | | | |
| | Communication In lift Car | | - | | |
| | Fireman's Grounding Switch | | - | | |
| | Lift Signage | | - | | |
| 17 | Standby power supply | | N.A. | | |
| 18 | Refuge Area. | | | | |
| | ➤ Total Area ➤ Location | | - | | |
| 19 | | | | | |
| | Detector System Panel | | - | | |
| | Flow Switch Panel | | | | |
| | PA System Panel | | | | |
| | Batter backup | | (* 1) | | |
| | Building Floor Plans | | - | | |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | _ | - | - | |

The fire protection systems provided in the building were test checked and found functional at the tire of inspection

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safe required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the De Fire Service Rules 2010/ issue shortcomings as noted at serial numbers

1

(E)

Signature of the Inspecting Officer

Name R. K. DAHIYA

Designation ASSTT DIV. OFFICER

Signature of the Inspecting Officer

Name

Designation