GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE; NEW DELHI-110 001.

No. 66/065/005/school/2011/2654

Dated: 2 / /10/1/

FIRE SAFETY CERTIFICATE

Certified that the MC Primary Boys School located at Nangal Thakran, Delhi110039 comprised of ground floor only and less than 9 meters in height, have complied with the fire prevention and fire safety requirement to accordance with Director of Edcuation circular dated 01.03.2001 and verified by the officer concerned of fire service on 12.09.2011 in the presence of Mrs. Kavita, Teacher Incharge and that the building/premises is fit for occupancy class Educational class with effect from __21/10011/1 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Chief Fire Officer Delhi Fire Service

MRS. KAVITA, TEACHER INCHARGE, MC Primary Boys School, Nangal Thakran, Delhi-110 039

Copy to:

The Director, Kashmiri Gate, Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

ole

	INSPEC	TION REPORT			
	Jetails of previous NOC Not Letter Details of previous NOC Not Letter Fire Safety directives letter No Date of inspection Name of the Inspecting Officers Name and designation of officers from the building side	Tasc/Renewal No. E-16/Estate/cc/	Date	d	
1	10 Applicant's letter No.	11L dated 18.08-2011			
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	 Road width Gate width Width of internal road 	Acceable	6 meters	MIR	
2	Number, Width, Type & Arrangement	of Exits N. A.	C	- 4	
	 a Number of staircases Upper Floors Basements Width of staircases Upper Floors Basements Protection of exits Fire check door Pressurization No of continuous staircases to terrace 		GROUND Flor	HC UNLY	
	g Width of Corridor h Door Size	la cm.	lio cum	to d	

	_				
3	Compartmentation.	N.A.			
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 				
4	Smoke Management System.	N.A.			
	Basements Upper floors	30 a/c per hour 12 a/c per hour			
5	Fire Extinguishers				
	 Total numbers Types IS marking 	ISI marked	4 (Four 3 - ABC 1 - CO2	MIR	
	First-Aid Hose Reels.	N.A.	1- 002		
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m			
	Automatic fire detection and alarming system.				
	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 				
	MOEFA				
	Public Address System. Automatic Sprinkler System. Basement	N/K N·A	Provided		

	Upper Floor Sprinkler above false ceiling	
11	Internal Hydrants	N.A.
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	
12	Yard Hydrants.	N.A.
	Total number of hydrants Hose Box	
13	Pumping Arrangements.	N.A.
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	
14	Captive Water Storage for fire fighting	. N.A.
	Underground tank capacity Draw-off connection	

	 Fire service inlet Access to tank Overhead Tank capacity 			
15	Exit Signage.	NI	Provided	-
1.6	Provision of Lifts.	N.A.	110.1005	
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 			
17	Standby power supply	NA.		
1.8	Refuge Area.	N.A.		
	➤ Total Area ➤ Location			
19	Fire Control Room	M·A -		
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 			
20	Special Fire Protection Systems for Protection of special Risks, if any	-		

The fire protection systems provided in the building were test checked and found functional at the time of inspection

Recping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

1

(E)

Signature of the Inspecting Officer

Name R.K. DAHIYA

Designation A D . D . 0

Signature of the Inspecting Officer

Name

Designation