GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/ons/school/2011/2637 Dated: 21/10/11

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Kanya Vidyalaya at New Seema Puri, Delhi-95. Comprised of ground plus one upper floor owned/occupied by Govt. Sarvodaya Kanya Vidyalaya School have complied with the fire prevention and fire safety requirements in accordance with with the circular issued by the Director of Education dtd.01.03.2011and verified by the officer concerned of Fire Service on 18.09.2011 in the presence of Smt. Shashi Kanta Dass , Principal, of the school and that the building is fit for occupancy class B' Educational Building' with effect from 2.1/1.0. for a period of three years , subject to conditions printed overleaf.

Chief Fire Officer Delhi Fire Service

OK (Sep) 10.11

To.

Principal Govt. Sarvodaya Kanya Vidyalaya New Seema Puri, Delhi-95

Copy:-

- The Joint Director of Education (Land & Estate)
 Directorate of Education,
 Lucknow Road, Delhi -54.
- Principal
 Govt. Sarvodaya Bal Vidyalaya
 New Seema Puri, Delhi-95

CONDITIONS:

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

h. Door Size

	INSPEC	TION REPORT				
1. Nam	e & address of the building :S.)	K.V New Se	ema Puri,	Delhi		
2. Type	1-1-1-1					
3. Type						
4. Deta	The second secon					
5. Fire						
6. Date	of inspection	18/9/11	- 01			
7. Nam	ne of the Inspecting Officers:) o Viscus	rg Si			
8. Nam	ne and designation of officers	2 8				
from	the building side	Smit. Shapl	i Kanta Da	8s (Prin		
9. Year	of Construction :	2008	100 100	al.		
10. Appl	icant's letter No. :	KU NSPINGI	delice and the same of the same	07/11		
	Minimum Standards on fire evention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR		
1 Acces	Access to building					
	Road width	6 M	6 M	MR		
	Gate width					
0	Width of internal road	-				
2 Num	ber, Width, Type & Arrangement	of Exits				
a. Nu	mber of staircases	2 NO.	3 No	MR		
	Upper Floors	2 No .	3 No -	MR		
	Basements			-		
b. Wi	dth of staircases	1.5 M.	1.5 M	MR		
	Upper Floors	1.5 M	1.5 M	MR		
	Basements					
c. Pro	otection of exits	1	1	1		
	Fire check door					
	Pressurization	1		/-		
e. No	of continuous staircases to terrace		/			
1	idth of Corridor	1. CM	1.CM	MR		

3	Compartmentation.			
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 			
4	Smoke Management System.		1	
	Basements Upper floors	30 a/c per hour 12 a/c per hour		
5	Fire Extinguishers			
	Total numbersTypesIS marking	ISI marked	10 NO 1 MR ABCICOZ MR Provided MR	
6	First-Aid Hose Reels.		Provided MR	
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m		
7	Automatic fire detection and alarming system.			
24	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 			
M	IOEFA			
	ublic Address System.			
A	utomatic Sprinkler System.			
	Basement			



	 Upper Floor Sprinkler above false ceiling 	
11	Internal Hydrants	1
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	
12	Yard Hydrants.	
	 Total number of hydrants Hose Box 	
13	Pumping Arrangements.	
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	
14	Captive Water Storage for fire fighting	. /
	 Underground tank capacity Draw-off connection 	

	 Fire service inlet Access to tank Overhead Tank capacity 				
15	Exit Signage.				
16	Provision of Lifts.				
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 				
17	Standby power supply				
18	Refuge Area.				
	➤ Total Area ➤ Location				
19	Fire Control Room				
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 				
20	Special Fire Protection Systems for Protection of special Risks, if any:				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/-issue shortcomings as noted at serial numbers.

(5)

Submitted Alease.

Signature of the Inspecting Officer

Name

VIRENDRA SINCOH

Designation

D. D (E)

Signature of the Inspecting Officer

Name

Designation