## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/0F5/ms/3chool/2011/2638 Dated: 21/10/11

## FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

20.10.11

To.

Principal
Govt. Co-Ed Sec.School
GH Block,Old Seema Puri,Delhi-95

Copy:-

The Joint Director of Education (Land & Estate)
Directorate of Education,
Lucknow Road, Delhi -54.

## CONDITIONS :

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

	PECTION REPORT			
<ol> <li>Type of Case : Ne</li> <li>Details of previous NOC : Le</li> <li>Fire Safety directives letter No : A.</li> <li>Date of inspection :</li> <li>Name of the Inspecting Officers :</li> <li>Name and designation of officers from the building side :</li> <li>Year of Construction :</li> </ol>	ew Case/ Renewal  Itter No. NL  -16 Estate   Cal Fs    -18   09   1  Do VIS  Mr. R-S	Date Date 2011/3298 to 3399. endra single (Pr	ed: N/C	
S. Minimum Standards on fire No. prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
Access to building				
<ul> <li>Road width</li> <li>Gate width</li> <li>Width of internal road</li> </ul>	6 M 4.5 M	6 M -	MR	
Number, Width, Type & Arrangeme	unt of F-its			
<ul> <li>a. Number of staircases</li> <li>Upper Floors</li> <li>Basements</li> <li>b. Width of staircases</li> </ul>	2 No. 2 No.	3 NS	MR MR	
<ul> <li>Upper Floors</li> <li>Basements</li> <li>Protection of exits</li> <li>Fire check door</li> <li>Pressurization</li> </ul>	1.5 M	1.5 M 1.5 M PA NA	MR MR	
e. No. of continuous staircases to terrace	e	Not Enquired		
g. Width of Corridor	1.5 M	1.5 m	MR	

1.0 M

h. Door Size

MR

			_		
3	Compartmentation.				
	Fire check door	-	NA		
	<ul> <li>Sealing of electrical shafts</li> </ul>	-	NA	-	
	Fire Rating of shaft door		NA		
	Water Curtain		NA	===	
	Fire Dampers		NA		
4	Smoke Management System.				
	Basements     Upper floors	30 a/c per hour 12 a/c per hour	NA		
	And the second s		MA	-	
5	Fire Extinguishers				
	Total numbers	9 No-	dro	MR	
	• Types		ABCR CO2	MR	
	IS marking	ISI marked	18\$ Mask	MR	
6	First-Aid Hose Reels.				
	Total numbers on each floor	Not executed	Not exeguist		
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	-11 -	-	
	Nozzle diameter	5 mm	- 11-	+	
7	Automatic fire detection and alarming system.				
	Type of detectors		AN	-	
	Location of Main Panel		NA		
	Location of Repeater Panel		ar		
	Alternate source of power		NA	===	
	Hooters' Location		H A		
3	MOEFA	2	Not Haquice		
)	Public Address System.		Not required		
0	Automatic Sprinkler System.		- H4 -		
	Basement		NA	الفسنوا	

	• Upper Floor		MA		
	Sprinkler above false ceiling	_	410		
1 I	nternal Hydrants				
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>		Hot required	(	
			Hot sequical		
		_	= (1 -		
12	Yard Hydrants.				
	Total number of hydrants	1:	Not Ecquiso		
	Hose Box	-	- 11 -		
13	Pumping Arrangements.				
	Ground Level	<b>=</b>	Not esquited		
	<ul> <li>Discharge of main Pump</li> </ul>	12-1	11-		
	➤ Head of Main pump		_11		
	> Number of main pumps		t <sub>s</sub>		
	<ul><li>Jockey Pump out put</li><li>Jockey pump head</li></ul>	~	= (v		
			-11 -		
	> Standby Pump out put		e II e		
	<ul> <li>Standby Pump Head</li> <li>Auto Starting/ Manual</li> <li>stopping</li> </ul>		- (1		
		-	- 10 -		
	> Pump House Access		- 11-	-	
	Terrace level		2 h 2	75	
	→ Discharge of pump  → Total Stheman  → Total Sthema		- (1 -		
	<ul> <li>➢ Head of the pump</li> <li>➢ Power Supply</li> </ul>		- 4 -		
	> Auto Starting of pump		- h -		
14	Captive Water Storage for fire fighting.				
4.0	Underground tank capacity	-	Not required		
	> Draw-off connection		-1 -		

	<ul> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>		Not sequies	_	
			- 1 -		
15	Exit Signage.		-11		
16	Provision of Lifts.		Not require		
	Pressurization of Lift Shaft		welster		
	<ul> <li>Pressurization of Lift lobby</li> </ul>		NA		
	Communication In lift Car		M		
	Fireman's Grounding Switch     Lift Signage	-	NA		
	Lift Signage		NA		
17	Standby power supply		Not enquired	_	
18	Refuge Area.				
	> Total Area	_	not required	_	
1.0	> Location	-	- 0		
19	Fire Control Room				
	Detector System Panel	_	pot sequired	-	
	<ul> <li>Flow Switch Panel</li> </ul>		-14	_	
	PA System Panel	-	- V -	_	
	Batter backup	==	× 11 =	-	
	Building Floor Plans		tr	-11 -	
20	Special Fire Protection Systems for Protection of special Risks, if any:		Not required	-	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of the Inspecting Officer

Name VIRENDRA SINGY

Designation

DO

Signature of the Inspecting Officer

Name

Designation