FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No: F6/OF5/MS/2011/2727

Dated: 2 8 /10/11

FIRE SAFETY CERTIFICATE

Certified that the "369 Banquet and Lounge" located at 33/33A, Rama Road, New Delhi-110015 comprised of basement, ground floor and two upper floors have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules. 2010 and verified by Sh. Sunil Chaudhaury Divisional Officer of this department on 19-10-11 in the presence of Shri Sumit Ajwani were present at the time of inspection and that the building/premises is fit for occupancy (Tass D (Assembly-Banquet) with effect from - 2 - 110-11 - for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the condition under rule 38 of the Delhi Fire Service Rules. 2010.

Chief Fire Officer
For Director
Delhi Fire Service

Copy to:

- The Deputy Health Officer, MCD, Health Department, Rajouri Garden, New Delhi.
- The Manager, 369 Banquet and Lounge, 33/33 A. Rama Road, New Delhi-110015.

Conditions for the validity of Fire Safety Certificate

- All the means of escape shall be kept free of all type of obstruction all the time.
- b. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- e. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- d. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.
- e. Basement shall be used as per BBL.
- f. This NOC may not be treated in any case for regularizations of unauthorized construction, if any
- g. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

May kindly peruse letter no. nil dated 07.07.11 & reminder sent directly to under signed on 15/09/11 with request to issue NOC in favor of Banquet Hall & Lounge named 369 located at 33/33A Rama Road, New Delhi-110015 this case was dealt earlier by ADO Rajmal Khokhar & DO Than Singh Sharma as per the guidelines issued by M.S. cell now Banquet Hall was re-inspected by undersigned as per the NBC part IV.

1. Name &address of the building

: Banquet Hall & Lounge named 369 located at 33/33A Rama Road ,

New Delhi-110015

2. Type of Occupancy

: Class-D (Assembly)

3. Type of Case

New

4. Details of previous NOC

Letter no. F6/DFS/MS/GH/10/1235 dated 28/4/10

Fire Safety directives letter No.

: N/A

6. Date of inspection

28/06/2011

7. Name of the Inspecting Officers

: DO Sunil Chawdhary

8. Name and designation of officers

From the building side

: Mr. Prem Chawla

9. Year of Construction

NIL

10. Applicant's letter No.

: Nil Dated 30/06/2011

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC IV/ BBL Requirement	Provided at site	Remarks MR/NMR	
1-	Access to building				
	Road width	06 mtrs	60 feets	M.R.	
	Gate width	5 mtrs	5 mtrs	M.R.	
	 Width of internal road 	Abutting 18 mtr road	N/A	M.R.	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases				

	 Basement 	Two	three	M.R.		
	b. Width of staircases					
	Upper Floors	1.5 mtr& 1.25 mtr ,	provided	M.R.		
	Basement	1.25 mtr, 1.25 mtr & 1.5 mtr	provided	M.R.		
	c. Protection of exits	Fire Check door	provided	M.R.		
	Fire check door	Required	Provided	M.R.		
	 Pressurization 	N.R.	N.R.	M.R.		
	d. No. of continuous staircases	two	Provided	M.R.		
	e. Width of Corridor	Halls only	Halls only	M.R:		
	f. Door size	Two doors each 2 mtr wide	Provided	M.R.		
3.	Compartmentation.					
	Fire check door	Required	Provided	M.R.		
	Sealing of electrical shafts	N.A.	N.A.	M.R.		
	Fire Rating of shaft door	N.A.	N.A.	M.R.		
	Water Curtain	N.A.	N.A.	M.R.		
	Fire Dampers	Required	Provided	M.R.		
4.	Smoke Management System.					
	 Basements 	Exhausts fans	Provided	provided		
	Upper floors	Exhausts fans	Provided	Provided		
5.	Fire Extinguishers					
	Total numbers	20	Provided	Provided		
	• Types	A.B.C. & CO2 type	Provided	-		

	IS marking	ISI marked	ISI marked	provided	
6.	First-Aid Hose Rees.				
	Total numbers on each floor	01	Provided	Provided	
	 Length of hose reel hose 	30 m	Provided	provided	
	Nozzle diameter	5 mm	Provided	-do-	
7.	Automatic fire detection and alar	ming system.			
	Type of detectors	Heat & smoke type	Provided	M.R.	
	Location of Main Panel	Ground floor	N/R		
	Location of Repeater Panel	Ground floor	N/R	14 66	
	Alternate source of power	required	Provided D.G. Set 65 KVA	14 14	
	Hooter's Location	N.R	Provided	** **	
8.	MOEFA	N/R	provided	W 11	
9.	Public Address System.	N/R	provided	(40.00)	
10.	Automatic Sprinkler system				
	Basement	required	Provided	M.R.	
	Upper Floor	N.R	Provided	4 4	
	Sprinkler above false ceiling	Required	Provided	394.384	
11.	Internal Hydrants				
	Size of riser/down-comer	4 inch	4 inch	& &	
	Number of hydrants per floor	one	Provided	(46.744.)	

	 Hose Box 	one	Provided	M.R.		
12.	Yard Hydrants.					
	Total number of hydrants	one	Provided	M.R.		
	Hose Box	one	Provided	- LL LL		
13.	Pumping Arrangements.					
	Ground Level					
	 Discharge of main pump 	N.R.	N.R.	M.R.		
	 Head of Main pump 	00 - 60	14	10010		
	Number of main pumps	44: 44	44 144	44 44		
	> Jockey Pump out put	(O.H) 180 LPM	180 LPM	14.144		
	> Jockey pump head	(O.H.) 45 mr	Provided	66. 66		
	> Standby pump out put	(O.H) 2280 LPM	Provided	a. 6		
	 Standby pump Head 	(O.H) 45 mtr	Provided	es te		
	 Auto Starting/Manual stopping 	41- 11	16. 16.	27. 77		
	➤ Pump Hose Access	44. 44	188 200	660 / 660		
	Terrace level					
	 Discharge of pump 	2 x 2280	Provided	M.R.		
	Head of the pump	45 mtr		1120-25		
	Power supply	required	1961(46)	166 - 16		
	Auto Starting of pump	W 10	66 64.	*** 3**		

	Underground tank capacity	N. R. same Capacity	N.P.	M.R.
	Draw -off connection	N.R	(ii ii) V	34. 34
	➤ Fire service inlet	IN.K	** **	11.11
	> Access to tank	N.R	146 768	** **
	Access to talk	N.A		
	Overhead Tank Capacity	50,000	50,000 ltrs	25.25
15	Exit Signage.	N.R.	Provided	M.R.
16.	Provision of Lifts		1	
	Pressurization of Lift Shaft	N.A. , Not Fooder	N.A. Not porri	M.R.
	Pressurization of Lift lobby	44 (44)	66 66	4 44
		44.146	w w	31 31
	Communication In lift Car			
	Fireman's Grounding Switch	14, 35	44 44	155 155
	Lift Signage		ec	3. 4
17.	Standby power supply	N.R	D.G. set 100 K.V.A	36 ,96
18.	Refuge Area	N.R.		
	> Total Area	N.R.	N.R.	M.R.
	➤ Location	N.R.	N.R.	66 66
19.	Fire Control Room	N.R.	N.R.	46. 65
	➤ Detector System Panel	N.R.	N.R.	46. 46.
	➤ Flow Switch Panel	N.R.	N.R.	14.04
	➤ PA system Panel	N.R.	N.R.	86.89
	 Batter backup 	N.R.	N.R.	

	➤ Building Floor plans	N.R.	N.R.	M.R.
20.	Special Fire Protection Systems for Protection of special Risks, if any:	N.R.	N.R.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial number.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Swift (Marchia)

Name

Designation