[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/ms/school/2011/2948

Dated [1/11/11

FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

To

Principal
Govt. Co-Ed. Secondary School
Teliwara, Shahdara, delhi-32

lopy to:-

The Joint Director of Education (Land & Estate) Directorate of Education, Lucknow Road, Delhi -54.

CONDITIONS

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1	Name & address of the building : Sov-	+ co-Ed S	econdry School	
2.	Type of Occupancy Educati	onal 7	eleware Shahadra	Del4-32
3.	Type of Case New Cas	se/ Renewal		
4.	Details of previous NOC : Letter No	r No Dated:		
5				3398
6.	Name of the Inspecting Officers: ADO Suresh Singh Name and designation of officers			
7.				
8.				
	from the building side	Durga 1	Dahiya Vice /	Tincipal
9.	Year of Construction : 20			
10	Applicant's letter No. 547	date	23.9.11.	
S.	Minimum Standards on fire		Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMB
1	Access to building			
	Road width	6 4	7 M	MR
	Gate width	-	3.85 M	-
	 Width of internal road 		-	-
2	Number, Width, Type & Arrangement of Exits			
	a. Number of staircases	2_	2	MR
	Upper Floors	-	-	5-
	Basements	-		7
	b. Width of staircases	1.50	1.48. 1.55 M	MR
	Upper Floors			77-1
	Basements	_	-	-
	c. Protection of exits	-	-	~
	Fire check door	-		B
	 Pressurization 	_	-	-
	e. No. of continuous staircases to terrace		Ho	
	g. Width of Corridor	1.50	1.80	MK
	h. Door Size) H	1 2	MR

			Par-			
3	Compartmentation.	E .	Provided	-		
	Fire check door Sealing of electrical shafts		e			
		-	2			
	Fire Rating of shaft door		-			
	Water Curtain					
	 Fire Dampers 	100	===			
4	Smoke Management System. N/A					
	Basements	30 a/c per hour				
	 Upper floors 	12 a/c per hour	7.			
	1-00			- A		
5	Fire Extinguishers Required.					
	 Total numbers 		8 110	MR		
	Types		1 Co2 7 ABC	MR		
_	IS marking	ISI marked	151	MR		
5		First-Aid Hose Reels.				
	 Total numbers on each floor 			-		
	 Length of hose reel hose 	30 m		_		
	Nozzle diameter	5 mm		-		
1_	Automatic fire detection and alarming system.					
	Type of detectors	-	-	=		
	 Location of Main Panel 	-	-	R		
	 Location of Repeater Panel 	~	_	2.0		
34.5	Alternate source of power	_				
	 Hooters' Location 					
N. T.	MOEFA	NA	-	_		
ų.	Public Address System.	MIA	Provided	MJR		
0	Automatic Sprinkler System.	HIA	y y y y y	OK		
	Basement	Cect A				

	Upper Floor Sprinkler above false ceiling	_		-
	Sprinkler above false ceiling		-	
11	Internal Hydrants	NIA	<u> </u>	-0
	 Size of riser/down-comer Number of hydrants per floor Hose Box 		V	-
		_	-	-
		_		-
12	Yard Hydrants.	+119	~	
	 Total number of hydrants 	-	-	-
	Hose Box	-		7
13	Pumping Arrangements.	MIA		
	Ground Level			-
	Discharge of main Pump		1	_
	➤ Head of Main pump		_	_
	> Number of main pumps		E	
	> Jockey Pump out put	_		-
	 ➢ Jockey pump head ➢ Standby Pump out put ➢ Standby Pump Head ➢ Auto Starting/ Manual stopping ➢ Pump House Access Terrace level ➢ Discharge of pump 	-		-
			-	2-
			-	-
		_	=	*:
		-	-	-
			_	-
	> Head of the pump			~
	➢ Power Supply			~
	> Auto Starting of pump	_	1 2 2	-
14	Captive Water Storage for fire fighting.	NIA		
	Underground tank capacity	-		
	> Draw-off connection	_		-

	> Fire service inlet			-
	> Access to tank	-	- 25	
	 Overhead Tank capacity 			55
15	Exit Signage.	HIA	241	
16	Provision of Lifts.	NIA .		
	Pressurization of Lift Shaft		9=	-
	Pressurization of Lift lobby	(-	=	1 5
	Communication In lift Car	-	-	-
9	 Fireman's Grounding Switch 	_	-	~
	• Lift Signage	-	15	-
17	Standby power supply			
18	Refuge Area.	141A	% =:	-
	> Total Area	-	_	-
	> Location	-	-	=
19	Fire Control Room	NIA		
	Detector System Panel	-	ine.	-
	 Flow Switch Panel 	_	- Table	-
	PA System Panel			-
	Batter backup	4		-
	Building Floor Plans			-
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA		-

The fire protection systems provided in the building were test checked and found functional at the tof inspection.

Stam

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name Samesh Int

Name

Designation Ap v

Designation