## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFS/ms/sch-of/2011/1871

Dated: 04 / 11 / 11

## FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

To.

Principal
Govt.Girls Sr.Sec School No.-1
B Block, Yamuna Vihar, Delhi-53.

Copy:-

The Joint Director of Education (Land & Estate)
 Directorate of Education,
 Lucknow Road, Delhi -54.

 Principal Govt.Boys Sr.Sec School No.-1 B Block, Yamuna Vihar, Delhi-53.

## CONDITIONS

- \*. All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

## INSPECTION REPORT

L	Name & address of the building : Co	ut. airls sr. see.	School No.T RI	bck-R	
2	Type of Occupancy	Educational		what when Bell	
3	A T TAC	w Case/ Renewal-			
4	- States of brotions two	ter No	Date	lua be	
5	File Safety directives letter No F-	16 Estate/ce/Fr/2	-11/12/98 to 329	8 dt 1.3-11	
6	5. Fire Safety directives letter No F-16 Estate   Cc   F5   2-11   3298 to 3398 dtd 1.3.  6. Date of inspection 20.09.11				
7	7 Name of the Inspecting Officers: Do Visculary Singh				
8.	Name and designation of officers				
	from the building side	Dr. y. Mark	ca (Principa	1)	
	Year of Construction	1998		9	
10	Applicant's letter No.	NIC old	30/7/11		
S. No	Minimum Standards on fire prevention and fire safety U/R 33	Circi lar Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	<ul> <li>Road width</li> </ul>		6 M	MR	
	<ul> <li>Gate width</li> </ul>			2	
	<ul> <li>Width of internal road</li> </ul>				
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	5 No.	5 No.	MR	
	<ul> <li>Upper Floors</li> </ul>	5 M.	5 No /	MR	
	<ul> <li>Basements</li> </ul>				
	b. Width of staircases	1.5 m	1.5 M	MR	
12	Upper Floors	1.5 M	1.5 M	MR	
	<ul> <li>Basements</li> </ul>				
	c. Protection of exits				
	Fire check door	4			
	<ul> <li>Pressurization</li> </ul>				
	e. No. of continuous staircases to terrac	e			
	g Width of Corridor	1.5 M	1.5 M	MR	
	h. Door Size	1.0 M	110 M	MR	

3				1	
3	Compartmentation.				
	Fire check door				
	<ul> <li>Sealing of electrical shafts</li> </ul>			3	
	<ul> <li>Fire Rating of shaft door</li> </ul>				
	Water Curtain	1		-	
	Fire Dampers	29			
1	Smoke Management System.				
	<ul> <li>Basements</li> </ul>	30 a/c per hour	1	1	
	Upper floors	12 a/c per hour	13 July 1		
				(	
5/	Fire Extinguishers				
	Total numbers	15 No.	24. No	MR	
	Types	===	ABC LCO2	MR	
	IS marking	ISI marked	121	MR	
5	First-Aid Hose Reels.				
	<ul> <li>Total numbers on each floor</li> </ul>		1	1	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	. /		
	<ul> <li>Nozzle diameter</li> </ul>	5 mm		1	
7	Automatic fire detection and alarming system.				
	Type of detectors	1	/	1	
	Location of Main Panel				
			-		
	Doublett of Repeater 1 affect				
19	Alternate source of power			1	
	Hooters' Location				
	MOEFA	1	1	1	
	Public Address System.				
0	Automatic Sprinkler System.				
	Basement		1	1	

dh

570	Upper Floor     Sprinkler above false ceiling		/	1		
11	Internal Hydrants					
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants per floor</li> <li>Hase Box</li> </ul>					
12	Yard Hydrants,					
	Total number of hydrants Hose Box					
13	Pumping Arrangements.	1. /				
	<ul> <li>Ground Level</li> <li>Discharge of main Pump</li> <li>Head of Main pump</li> <li>Number of main pumps</li> <li>Jockey Pump out put</li> <li>Jockey pump head</li> <li>Standby Pump out put</li> <li>Standby Pump Head</li> <li>Auto Starting/ Manual stopping</li> <li>Pump House Access</li> <li>Terrace level</li> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power Supply</li> <li>Auto Starting of pump</li> </ul>					
14	Captive Water Storage for fire fighting.					
	Underground tank capacity  Draw-off connection					

THE RESERVE OF THE PARTY OF THE	
STIER STEEL	Ď.
<b>第1</b> 3757	
國語言語	
1,5% T.	

	<ul> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>				
15	Exit Signage.				
16	Provision of Lifts.				
	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> </ul>			1	
17	Standby power supply	,	1	1	
18	Refuge Area.				
	➤ Total Area > Location				
19	Fire Control Room				
	<ul> <li>Detector System Panel</li> <li>Flow Switch Panel</li> <li>PA System Panel</li> <li>Batter backup</li> <li>Building Floor Plans</li> </ul>				
20	Special Fire Protection Systems for Protection of special Risks, if any:				

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sa required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the I Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name VIRENDRA SINGH

Designation De (East)

Signature of the Inspecting Officer

Name

Designation

dh

1