GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : CONNAUGHT LANE NEW DELHI-110 001.

No. F6/0 FS/015/school/2011/2995

Dated: 16/11/11

FIRE SAFETY CERTIFICATE

Certified that the GOVT. SARVODAYA CO-ED. VIDYALAYA located at, Sector-8, Rohini, Delhi-110 085, comprised of five blocks i.e. A,B,C,D & E block. A,B & E block consist of ground floor only and C & D block consist of ground plus one upper only and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Director of Education circular dated 01.03.2001 and verified by the officer concerned of fire service on 24.09.2011 in the presence of Shri Sushil Kumar, Principal and that the building/ premises is fit for occupancy class Educational class with effect from \(\frac{16}{11} \) \(\frac{11}{11} \) for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ______at New Delhi by

Chief Fire Officer Delhi Fire Service

MCAH

Shri Sushil Kumar, Principal, GOVT. SARVODAYA CO-ED. VIDYALAYA, Sector-8, Rohini, Delhi-110 085...

Copy to:

The Director,
Dte. Of Education,
Old Sectt., Delhi,

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

INSPECTION REPORT Name & address of the building Gort. Sarvodays Co-ed Vedyalays, Sec. 8. Rolm Type of Occupancy School 3 Type of Case New Case/ Renewal 4 Details of previous NOC NA Letter No. 5. Fire Safety directives letter No. F. 16 Estate Cc Fin Safety 2011 3298.3798 St. 13.11 6 Date of inspection 24.09-2011 7 Name of the Inspecting Officers SHRI R.K. DAHIYA, ASO 8. Name and designation of officers from the building side N.A. 9. Year of Construction 1987 Applicant's letter No. GS CO-Ed V 8 R /343 25.09.11 Lated Minimum Standards on fire S. NBC Provided at site Remarks No. prevention and fire safety U/R 33 Requirement MR/NMR Access to building Road width Accepted 12 meters Gate width 6 Helis Width of internal road Number, Width, Type & Arrangement of Exits a Number of staircases Three Three Upper Floors One apportant Basements b Width of staircases Lowerd 150 cm eath Upper Floors Same as above Basements c. Protection of exits N-A · Fire check door Pressurization e. No of continuous staircases to terrace 3 Stawcases

2 melers

100 cme each

g Width of Corridor

h Door Size

	_					
3	Compartmentation.	NA.				
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 					
į	Smoke Management System.	N.A				
	Basements Upper floors	30 a/c per hour 12 a/c per hour		2		
Š	Fire Extinguishers					
	Total numbersTypes		25 ABC & CO2	W J D		
0	IS marking	ISI marked	700	11/		
	First-Aid Hose Reels.					
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m				
	Automatic fire detection and alarming system.					
	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	September 1				
t	MOEFA	at A				
-	Public Address System. Automatic Sprinkler System.	NIR	Provided			
	Basemoni	CONTRACTOR NO	NA.			

	Upper Floor Sprinkler above false ceiling	
11	Internal Hydrants	N.A.
	Size of riser/down-comer Number of hydrants per floor Hose Box	
12	Yard Hydrants.	4.U)
	Total number of hydrants Hose Box	
13	Pumping Arrangements.	N.A
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level 	
	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	
14	Captive Water Storage for fire fighting.	N-A
	Underground tank capacity Draw-off connection	

	 Fire service inlet Access to tank Overhead Tank capacity 			
15	Exit Signage.	AV / AVA		
16	Provision of Lifts.	- MIL	Provided	
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 		N A,	
17	Standby power supply			
1.8	Refuge Area.		N.A	
	Total AreaLocation		N.A.	
9	Fire Control Room		Paris a	
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 		N.A.	
S	pecial Fire Protection Systems for rotection of special Risks, if any:	-		

The fire protection systems provided in the building were test checked and found functional at the tire of inspection

Reeping in view the substantial compliance of the minimum standards on fire prevention and fire sa required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the 1 Fire Service Rules 2010/ issue shortcomings as noted at scrial numbers

(S-)

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name R.K. DAHIYA

Name

Designation ASSTT. DIV. OFFICER

Designation