## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFs/ans/ school/2011/3006

Dated 16/11/11

## FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

To,

Principal Nagar Nigam Prathmic Vidyalaya Vivek Vihar Ph-2, Shahdara Delhi-95

Copy to:-.

The Director of Education, MCD,Nigam Bhawan, Kashmiri Gate, Delhi.

## CONDITIONS:

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www,dfs.delhigovt.nic.in

## INSPECTION REPORT

Į	Name & address of the building : / / R Type of Occupancy	gar Nigam P	ralhmic vidrals	virele
2	Type of Occupancy Edu	cetonal with	ar phyc-2 Shel	uolar- 95
3	Type of Case : New (	lase/Renewal		
4	Details of previous NOC : Letter	No	Date	d: —
5	Fire Safety directives letter No : 8-16	Estate   cc   Fr	e Safety / 2011/ 829	9 to 321 P
:6	Date of inspection : 31-1	0. 204	deted 1-8	2014
7			yol	
8	Name and designation of officers			1
	from the building side	Suraksky K	ani Principo	e
9	Year of Construction :/			
10	Applicant's letter No.	NII dated	21-9-2421	
S.	Minimum Standards on fire		Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMI
1	Access to building			
	<ul> <li>Road width</li> </ul>	64	6.5 M	MR
	Gate width		3.80	2
	<ul> <li>Width of internal road</li> </ul>			ie-
2	Number, Width, Type & Arrangement	of Exits .	2- 5	
	a. Number of staircases	-	_	-
	Upper Floors	-		
	Basements	-	~	-
	b. Width of staircases	_	-	50
- 51	<ul> <li>Upper Floors</li> </ul>			
1	Basements			
	c. Protection of exits			1 2 2 2
	Fire check door			
	Pressurization			
	e. No. of continuous staircases to terrace			
Ì	g Width of Corridor			
	h. Door Size	1 14	1 17	MR

			-5.5		
			Provided		
3	Compartmentation.	1/2		- 4	
	Fire check door		-	-	
	<ul> <li>Sealing of electrical shafts</li> </ul>		-	-	
	<ul> <li>Fire Rating of shaft door</li> </ul>				
	Water Curtain	-	N ~	-	
	Fire Dampers		155	2007	
4	Smoke Management System.	HIA			
	Basements	30 a/c per hour		-	
	Upper floors	12 a/c per hour	7.00		
				55.	
5	Fire Extinguishers Regarde-				
	<ul> <li>Total numbers</li> </ul>	2	2	HR	
	Types		ABO	MR	
	<ul> <li>IS marking</li> </ul>	ISI marked	151	MR	
6	First-Aid Hose Reels.				
	<ul> <li>Total numbers on each floor</li> </ul>		-	-	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m			
	Nozzle diameter	5 mm	-		
7	Automatic fire detection and alarming system.				
	<ul> <li>Type of detectors</li> </ul>	-		-	
	Location of Main Panel			1-	
	<ul> <li>Location of Repeater Panel</li> </ul>			_	
8	Alternate source of power			-	
	Hooters' Location		1111		
8	MOEFA	NA	-	-	
9	Public Address System.	HIA	-	-	
10	Automatic Sprinkler System.	NIA			
	Basement				

88	Upper Floor				
	Sprinkler above false ceiling				
	Internal Hydrants	HIA			
	Size of riser/down-comer	-	-		
	<ul> <li>Number of hydrants per floor</li> </ul>	-		+	
	Hose Box	-	-		
2	Yard Hydrants.	7114			
	Total number of hydrants	_	-	~	
	<ul> <li>Hose Box</li> </ul>	_	-	-	
3	Pumping Arrangements.				
	Ground Level	-	-		
	> Discharge of main Pump	-	100	=	
	> Head of Main pump	-			
	> Number of main pumps		-	-	
	> Jockey Pump out put	-		-	
	> Jockey pump head	_	-		
	> Standby Pump out put		-	-	
	> Standby Pump Head		-	72=	
	> Auto Starting/ Manual stopping			22	
	> Pump House Access	_		-	
	Terrace level	-		( E)	
	> Discharge of pump	Here:		-	
	> Head of the pump				
	<ul><li>➤ Power Supply</li><li>➤ Auto Starting of pump</li></ul>				
1	4 Captive Water Storage for fire fighting.				
1	Underground tank capacity		-		
	> Draw-off connection				

3	> Fire service inlet			1	
	<ul> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>				
15	Exit Signage.	NIA	-	~	
16	Provision of Lifts.	MA			
	Pressurization of Lift Shaft		-	-	
	<ul> <li>Pressurization of Lift lobby</li> </ul>	-	-	-	
	Communication In lift Car		-	-	
*	<ul> <li>Fireman's Grounding Switch</li> </ul>	-	<u>v.</u>	w.:	
	Lift Signage	-	-		
17	Standby power supply	KIA			
18	Refuge Area.				
	➤ Total Area	11/2	•		
	> Location			( To 1	
19	Fire Control Room & 16.				
	Detector System Panel		. %		
	Flow Switch Panel	-			
	<ul> <li>PA System Panel</li> </ul>		- ( <del>-</del>		
	Batter backup			F-12	
	Building Floor Plans			-	
20	Special Fire Protection Systems for Protection of special Risks, if any:	NH			

The fire protection systems provided in the building were test checked and found functional at the to of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sarequired under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the D-Fire Service Rules 2010/ issue shortcomings as noted at serial numbers......

Sangh

Signature of the Inspecting Officer

Name

Syrack Suga

Designation

ADO

Signature of the Inspecting Officer

Name

Designation

OSAKA