GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DF5/015/ School/2011/2972

Dated 15/11/11

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Government Kanya Vidyalaya Block-13, Geeta Colony, Delhi-31. Comprised of ground plus one upper floor owned/occupied by Sarvodaya Government Kanya Vidyalaya Block-13, Geeta Colony, Delhi-31, have complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education dated 01.03.2011 and verified by the officer concerned of Fire Service on dated 22.10.2011 in the presence of Mr. S.S. Lal, Incharge of the school and that the building is fit for occupancy class B' Educational Building' with effect from And Andrew Land Conditions printed overleaf.

Issued on _________at New Delhi by

Chief Fire Officer Delhi Fire Service

To

Principal Sarvodaya Government Kanya Vidyalaya, Block-13, Geeta Colony, Delhi-31

Copy to:-

The Joint Director of Education (Land & Estate) Directorate of Education, Lucknow Road, Delhi -54.

CONDITIONS:

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1_	Name & address of the building : Sarvo	drya Forerym	ent Kanya vidy	alg	
2	Type of Occupancy Educ		Block 13 Feet	a Calony Delhe-31	
3.	Type of Case : New Co	ase/ Renewat			
4	Details of previous NOC Letter N	ious NOC Letter No Dated:			
5.	5. Fire Safety directives letter No : F-16 / Estate / CC / Fire Safety / 2011 / 3298 to 5. Date of inspection 22-10-2011				
6.					
7					
8.	Name and designation of officers				
	from the building side S.S	. lal Inch	arge	14	
9.	Year of Construction : 20	10	41,		
10	Applicant's letter No.	11 dated 1	9.9.11		
S.	Minimum Standards on fire	-	Provided at site	Remarks	
No	prevention and fire safety U/R 33	Requirement		MR/NMR	
1	Access to building				
	Road width	6 M	12 M	MR	
	 Gate width 	-	3. COM	MR	
	 Width of internal road 				
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	5	5	MR	
	Upper Floors		_	-	
	 Basements 	-		-	
	b. Width of staircases	1. 5	4 No. 1.45	MR	
100	 Upper Floors 				
	• Basements	-	-	-	
	c. Protection of exits	-		7=	
	 Fire check door 	1	-	-	
	Pressurization	-	-	-	
	e. No. of continuous staircases to terrace	_	No	-	
	g. Width of Corridor	1.5 4	2.70. 1.55#	MR	
	h. Door Size	1 2	I M	MR	

3	Compartmentation.		frovided		
	Fire check door		-		
	Sealing of electrical shafts	~	-	-	
	Fire Rating of shaft door Water Curtain			-	
	Water Cultain	1	F4-1		
	• Fire Dampers		-		
4	Smoke Management System.				
	BasementsUpper floors	30 a/c per hour 12 a/c per hour		-	
			10	10	
5	Fire Extinguishers Required.				
	 Total numbers 		16 NO	MR	
	Types		2 C=2 , 14 ABC	MR	
	IS marking	ISI marked	151	MR.	
6	First-Aid Hose Reels.				
	 Total numbers on each floor 		**	-	
	 Length of hose reel hose 	30 m		-	
	Nozzle diameter	5 mm		127	
7	Automatic fire detection and alarming system.				
	Type of detectors	-		24	
	 Location of Main Panel 		_		
	Location of Repeater Panel	_	-		
	Alternate source of power			-	
	Hooters' Location	122 11	-	,	
3	MOEFA	NA	20	-	
)	Public Address System.	NA	-	-	
10	Automatic Sprinkler System.				
	Basement	-	<u></u>		

S R

	T.I. and the second				
	 Upper Floor Sprinkler above false ceiling 			-	
		_		#	
11	Internal Hydrants				
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	-	*	-	
		_=		=	
		-	-	- 2	
12	Yard Hydrants.				
	 Total number of hydrants 	i e	-	-	
	Hose Box	=		.5	
13	Pumping Arrangements.				
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply 	-	-	*	
				-	
		-	2-	-	
			-	-	
			-	~	
		_	-	~	
			-	-	
		10 To	-		
		-		7 - 4	
		-	-	121	
		_	-	-	
				-	
		===	155	==	
	> Auto Starting of pump	(2 ==	_	=	
14	Captive Water Storage for fire fighting.				
	· • Underground tank capacity	-	-	=	
	> Draw-off connection	_			

	> Fire service inlet	-	-	_
	 Access to tank Overhead Tank capacity 	-		
15	Exit Signage.	NA	-	-
16	Provision of Lifts.	NA		
	Pressurization of Lift Shaft	_	-	~
	 Pressurization of Lift lobby 		-	
	Communication In lift Car	1	-	
41	Fireman's Grounding Switch	-	-	-
	Lift Signage	1 50	-	
17	Standby power supply	MIA	-	-
18	Refuge Area.			
	> Total Area	-		
İtarik	> Location			
19	Fire Control Room			
	Detector System Panel			121
	 Flow Switch Panel 	-	#	-
	 PA System Panel 		-	
	Batter backup	-		
	Building Floor Plans		402	
20	Special Fire Protection Systems for Protection of special Risks, if any:	MA	-	~
20	Special Fire Protection Systems for	HA		

The fire protection systems provided in the building were test checked and found functional at the t of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sa required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the D Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

South

Signature of the Inspecting Officer

Name

Suresh Sugh

Designation A Do

Signature of the Inspecting Officer

Name.

Designation