FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE
[SEE SUB-RULE (1) OF RULE 35]

OVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI
HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. 66/0 FS/ms/ EH/2011/2888

Dated: 04/ 11/2011

FIRE SAFETY CERTIFICATE

Issued on.....at New Delhi by

Chief Fire Officer
For Director
Delhi Fire Service

Copy to: Sh. Pardeep Jain (Manager) Cavendish Banquet & Restaurant D-4, Udyog, Nagar, Near Peera Garhi Chowk, New Delhi-110041

Note: For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time.
- Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs. delhigovt. nic.in

May Kindly peruse letter no. nil dated 08-08-2011 received from Authorized signatory Cavendish Banquet Hall, requesting to issue NOC from fire safety point of view in favor of Cavendish Banquet & restaurant. Inspection was carried out and observed that building is comprised of basement, ground, first floor, terrace is covered with fiber sheet & is used for kitchen, pumps, cooling tower etc. ground floor is used for banquet & upper floor is for restaurant each floor measuring 1316.49 sq mtr out of which 805.518 sq mtr at ground & 797.419 sq mtr at first floor is used for banquet & restaurant respectively.

Name &address of the building : Cavendish Banquet & restaurant located at D-4, Udyog, Nagar,

Near Peera Garhi Chowk, New Delhi-110041.

2. Type of Occupancy : Cass D (Assembly)

Type of Case : Renewal

Details of previous NOC
 F6/DFS/96/45, F6/MS/DFS/2007/EN/1318 dated 10-052007

Fire Safety directives letter No. : F6/DFS/MS/BP/2011/1338 dated 30-06-11

6. Date of inspection : 06.10.2011

7. Name of the Inspecting Officers : Division Officer Sunil Chowdhary

8. Name and designation of officers

From the building side : Sh. Pardeep Jain (Manager)

9. Year of Construction : 1996

10. Applicant's letter No. : nil dated 08-08-2011

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR		
1.	Access to building					
	Road width	06mtrs	30 mtr	M.R -		
	Gate width	4.5 mtr	5 mtr	M.R		
	Width of internal road	15.2"	provided	M/R		
2.						
	a. Number of staircases	Two	Provided /	M.R.		
	Upper Floors	Two	Provided	M.R.		

	Basement	Two	Provided	M.R.
	b. Width of staircases	1.5 mtr	Provided	M.R.
	Upper Floors	1.5 mtr	Provided /	M.R.
	Basement	1.5 mtr	Provided /	M.R.
	c. Protection of exits			
	Fire check door	Required	Provided	M.R
	Pressurization	N.R	N.R	M.R
	d. No. of continuous staircases to terrace	Two	provided /	M.R
	e. Width of Corridor	N.R/Halls	N.R.	M.R
	f. Door size	2 mtrs	provided	M.R.
	Compartmentation.			
	Fire check door	Required	Rovided	M.R
	 Sealing of electrical shafts 	Required	No. electrical shafts available	M.R
	Fire Rating of shaft door	required	No. electrical shafts available	M.R
	Water Curtain	N.R.	N.R.	M.R.
	Fire Dampers	required	on Split A.C. are provided /	M.R
N.	Smoke Management System.			
	Basements	Required	Provided	M.R
	Upper floors	Required	Provided	M.R
	Fire Extinguishers			
	Total numbers	20	provided	M.R

	Types	ABC & CO2 type	provided	M.R	
	IS marking	ISI marks	provided	M.R	
5.	First-Aid Hose Rees.				
	Total numbers on each floor	One on each floor	provided /	M.R	
	Length of hose reel hose	30 m	provided	M.R	
	Nozzle diameter	5 mm	provided	M.R	
	Automatic fire detection and alar	ming system.	hi		
	Type of detectors	Smoke & Heat type are required	Provided	M.R	
	Location of Main Panel	Ground floor	Provided	M.R	
	Location of Repeater Panel	Ground floor	Provided	M.R	
	Alternate source of power	Required	provided	M.R	
	Hooter's Location	Required	Provided	M.R	
	MOEFA	Required	Provided	M.R	
	Public Address System.	Required	Provided	M.R	
).	Automatic Sprinkler system				
	Basement	Required	Provided	M.R	
	Upper Floor	Required	Provided	M.R	
	Sprinkler above false ceiling	Required	Provided	M.R	
1.	Internal Hydrants				
	Size of riser/down-comer	150 mm	provided	M.R	
	Number of hydrants per floor	one	provided	M.R	

	Hose Box	required	provided /	M.R	
12.	Yard Hydrants.				
	Total number of hydrants	N.R	N.R.	M.R	
	Hose Box	N.R	N.R.	/ M.R	
13.	Pumping Arrangements.				
	Ground Level	N.R	N.R.	M.R	
	> Discharge of main pump	36 33	w w	61/46	
	> Head of Main pump	14. W	11 00	4 4	
	> Number of main pumps	a u	и и	66 66	
	> Jockey Pump out put	66 16	44 44	8.0	
	> Jockey pump head	u u	** **	wa	
	> Standby pump out put	14 14	14 44	A* 58	
	> Standby pump Head	14. 14	56 - 36	22. 22.	
	 Auto Starting/Manual stopping 	16 46	140.04		
	Pump Hose Access	16 . 56	u u	,, ,,	
	Terrace level				
	 Discharge of pump 	900 LPM	Provided	M.R	
	➤ Head of the pump	40 mtr	Provided	397 39	
	➢ Power supply	Required	Provided	" "	
	> Auto Starting of pump	Required	Provided	,,/	

14.	Captive Water Storage for fire fighting.				
	Underground tank capacity	One lack	provided	M.R.	
	Draw -off connection	required	64.39	66 31	
	➤ Fire service inlet	u. 11	££ 33	66-20	
	> Access to tank	(22)99	.66.77	46.55	
	 Overhead Tank Capacity 	Required 20,000 ltr	20,000 ltr	M.R	
15	Exit Signage.	Required	Provided	M.R	
16.	Provision of Lifts				
	Pressurization of Lift Shaft	N.A.	N.A.	M.R	
	Pressurization of Lift lobby	33.33	33.95	** **	
	Communication In lift Car	511 11	39 35	99.192	
	Fireman's Grounding Switch		39.39	88(98))	
	Lift Signage		27 15	11 11	
17.	Standby power supply	Required	60 K.V.A.	M.R	
18.	Refuge Area	N.R.	N.R	M.R	
	> Total Area	***		** **	
	> Location	25.23	21 22	11 17	
19.	Fire Control Room				
	 Detector System Panel 	N.R.	N.R.	M.R	
	➤ Flow Switch Panel	N.R.	N.R.	M.R	

		The second secon	14.0
➤ PA system Panel	Required	Provided	M.R
	и. 11	66.37	M.R
> Batter backup	44 - 44	55, 33	M.R.
➤ Building Floor plans		-	
20. Special Fire Protection Systems for	N.R.	N.R.	M.R.
Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection officer

Signature of the Inspection Officer

Name Syrik (hawahan)

Designation D-O (MM)

Name

Designation