## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFs/ans/school/2011/3007

Dated: / 6/11/1)

## FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

To,

Principal Nagar Nigam Prathmic Balika Vidyalaya D-Block, New SeelamPur, Shahdara, Delhi-53

Copy to:-.

The Director of Education, MCD,Nigam Bhawan,Kashmiri Gate, Delhi.

## CONDITIONS:

 All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.

 All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

 All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall

be responsible.

 Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This NOC may not be treated in any case for regularizations of unauthorized

construction unauthorized use of land if any.

 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

## INSPECTION REPORT

1. Name & address of the building : Na	tar Nigam	Prathoner Baleka	retainalen	
1. Name & address of the building : Neg 2. Type of Occupancy Educe	Honel DE	book Now Section Po	or Delle-53	
3. Type of Case New (	- CA			
<ol> <li>Details of previous NOC : Letter</li> </ol>	Letter No - Details			
5. Fire Safety directives letter No : F. 16	/ Estate Ice / To	Date Color 12 11 12 a	ed.	
<ul> <li>5. Fire Safety directives letter No</li></ul>	10. 2111	day. 1	98 10 1592	
7 Name of the Inspecting Officers : A	Do Sureth Si	w . P		
Name and designation of officers		190		
from the building side	ani Devi	Principal.		
9 Year of Construction : 2		<i>(</i>		
10. Applicant's letter No.		23. 9. 2011		
Minimum Standards on fire		Provided at site	Remarks	
No. prevention and fire safety U/R 33	Requirement	The state of the s	MR/NMI	
Access to building	15			
<ul> <li>Road width</li> </ul>	6 M	6 H	MR	
<ul> <li>Gate width</li> </ul>		75.8 4		
<ul> <li>Width of internal road</li> </ul>	-			
Number, Width, Type & Arrangement	of Exits			
a. Number of staircases	2	2.	MR	
Upper Floors	1	1		
Basements			MR	
b. Width of staircases	1.54	1.20 M		
Upper Floors	1.5 M	1.80 M	MR	
Basements	1.80	1.80 M	MR	
The state of the s			100	
c. Protection of exits		_		
Fire check door	~		-	
Pressurization				
e. No. of continuous staircases to terrace	4	1	MR	
g Width of Corridor	1.50	2.20 H	MR	
h. Door Size	1 4	1 14	1 2	

3	Compartmentation.	Reguland	Provided	MK	
	<ul> <li>Fire check door</li> </ul>		-		
	<ul> <li>Sealing of electrical shafts</li> </ul>				
	Fire Rating of shaft door			-	
	Water Curtain				
Fire Dampers	Fire Dampers	n===		~	
4	Smoke Management System.				
	<ul><li>Basements</li><li>Upper floors</li></ul>	30 a/c per hour 12 a/c per hour		-	
				-	
5	Fire Extinguishers Required				
	<ul> <li>Total numbers</li> </ul>		4 NO	MR	
	• Types	3.4	ABC. 5kg	HR	
_	IS marking	ISI marked	151	MR	
5	First-Aid Hose Reels.				
	Total numbers on each floor	<u> </u>	-	-	
	Length of hose reel hose	30 m	, e	-	
-	Nozzle diameter	5 mm	-	-	
7	Automatic fire detection and alarming system.				
	<ul> <li>Type of detectors</li> </ul>		-	-	
	Location of Main Panel	-	-	-	
	Location of Repeater Panel		-	-	
* **	<ul> <li>Alternate source of power</li> </ul>				
	Hooters' Location				
	MOEFA	NA			
	Public Address System.	1×A	-		
0	Automatic Sprinkler System.	NA			
	Basement				

	Upper Floor	-		-	
	Sprinkler above false ceiling	-			
1 II	Internal Hydrants N/A				
	Size of riser/down-comer			-	
ŀ	Number of hydrants per floor     Hose Box			-	
			~	-	
12 3	Yard Hydrants.	HA			
	Total number of hydrants		-	* <del>-*</del>	
4	Hose Box			La -	
13	Pumping Arrangements.	HIA			
	Ground Level	-			
	> Discharge of main Pump		-		
	> Head of Main pump	-	-	-	
	> Number of main pumps		-		
	> Jockey Pump out put			67	
	> Jockey pump head	==-,	-		
	Standby Pump out put				
	> Standby Pump Head			-	
	> Auto Starting/ Manual stopping	-			
	> Pump House Access	10-			
	Terrace level	2-		-	
	> Discharge of pump				
	> Head of the pump			100	
	<ul> <li>Power Supply</li> <li>Auto Starting of pump</li> </ul>				
14	LIIA KIIIA				
14.7	Underground tank capacity	-			
	> Draw-off connection				

a

	➤ Fire service inlet	-	-		
	> Access to tank	-		-	
	<ul> <li>Overhead Tank capacity</li> </ul>	T. 10.	<b>5</b> 3	-	
15	Exit Signage.	1214		- 1	
16	Provision of Lifts.	NIA			
	Pressurization of Lift Shaft	-		-	
	<ul> <li>Pressurization of Lift lobby</li> </ul>	_	_	-	
	Communication In lift Car				
15	<ul> <li>Fireman's Grounding Switch</li> </ul>		5	-	
	• Lift Signage	_		1-	
17	Standby power supply	MIA		~	
18	Refuge Area.				
	> Total Area	-	<	-	
	> Location	-			
19	Fire Control Room				
	Detector System Panel				
	Flow Switch Panel				
	<ul> <li>PAi System Panel</li> </ul>	-	-	- Acces	
	Batter backup		-	-	
	Building Floor Plans	-			
20	Special Fire Protection Systems for	NIA	-	=	
	Protection of special Risks, if any:			~	

The fire protection systems provided in the building were test checked and found functional at the toef inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sarequired under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the D-Fire Service Rules 2010/ issue-shortcomings as noted at serial numbers.

South

Signature of the Inspecting Officer

Name Aurest Sugh

Designation 400

Signature of the Inspecting Officer

Name

Designation