GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/ans/school/2011/3005 Dated: 16/11/11

FIRE SAFETY CERTIFICATE

Certified that the M.C.Primary Girls School at A-2 Block, Nand Nagri, Delhi-93. Comprised of ground floor only owned/occupied by M/s M.C.Primary Girls School have complied with the fire prevention and fire safety requirements in accordance with with the circular issued by the Director of Education dtd.01.03.2011 and verified by the officer concerned of Fire Service on 4.11.2011 in the presence of Sh.Goramani, Principal, of the school and that the building is fit for occupancy class B' Educational Building' with effect from .../.6././/./... for a period of three years , subject to conditions printed overleaf.

Issued on 16 / (1 / 1) at New Delhi by

Chief Fire Officer Delhi Fire Service

Real !!

To.

Principal
M.C.Primary Girls School
A-2 Block,Nand Nagri,Delhi-93.
Copy:-

- The Director of Education MCD, Nigam Bhawan, Kashmiri Gate, Delhi.
- Principal
 M.C.Primary Boys School
 A-2 Block,Nand Nagri,Delhi-93.

CONDITIONS

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

Ground only

INSPECTION REPORT

5 6 5	Details of previous NOC : Letter I Fire Safety directives letter No : _F/4/ Date of inspection :	un calnonal, ase/Renewat No	Date 1 Singh	d: NIL dtf 1.3.11
	O. Applicant's letter No. O. Applicant's letter No. O. Applicant's letter No.	1986 dtd - 31	ulti	
S. No	Minimum Standards on fire prevention and fire safety U/R 33	NBC Curtalen Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	 Road width Gate width Width of internal road 		la W	MR
2	Number, Width, Type & Arrangement	of Exits	N	
	a. Number of staircases • Upper Floors • Basements b. Width of staircases • Upper Floors • Basements c. Protection of exits • Fire check door • Pressurization c. No. of continuous staircases to terrace g. Width of Corridor h. Door Size		I.O.M	MR

		1		- T		
3	Compartmentation.					
24	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 					
A	1 11-0 Dempors					
1	Basements Upper floors	30 a/c per hour 12 a/c per hour				
5	Fire Extinguishers					
	 Total numbers Types IS marking 	ISI marked	ABCCOL		MR	
6	First-Aid Hose Reels.	. I Theory on the Walks	1-	3.1	MR	
	Total numbers on each floor Length of hose reel hose Nozzle diameter	30 m 5 mm	2/1			
7	Automatic fire detection and alarming	g system.				
Э. Б.	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 			22		
8	MOEFA					
9	Public Address System. Automatic Sprinkler System.					
	Basement					

	Upper Floor Sprinkler above false ceiling	- 13		1		1
11	Internal Hydrants	1				
	 Size of riser/down-comer Number of hydrants per floor Hose Box 					
12	Yard Hydrants.					
	Total number of hydrants Hose Box				5	
13	Pumping Arrangements.					
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 					
14	Captive Water Storage for fire fighting. • Underground tank capacity					

1	 Fire service inlet Access to tank Overhead Tank capacity 				1. I.			
15	Exit Signage.			+				
16	Provision of Lifts.							
	Pressurization of Lift Shaft Pressurization of Lift lobby				2			
	Communication In lift Car		-					
8	 Fireman's Grounding Switch Lift Signage 						 * 1	
	- Ditt Signage							
17	Standby power supply							
18	Refuge Area.	1807						
	➤ Total Area ➤ Location		52					
19	Fire Control Room	1		100				
	Detector System Panel		J2.					
	 Flow Switch Panel 							
	PA System Panel			.X =	4 -		4	
	Batter backup				100			
	Building Floor Plans				103.5	9		
20	Special Fire Protection Systems for Protection of special Risks, if any:		ē	a	-		1	

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Signature of the Inspecting Officer

Name VIRENDRA SINGH

Designation

Designation

Designation