GOVERNTMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTER: DELHI FIRE SERVICE: NEW DELHI-110001

No: FEIDFS/MS/Schol/2011/2732

Dated:

То

18

The Principal, Bapu AdarshVidyalaya Sec., R-Block, New Rajinder Nagar, New Delhi-110060.

Ref No: No. BAV/2011-12/5371 dated 26.05.2011.

FIRE SAFETY CERTIFICATE

Certified that the Bapu Adrash Vidyalaya Sec., R-Block, New Rajinder Nagar, New Delhi-110060 comprised of - ground floor plus one upper floors, owned/occupied by Bapu Adrash Vidyalaya Sec. has complied with the fire prevention and fire safety requirements in accordance with the Director of Education circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 and verified by the officers concerned of Fire Service on 05.09.2011 in the presence of - Smt. Asha Kadam Principal and that the building/premises is fit for occupancy class—group-B (educational) with effect from the date of issue of this certificate for a period of - three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules,2010 printed overleaf.

2g)| 0 2 0 1 | Issued on_at New Delhi.

> Chief Fire Officer Delhi Fire Service

40

Copy to:

The Director
 Govt. of N.C.T. of Delhi
 Directorate of Education,
 Old Secretariat, Delhi

	INSPE	CTION REPORT		
	Type of Case : New Details of previous NOC : Letter Fire Safety directives letter No : C Date of inspection : C Name of the Inspecting Officers : D Name and designation of officers from the building side : Mx Year of Construction	F No	1848 dt 11.	
		Ax 2011-12/53	71 At 26.5.11	
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
	Access to building			
	Road widthGate width	R.	9 Mbs -	MR
	Width of internal road		- YOMIN.	THR
	Number, Width, Type & Arrangemen	it of Exits		
	a. Number of staircases	R	24100 /	MR
	Upper Floors Basements	R	SMOD	MR.
	b. Width of staircases	R	HILL.	HIL
	Upper Floors		180aue 160au	MR
	Basements	NIC	Me	MIC
	c. Protection of exits • Fire check door	MR	MP	MMR
	Pressurization	~ \u		D
	e. No. of continuous staircases to terrace	_ u	- u -	- 6
	g. Width of Corridor		24100	MR
		MR	190 aus -	

3	Compartmentation.	-			
	Fire check door	NIR	ND	NMR	
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-u-	t("		
	scaring of electrical shafts	eti	- 41-		
	The Raing of shaft door	u	- 13 -		
	Water Curtain			- 4	
	Fire Dampers	- 4	~ · · · ·		
4	Smoke Management System.	MR		-4-	
	 Basements 	30 a/c per hour	MP	MMR	
	 Upper floors 	12 a/c per hour	- 1 -	-11-	
7.		1.000			
5	Fire Extinguishers	R	D		
	 Total numbers 		Privided	MR	
	• . Types		4 MOD ALLA	MP	
	IS marking	ISI marked	ABE TYPE	-	
6	First-Aid Hose Reels.	MR		JI-	
	 Total numbers on each floor 	MA	MP	NMR	
	 Length of hose reel hose 	30 m			
	Nozzle diameter	5 mm			
7	Automatic fire detection and A				
	Time of St.	system. 1/ P	NP.	MMR	
	Type of detectors	-			
	 Location of Main Panel 				
	 Location of Repeater Panel 				
191	 Alternate source of power 			-	
	Hooters' Location			-	
	Location Location				
8	MOEFA	8			
9	Public Address System.			***	
10	Automatic Sprinkler System.				
	The state of the s	¥	-		

	Upper Floor Sprinkler above false ceiling			
11	Internal Hydrants	NR		200000000000000000000000000000000000000
	 Size of riser/down-comer Number of hydrants per floor 	IN C	ND	MMR
W.C-	Hose Box			
12	Yard Hydrants.	NR	NID	1
	 Total number of hydrants Hose Box 			NMR
13	- maping carrangements			
	Ground Level	- 0 -		NMR_
	 Discharge of main Pump Head of Main pump 			
	 Number of main pumps 	-		-
	> Jockey Pump out put			
	 ➤ Jockey pump head ➤ Standby Pump out put ➤ Standby Pump Head ➤ Auto Starting/ Manual stopping ➤ Pump House Access 	_		
			-	
	 ➢ Pump House Access Terrace level 			
	 ➤ Discharge of pump 	-	-	
	➤ Head of the pump			
	➢ Power Supply➢ Auto Starting of pump		-	-
4	Captive Water Storage for fire fighting		•	
	Underground tank capacity	,		
	➤ Draw-off connection	8		-

i

	 Fire service inlet Access to tank Overhead Tank capacity 	-и		-
15	Exit Signage.	MR	118	
16	Provision of Lifts.	91.R	M.D	MMR
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	- 1.		- 4 -
		_ tv		_ 0 -
		N		-1
		1	-11-	-1)-
17	Standby power supply	a.	- 4 -	
18	Refuge Area.			
	➤ Total Area ➤ Location	·	+ 4 -	
19	Fire Control Room			_4
	Detector System Panel	tı		- 4 -
	Flow Switch Panel	_ 4	- OL -	
	PAi System Panel		- " -	4\
	Batter backup Building Floor Plans	<u> </u>		8
20			- \ -	
15	Special Fire Protection Systems for Protection of special Risks, if any:	- u -		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name 41, L. Anejs

Designation Div. Officer

Workye Signature of the Inspecting Officer

Name P. S. Doluge
Designation AssH Div Affer.