## GOVERNTMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No: F6/0F5/m5/school/2011/2852

Dated: 03/11/11

To

The H.O.S., Ramjas Senior Sec. School-2, Anand Parbat, New Delhi-110005.

Ref No: No.5652 dated 20.05.2011.

## FIRE SAFETY CERTIFICATE

Certified that the - Ramjas Senior Sec. School, Anand Parbat, New Delhi110005 comprised of - ground floor plus one upper floors, owned/occupied by Ramjas
Foundation school has complied with the fire prevention and fire safety requirements in
accordance with the Director of Education circular No. F.16/Estate/CC/CC/Fire
Safety/2011/3298 to 3398 dated 01.03.2011 and verified by the officer concerned of Fire
Service on 19.10.2011 in the presence of - Sh. Hement Kumar Act.Principal and that the
building/premises is fit for occupancy class - group-B (educational) with effect from the
date of issue of this certificate for a period of - three years in accordance with role 36
unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to
compliance of the conditions under rule-38 of the Delhi Fire Service Rules,2010 printed
overleaf.

Copy to:

The Director
 Govt. of N.C.T. of Delhi
 Directorate of Education,
 Old Secretariat, Delhi

Chief Fire Officer Delhi Fire Service

9- (1)

	INSPE	CTION REPORT			
	Details of previous NOC Lette Fire Safety directives letter No	Case/ Renewal  The No. NIC  AND THE DATE  TO DO THE DATE  TO THE L. AV  THE MAN TO THE LEADING THE LEA	Dato 1998 dt 24.	d: — 7.07	
S.	Minimum Standards on fire	The second secon	df 20.5, 2011.		
No.	prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	<ul> <li>Road width</li> </ul>	R	10 mbs	MR	
	Gate width	R	4.40	MR	
	Width of internal road	NR	MP	NMR	
	Number, Width, Type & Arrangemen	t of Exits	1,00.17	1 37 100	
	a. Number of staircases	P	2 200	MR	
	<ul> <li>Upper Floors</li> </ul>	R	it.	MR	
	Basements	4110	Mu	KHC	
	b. Width of staircases	R	1502153Cm	MR	
	• Upper Floors	R			
	Basements  C. Protection C. T.  C. Protection	4100	FIIC	HIL	
	c. Protection of exits	MR	MP	11mil	
	Fire check door     Pressurization		cu	FIMIC -	
	e. No. of continuous staircases to terrace	- <u>u</u>	-	4	
	g. Width of Corridor	P	2 Nos	MME	
	h. Door Size	R_	2.58 Mts	NINE	
		R	112-X205	HILL	

3	Compartmentation.			
	<ul> <li>Fire check door</li> <li>Sealing of electrical shafts</li> </ul>	HR /	MP /	TIMR /
	<ul> <li>Fire Rating of shaft door</li> <li>Water Curtain</li> <li>Fire Dampers</li> </ul>			
4	Smoke Management System,	10	1	
	Basements     Upper floors	30 a/c per hour 12 a/c per hour	NØ.	HHR.
5	Fire Extinguishers	D		
	<ul><li>Total numbers</li><li>Types</li><li>IS marking</li></ul>	ISI marked	- World-ed	MR u -
б	First-Aid Hose Reels.		C - 21	
	<ul> <li>Total numbers on each floor</li> <li>Length of hose reel hose</li> <li>Nozzle diameter</li> </ul>	30 m	NP	MAR
7	Automatic fire detection and alarming		V 1 0	
	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> </ul>	System. Puk.	N.V.	NIMP
	Hooters' Location			
3	MOEFA	NR	N.F	N L via
10	Public Address System.	u-	-0-	NMR
U	Automatic Sprinkler System.  Basement	MR	NP	KIMR

	Upper Floor     Sprinkler above false ceiling	-		
11	Internal Hydrants	HR	ND	
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>		NV /	MMR
12	Yard Hydrants.	71.8	11.8.	VIOL D
	Total number of hydrants     Hose Box		/	MMR
13	Pumping Arrangements.	MIR.	× 9	KIMR
	<ul> <li>Ground Level</li> <li>Discharge of main Pump</li> <li>Head of Main pump</li> <li>Number of main pumps</li> <li>Jockey Pump out put</li> <li>Jockey pump head</li> <li>Standby Pump out put</li> <li>Standby Pump Head</li> <li>Auto Starting/ Manual stopping</li> <li>Pump House Access</li> </ul>			
	<ul> <li>Terrace level</li> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power Supply</li> <li>Auto Starting of pump</li> </ul>	· /	N.Y.	NIME
14	Captive Water Storage for fire fighting.	MR	NIP	/
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>	1700	N.Y.	MINK

	> Fire service inlet	1	/	1
	➤ Access to tank			-
	Overhead Tank capacity			-
15	Exit Signage.	NIR	N.P	ting
16	Provision of Lifts.	NIR.	N.P.	NMR
	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> </ul>			
17	Standby power supply	N.R.	N.P.	No. of the Contract
18	Refuge Area.	NI R.	0	NMR
	> Total Area > Location		N.P.	KIMP
19	Fire Control Room	MIR	1).8	11000
	<ul> <li>Detector System Panel</li> <li>Flow Switch Panel</li> <li>PAl System Panel</li> <li>Batter backup</li> <li>Building Floor Plans</li> </ul>		N.1.	NMR/
20	Special Fire Protection Systems for Protection of special Risks, if any:	N.R.	N.P.	NMR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name H.L.ANEJA

Designation Piv. Efficar.

Signature of the Inspecting Officer

Name

Designation