GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F-6/08-5/05/ School/2011/2899 Dated: 16/11/11

FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

Carl II

To.

Principal Rajkiya Sarvodaya Kanya Vidyalaya Patpar Ganj ,Delhi-91. Copy:-

The Joint Director of Education (Land & Estate)
 Directorate of Education.

Lucknow Road, Delhi -54.

2. Principal
Rajkiya Sarvodaya Bal Vidyalaya
Patpar Gani Delhi-91.

CONDITIONS

- All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

Ť	Name & address of the building: R. S	S. K.V Patt	bar Gam Del	hi -91				
3		ducational		, , , , ,				
Ì	Type of Case : New Case/ Renewal							
3	Details of previous NOC : Letter No. NIL Dated: NIL							
j	5. Fire Safety directives letter No : F.16	lestetel cel sola	-011/22 G P 1227	== IHIII				
1	6. Date of inspection	110/11	11 12 17 20 20	18 2011 3.1				
į	7. Name of the Inspecting Officers : D	o Viscodya	Sinch					
1	8. Name and designation of officers							
	from the building side	nt - H. Makan	i (Princip	nal)				
3		1995 29		7)				
1	O. Applicant's letter No.	RS.KU PPG	462 dtd	28/09/11				
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR				
1	Access to building							
	 Road width 		6 M	MR				
	Gate width							
	 Width of internal road 							
2	Number, Width, Type & Arrangement	of Exits						
	a. Number of staircases	N No.	y No.	MR				
	Upper Floors	y No.	9 No: -	MR				
	Basements							
	b. Width of staircases	(S M	1.5 m	MR				
29	Upper Floors	1.5 M	1.55 M	MR				
	 Basements 	-		====				
	c Protection of exits							
	Fire check door							
	 Pressurization 							
	e. No. of continuous staircases to terrace			-				
	g. Width of Corridor	1-5 M	1-5 M.	MR				
	h. Door Size	10 M	1.5 M	MR				

				-			
- (Compartmentation.						
	 Fire check door Sealing of electrical shafts 						
	 Fire Rating of shaft door Water Curtain 						
	Fire Dampers	Į.		11.7			
4 1	Smoke Management System.						
	Basements Upper floors	30 a/c per hour 12 a/c per hour					
5	Fire Extinguishers		Lavas				
	Total numbersTypesIS marking	1.5 Ro	20 No ABC (CO2	MR			
6	First-Aid Hose Reels.						
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m 5 mm					
7	Automatic fire detection and alarming system.						
	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 						
8	MOEFA						
9	Public Address System.						
10	Automatic Sprinkler System.						
	Basement	1.4	1				

Th:	Upper Floor Sprinkler above false ceiling	/					
11	Internal Hydrants						
	Size of riser/down-comer Number of hydrants per floor Hose Box						
12	Yard Hydrants.						
	Total number of hydrants Hose Box	1		1			
13	Pumping Arrangements.						
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 						
14	Captive Water Storage for fire fighting.						
	Underground tank capacity Draw-off connection						

> Fire service inlet				(\$)	1			,
> Access to tank Overhand Tank contains					1			
- Overnead Tank capacity				33				
Exit Signage.		-/	100		*W			
Provision of Lifts.	14	9/						
Pressurization of Lift Shaft		1						Ý
		1			7			
					+			
	1 1						_	
	- 1	=						
• Litt Signage	9				7			
Standby power supply								
Refuge Area.								
➤ Total Area ➤ Location								
Fire Control Room								
Detector System Panel	17. 21	1		1				
Flow Switch Panel						-		
PA System Panel	The second	7		-	150			
Batter backup								
Building Floor Plans				11 11	1		- 1/	
Special Fire Protection Systems for Protection of special Risks, if any:				X				
	 ➤ Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. ➤ Total Area ➤ Location Fire Control Room Detector System Panel Flow Switch Panel PAi System Panel Batter backup Building Floor Plans Special Fire Protection Systems for 	➤ Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. ➤ Total Area ➤ Location Fire Control Room Pales System Panel Pales System Panel Batter backup Building Floor Plans Special Fire Protection Systems for	➤ Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. ➤ Total Area ➤ Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for	➤ Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. ➤ Total Area ➤ Location Fire Control Room Pldw Switch Panel Fldw Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for	➤ Access to tank • Overhead Tank capacity Exit Signage. Provision of Lifts. • Pressurization of Lift Shaft • Pressurization of Lift lobby • Communication In lift Car • Fireman's Grounding Switch • Lift Signage Standby power supply Refuge Area. ➤ Total Area ➤ Location Fire Control Room • Detector System Panel • Flow Switch Panel • PA System Panel • Batter backup • Building Floor Plans Special Fire Protection Systems for	➤ Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. ➤ Total Area ➤ Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Bafter backup Building Floor Plans Special Fire Protection Systems for	> Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. > Total Area > Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for	> Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. > Total Area > Location Fire Control Room Detector System Panel Fldw Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire so required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the I Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name VIRENDRA SINGH

Designation

Designation