## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE NEW DELHI-110 001.

No. F6/DF5/ons/school/2011/2944

Dated: [1 / 11 / 11

## FIRE SAFETY CERTIFICATE

Certified that the RAJKIYA SARVODAYA KANYA VIDYALAYA No. 1 located at Narela, Delhi-40, comprised of three blocks. First block is ground floor only and second & third blocks are ground and one upper floor and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Director of Education circular dated 01.03.2001 and verified by the officer concerned of fire service on 20.10.2011 in the presence of Smt. Sneh Kapoor, Principal and that the building/ premises is fit for occupancy class Educational class with effect from 11/11/11 for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on \_\_\_\_\_\_ at New Delhi by

Delhi Fire Service

Smt. Sneh Kapoor, Principal, Rajkiya Sarvodaya Kanya Vidyalaya No. 1, Narela, Delhi-40.

Copy to:

The Director, Dte. Of Education, Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

	INSPEC	CTION REPORT		
	4. Details of previous NOC NA: Letter 5. Fire Safety directives letter No : F.16 6. Date of inspection : 20.1 7. Name of the Inspecting Officers : 4km 8. Name and designation of officers from the building side : No.	Case/Renewal  No.  Estate ce fine So  2011  R. K. Dahiys	Date of 2011 2298	ed:
- 1	0 Applicant's letter No			23.09.2011
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement		Remarks MR/NMR
	Access to building	1.3.77		
	<ul> <li>Road width</li> <li>Gate width</li> <li>Width of internal road</li> </ul>	+cembre	10 meless Acceptable	mir
	Number, Winth, Type & Arrangement	of Exite	_	
	a. Number of staircases	-4	T- 1	
	<ul><li>Upper Floors</li><li>Basements</li></ul>	-	one -	MR
	b. Width of staircases  • Upper Floors  • Basements	150 du	18-Privale - 150 cm C. Pswale - 14P, 1500 — Bame —	
	c. Protection of exits		kp	
	Fire check door     Pressurization			
	e. No. of continuous staircases to terrace		5	
	g Width of Corridor h Door Size	1.5 mts. Double Door	2 Melis 100 cms ead	MIR

3	Compartmentation.			
	Fire check door		NA	
	<ul> <li>Sealing of electrical shafts</li> <li>Fire Rating of shaft door</li> <li>Water Curtain</li> <li>Fire Dampers</li> </ul>			
4	Smoke Management System.	-		
	Basements		AW	
	Upper floors	30 a/c per hour 12 a/c per hour		
5	Fire Extinguishers			
	<ul> <li>Total numbers</li> <li>Types</li> <li>IS marking</li> </ul>		Provided 23 /	mil
	First-Aid Hose Reels.	ISI marked	151 Mareley	1
	Total numbers on each floor	N.A		
	Length of hose reel hose     Nozzle diameter	30 m		
1.	Automatic fire detection and alarming	1 - min	·	
	Type of detectors	system.	N.A	
	Location of Main Panel		-	
	Location of Repeater Panel	-		
	<ul> <li>Alternate source of power</li> </ul>			
	Hooters' Location		-	
M	IOEFA	-		
	ublic Address System.		N. A.	
At	utomatic Sprinkler System.		Provided	mpR
	Basement			-

	Upper Floor     Sprinkler above false ceiling	11-	-		
11	Internal Hydrants		1UA		
	Size of riser/down-comer	-			
	<ul> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>		æ		
			<u></u>		
12	Yard Hydrants. N. A.				
	<ul> <li>Total number of hydrants</li> <li>Hose Box</li> </ul>				
13			-		
13	Pumping Arrangements.		NA		
	Ground Level		-		
	Discharge of main Pump		-		
	F Head of Main pump				
	Number of main pumps				
	> Jockey Pump out put				
	➤ Jockey pump head				
	<ul> <li>Standby Pump out put</li> <li>Standby Pump Head</li> </ul>				
	> Auto Starting/ Manual				
	stopping				
	<ul> <li>Pump House Access</li> <li>Terrace level</li> </ul>		-		
	- > Discharge of pump				
	Head of the pump		F-1		
	> Power Supply	-	<del></del>		
	➤ Auto Starting of pump		~		
14	Captive Water Storage for fire fighting.	NA			
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>		-		

	➤ Fire service inlet  ➤ Access to tank  • Overhead Total	·		
-	Overhead Tank capacity		-	
15	Exit Signage.			
16	Provision of Lifts.		Provided	MrR
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	-	NA	Ţ
	Pressurization of Lift lobby     Communication	-		
	Communication In lift Car     Fireman's Grounding Switch		_	
	* Lift Signage			
17	Standby power supply			
18	Refuge Area.		N.A	
	➢ Total Area		N.A	
	Location	-	-	
9	Fire Control Room		h-	
			N.A	
į	<ul> <li>Detector System Panel</li> <li>Flow Switch Panel</li> </ul>	-	1	
P	PA System Panel		-	
		-	-	
	Building Floor Plans			
S	pecial Fire Protection	<u> </u>	-	
P	pecial Fire Protection Systems for rotection of special Risks, if any:			W.

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the inspecting officer

Signature of the Inspecting Officer

Name SHRI R. K. DAHIYA

Name

Designation ASSTT DIV. OFFICER

Designation

RUMANA.

- minnert