## GOVERNTMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No: F6/2FS/ms/school/2011/2889

Dated: 04/11/11

To

The Principal, Shahid Captain Amit Verma Govt. Co-Ed Sarvodaya Vidyalaya, C-Block Inder puri, New Delhi-110012.

Ref No: No.2284/SCAV/11 dated 14.09,2011.

## FIRE SAFETY CERTIFICATE

Certified that the – Shahid Captain Amit Verma Govt Co-Ed Sarvodaya Vidyalaya C-Block, Inder puri, New Delhi-110012 comprised of - ground floor plus one upper floors, owned/occupied by Govt.of N.C.T. school has complied with the fire prevention and fire safety requirements in accordance with the Director of Education circular No. F.16/Estate/CC/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 and verified by the officer concerned of Fire Service on 18.10.2011 in the presence of - Sh. K.L. Meena Vice .Principal and that the building/premises is fit for occupancy class – group-B (educational) with effect from the date of issue of this certificate for a period of - three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules,2010 printed overleaf.

Chief Fire Officer Delhi Fire Service

0710

Copy to:

The Director
 Govt. of N.C.T. of Delhi
 Directorate of Education,
 Old Secretariat, Delhi

## INSPECTION REPORT

1.	Name & address of the building: 5	Lahid Coplain Ami	L Verma levil Cored Sa	rodaye viday		
2.	Type of Occupancy	ding: Shahid affain Amit Verma (ir) Good Sarvadey  Edua ting!  New Case/ Renewal		k, Inder pari		
3.	Type of Case			1		
4.	T.	etter No. MIL	Dated	1:		
5.	and outerly directives letter (40	MIC				
6.	- Are or mapociton	18/10/2011				
7.	Name of the Inspecting Officers :_	ele				
8.	Name and designation of officers					
	from the building side AL Meing Vice Vyncibal					
	Year of Construction					
S. Minimum Standards on five						
	Minimum Standards on fire	NBC	Provided at site	Remarks		
0.	prevention and fire safety U/R.	33 Requirement	9	MR/NMR		
	Access to building					
Ĭ	<ul> <li>Road width</li> </ul>	R.	9 Mbs	MR		
	<ul> <li>Gate width</li> </ul>	R	of Mh	MR		
	<ul> <li>Width of internal road</li> </ul>	Ne	MP	NMR		
	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	R	2x100	MR		
	<ul> <li>Upper Floors</li> </ul>	P		11-		
	<ul> <li>Basements</li> </ul>	The	MILL	MIC		
	b. Width of staircases	ft.	144 2 1 47 cm	HR		
	Upper Floors			_4/		
0	Basements	Ma	Hic	NICE		
	c. Protection of exits	NO	ND			
	Fire check door	- tx		NMR.		
	Pressurization	-4.	3\			
	e. No. of continuous staircases to te	тасе	2 Moo	MR		
	g. Width of Corridor	R	1.2 MM	MR		
	h. Door Size	0	100 x 205 cm	AL STATE		

3					
	Compartmentation,	HR			
	<ul> <li>Fire check door</li> </ul>	FIK	NV_	MME	
	<ul> <li>Sealing of electrical shafts</li> </ul>			1	
	<ul> <li>Fire Rating of shaft door</li> </ul>		/		
	Water Curtain				
	Fire Dampers	/			
	Smoke Management System.				
	Basements	NR	M.P.	MMR	
	<ul> <li>Upper floors</li> </ul>	30 a/c per hour		1	
		12 a/c per hour			
	Fire Extinguishers		(		
	Total numbers	- K	Privided	- NE	
	• Types		-6-	01 -	
			ABELYE	-6-	
	IS marking First-Aid Hose Reels.	ISI marked	0_1 -		
		MR	MP	Way and AD	
	<ul> <li>Total numbers on each floor</li> </ul>		2	YIMR	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	f -		
	<ul> <li>Nozzle diameter</li> </ul>	5 mm			
	Automatic fire detection and alarming system.				
	<ul> <li>Type of detectors</li> </ul>		MP.	MMR	
	<ul> <li>Location of Main Panel</li> </ul>				
			/		
	<ul> <li>Location of Repeater Panel</li> </ul>		/		
	<ul> <li>Alternate source of power</li> </ul>			/	
	<ul> <li>Hooters' Location</li> </ul>				
			1	1	
	MOEFA	N.R.	N 0		
	Public Address System.	TAN.	N.P.	NME	
)	Automatic Sprinkler System.			-	
	Basement		-		
-	The second secon	2114	MIC	MIL	

Ŷ

	<ul> <li>Upper Floor</li> <li>Sprinkler above false ceiling</li> </ul>	_		
11	Internal Hydrants			
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>	+IR	110	1412
12	Yard Hydrants.	11.0	1 , 0	
	<ul> <li>Total number of hydrants</li> <li>Hose Box</li> </ul>	HIR	N.Y.	HMR
13	Pumping Arrangements.	N. R	D	-
	<ul> <li>Ground Level</li> <li>Discharge of main Pump</li> <li>Head of Main pump</li> <li>Number of main pumps</li> <li>Jockey Pump out put</li> <li>Jockey pump head</li> <li>Standby Pump out put</li> <li>Standby Pump Head</li> <li>Auto Starting/ Manual stopping</li> <li>Pump House Access</li> </ul>	NA	N.P.	NHR
		-	·	
		-	2-	
			•	
		50	7	
		-		-
			H	Pa
		-	-	
		·		8
	Terrace level		-	-
	<ul> <li>▶ Discharge of pump</li> </ul>			
	➤ Head of the pump	<u> </u>	-	
	Power Supply		<u> </u>	
-374	➤ Auto Starting of pump		-	+
14	Captive Water Storage for fire fighting	. NR	×10	Mary
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>	1	1	MNY

	➤ Fire service inlet	-4		
	> Access to tank		-1-	
	<ul> <li>Overhead Tank capacity</li> </ul>		x 4	_4
15	Exit Signage.	MR:	MP	Nua
16	Provision of Lifts.			
	Pressurization of Lift Shaft			_+
	Pressurization of Lift lobby		W <del>.</del>	-
	Communication In lift Car			
	<ul> <li>Fireman's Grounding Switch</li> </ul>		- 11	
	Lift Signage			-
17	Standby power supply	NR	NIP	NMR
18	Refuge Area.	NR	N.P	N.WR.
	➤ Total Area			
	> Location		-	
19	Fire Control Room	MR	M.P.	N.NR
	Detector System Panel		1	1
	Flow Switch Panel			
	PA System Panel			
	Batter backup			/
	Building Floor Plans		1	
20		MR.	NI.P	NWR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

·-©

Signature of the Inspecting Officer

Name H. L. ANEJA.

Designation Div. Hicer

Signature of the Inspecting Officer

Name

Designation