[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFS/05/School/2012/1234

Dated: 0 8/0 4/12

## **FIRE SAFETY CERTIFICATE**

Chief Fire Officer For Director Delhi Fire Service

414/12

To,

Principal M.C. Primary School, Vishwakarma Park, Delhi-51

Copy to:-.

The Director of Education, MCD, Nigam Bhawan, Kashmiri Gate, Delhi

## CONDITIONS:

1. All the means of escape shall be kept free of all type of obstruction all the type of

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This NOC may not be treated in any case for regularizations of unauthorized construction

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

•

1

		TION REPORT		8 g S			
. 1	M.C.	Primary Sch	rool,	1 a 1			
1	, wish war part, Dem - 42						
2	Type of Occupancy: Educational						
3	. New Case/ Kenewal						
4	Dated:						
5	5. Fire Safety directives letter No: F.16/cstate/C.c/fire Safety/2011/3 298 to 3398 dt.  6. Date of inspection: 22.3.12						
6							
7	7. Name of the Inspecting Officers: Mr. Suresh Singh (ADO)						
8	and and application of officers						
	from the building side : Mrs.	Bhawna,	In Charge of a	School			
		104	V				
		ty 25.1.12					
S.	Minimum Standards on fire		Provided at site	Remarks			
No.	prevention and fire safety U/R 33	Requirement		MR/NMR			
1	Access to building		3 a 2 a a a a a a a a a a a a a a a a a				
	Road width	6 h	6 m	MR			
4.	Gate width		3.8 M	mR			
	Width of internal road						
2	Number, Width, Type & Arrangement of	of Exits		***************************************			
V *	a. Number of staircases		1	mR			
	Upper Floors						
#E	• Basements						
	b. Width of staircases		1.5 m	mR =			
	Upper Floors						
	Basements	1 .					
	c. Protection of exits			-			
	Fire check door						
- - 	• Pressurization						
	e. No. of continuous staircases to terrace			- 1			
	g. Width of Corridor		2 m	mk			
	h. Door Size	1 1	14	MR			

2.8				
				Value of the second
3 Compartmen	itation.		Frontded	
	heck door			
• Sealin	g of electrical shafts			
	ating of shaft door			
• Water	Curtain			
• Fire D	ampers			
4 Smoke Mana	gement System.			
Basem		N.A	7	
• Upper		30 a/c per hour	3.	
Opper	HOORS	12 a/c per hour		
5 Fire Extingui	Phone			_
	umbers		04	MR
• Types	**************************************		Co2+ ABC	MR
• IS mar		ISI marked	181	MR.
ZASCIAM HOS		N.A		
	umbers on each floor		1	
	of hose reel hose	30 m		
	diameter	5 mm		
Automatic fire	detection and alarming	system.		
	detectors			2
	n of Main Panel			~
				_
	of Repeater Panel			
• Alternat	e source of power			
• Hooters	Location			
MOEFA				
Public Address	System.			
Automatic Spri		N' A		
Basemen				

· ·

	Upper Floor			
	Sprinkler above false ceiling			
1	Internal Hydrants	N-A		
0	Size of riser/down-comer			
	Number of hydrants per floor			
	Hose Box			
12	Yard Hydrants.	NA		
	Total number of hydrants			
	Hose Box			
13	Pumping Arrangements.	NA		<del> </del>
	Ground Level			
	> Discharge of main Pump			
	> Head of Main pump			
	> Number of main pumps			
8	> Jockey Pump out put			
, r	> Jockey pump head			-
	> Standby Pump out put			
	> Standby Pump Head			
	> Auto Starting/ Manual			
	stopping			
	> Pump House Access		s. of the writer	_
	Terrace level			
	> Discharge of pump			
	> Head of the pump			
2 7 9	> Power Supply			
10 Sup	> Auto Starting of pump	uiglandishis A:		
14	Captive Water Storage for fire fight	ing.	A	
	Underground tank capacity			
	> Draw-off connection			

1114 1

> Fire service inlet		
> Access to tank		
Overhead Tank capacity		
Exit Signage.	NA:	local =
Provision of Lifts.	NA	
Pressurization of Lift Shaft		
Pressurization of Lift lobby		
Communication In lift Car		
• Fireman's Grounding Switch		
• Lift Signage		
Standby power supply	N'A	
Refuge Area.	N. A	
> Total Area		
> Location		
Fire Control Room	N.A	
Detector System Panel		
Flow Switch Panel		
PAi System Panel		
PAi System Panel     Batter backup		
Building Floor Plans  Special Fire Protection Systems for		
Batter backup     Building Floor Plans	<i>N</i> ∙ A	
	<ul> <li>➤ Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>➤ Total Area</li> <li>➤ Location</li> <li>Fire Control Room</li> <li>Detector System Panel</li> </ul>	➤ Access to tank  Overhead Tank capacity  Exit Signage.  Provision of Lifts.  Pressurization of Lift Shaft  Pressurization of Lift lobby  Communication In lift Car  Fireman's Grounding Switch  Lift Signage  Standby power supply  Refuge Area.  ➤ Total Area  ➤ Location  Fire Control Room  Other Panel

The fire protection systems provided in the building were test checked and found functional at the tof inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sarequired under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the D-Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer Signature of the Inspecting Officer Suresh Stage Name Name Designation Designation ADO