GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

NO. F6/OFS/ns/2012/1428

DATED: 20/04/12

FIRE SAFETY CERTIFICATE

Issued on ...20 Jo.y. J. 2....... at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to,

- 1. The Executive Engineer (Bldg) HQ, Building Department, MCD, Town Hall, Delhi.
- 2. The Director, M/s Richa Fashion Pvt. Ltd. at Plot No F-23/2, Okhla Industrial Area, Phase-II

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The basement shall be used strictly as per the provisions of Building Bye laws.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigovt.nic.in

1	Name & address of the building	M/s Richa	Fashion F	vt. Ltd., at Pl	ot No F-2	23/2 Okhla	
		Industrial	Area, Phas	e-II New Del	hi	.o/z, Okilia	
2	Type of Occupancy		building "C				
3	Type of case	New					
4	Details of previous NOC	No					
5	Fire safety directives letter No	F6/DFS/M	F6/DFS/MS/BP/1990/803 dated 17.05.1990				
6	Date of inspection	130.03.201	2	, coo datod 1	7.00.100	J	
7	Name of the inspecting Officers	DO Dhara	mpal Bhar	dwaj, ADO S	S Kushil	4	
8	Name and designation of officer	s Mr. Sunil k	Kumar Jain	(Director)	.o. rasiii	`	
0	from the building side			(,			
9	Year of construction	1990					
		Nil	10.03.2012		basement, ground , mezzanine floor, first		
					floor and one room a		
					second		
10	Applicant's letter No.	1			Second	lloor	
S. NO.	Minimum Standards on fire	NBC Rec	uirement	Dravida	d -1 11	T	
	prevention and fire safety U/R	I II DO FICE	lan emem	Provide	a at site	Remarks	
	33					MR/NMR	
1	Access to building						
	1) Road width	20 Mtr		ID			
	2) Gate width	5 Mtr		Provided		MR	
	3) Width of internal road	N/A		Provided		MR	
2				N/A		N/A	
	Number, width Type & arrange a. Number of staircases	ment of exit	S				
	1. Upper floors	Demind					
	2. basements	Required		Two Provide		MR	
	b. Width of staircase	Required		Two Provide	ed	MR	
	or width of stallcase						
	1. Upper floors	1.25 Mtr		1.5 Mtr & 1.	19 Mtr	MD	
	1. Opper floors	2000-000 AND 100-000 AND 100-0000 AND 100-000 AND 100-		Provided		MR	
	2. basements	1.25 Mtr		1.5 Mtr & 11	2 Mtr	MR	
	c. Protection of exits			Provided		IVIR	
	1. Fire check door	Dogwined					
	2. Pressurization	Required N/A	-	Provided		MR	
	d. No. of continuous staircase	Dogwing d		N/A		N/A	
	to terrace	nequired		One Provide	ed	MR	
	e. Width of corridor	N/A		N.1/4			
	f. Door size	Required		N/A		N/A	
3	Compartmentation.	rtequired		125 cm Prov	<u>rided</u>	MR	
	1. Fire check door	Doguisad					
	Sealing of electrical shafts	Required		Provided		MR	
	3. Fire Rating of shaft door	Required		Provided		MR	
	1.4	Required		Provided		MR	
	F F	N/A N/A		N/A		N/A	
4		IN/A		N/A		N/A	
•	Smoke Management system.	00 /					
		30 a/c per hour		Exhust Fan Provided		MR	
		12 a/c per ho	Jul			INIL	
5	upper floors			Natural Venti	lation	MR	
5	Fire Extinguishers						
-	total numbers		12	25 Nos. Prov	ided	MR	
	Types			ABC, CO2		MR	
	ISI marking	ISI	-	Provided		MR	
6	First-Aid Hose Reels.						
-		Two	F	Provided		MR	
-		30 Mtr		Provided		MR	
	Nozzle Diameter	ōmm		Provided		MR	
						IVII (

Page 1

7	Automatic fire detection and alarming system					
			Somke Detector			
	Type of detectors	Required	Provided	MR		
	location of Main Panel	Required	Ground Provided	MR		
	location of Repeater panel	Not Required	N/A	N/A		
	Alternate source of power	Required	Battery Backup Provided	MR		
	hooter's location	Required	Staircase Provided	MR		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Not Required	Provided	MR		
10	Automatic Sprinkler System.	rotrioquiou	1 TOVIGCO	TWIT C		
	basement	Required	Provided	MR		
	upper floors	Required	Provided	MR		
	sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants	IN/A	[1V//\]	JIN/A		
	Size of riser/down-corner	150 MM	Provided	MR		
	Number of Hydrants per floor	Required	One Provided	MR		
	Ihose Box	Required	One Provided	MR		
		nequireu	Jone Provided	IIVIN		
12	Yard Hydrants.	D	Te - B - + + +	Tub		
	total number of hydrants	Required	Four Provided	MR		
	house box	Required	Four Provided	MR		
13	Pumping arrangements					
	1. Ground level					
	a. Discharge of main Pump	2280 LPM	2280 LPM	MR		
	b.Head of main pump	60 Mtr	60 Mtr	MR		
	c.Number of main pumps	One	One	MR		
	d.jockey pump out put	180 LPM	180 LPM	MR		
	e.jockey pump head	60 Mtr	60 Mtr	MR		
	f. Standby Pump output	2280 LPM	2280 LPM	MR		
	g.Stanby Pump head	60 Mtr	60 Mtr	MR		
		Required Both				
	h.Auto Starting/Manual stopping	Provided ~	Both Provided	MR		
	pump house access	Provided	Provided	MR		
	2.Terrace level			waltonia wa		
	a. Discharge of pump	900 LPM	900 LPM	MR		
	b. head of the pump	40 Mtr	40 Mtr	MR		
	c. Power supply	Not Required	Required	MR		
	d. Auto starting of pump	Not Required	Required	MR		
	Captive water storage for fire			L		
14	fighting					
	1. Underground tank capacity	75,000 ltr	75,000 Ltr Provided	IMR		
	a. Draw-off connection	Required	Provided	MR		
	b. fire service inlet	Required	Provided	MR		
	c.Access to tank	Required	Provided	MR		
	Over head tank Capacity	20,000 ltr	20,000 ltr Provided	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of lifts.	INI/A	N/A	INI/A		
	a. Pressurization of lift shaft	N/A	N/A	N/A		
	b. pressurization of lift lobby	N/A	N/A	N/A		
	c. communication in lift car	N/A	N/A	N/A		
	d. Fireman's grounding switch	N/A	N/A	N/A		
	e. Lift signage	N/A	N/A	N/A		
	Standby power supply	Required	Provided	MR		

18	Refuge Area.		Not Required			
	total area					
	location					
19	Fire control room			6		
	a. detector system Panel	Required	Provided	MR		
	b. Flow switch Panel	N/A	N/A	N/A		
	c. PA system Panel	Required	Provided	MR		
	d. Batter backup	Required	Provided	MR		
	e. Building floor plans	N/A	N/A	N/A		
20	Special Fire Protection systems for protection of special risks, if any:					

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rule it is recommended to grant of Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010

Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name Dharampal Bhardwaj

Designation : Divisional Officer

Signature of the Inspecting O

S.S. Kushik

Designatic ADO (BCP)