FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/OFS/MS/EH/2012/16/1

Dated: 03 / 05 /2012

FIRE SAFETY CERTIFICATE

Issued on ... 03/05/12 ... at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to:

Mr. Kulmohan
 D.K. Plaza Restaurant
 A-12 Vishal Enclave Rajouri Garden, New Delhi

Dy. Health Officer
 Municipal Corporation of Delhi, (West Zone)
 Rajouri Garden, New Delhi

Following fire safety directives must be adhered to:-1) All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time. 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management. 3) The trained fire fighting staff should be available round the clock. 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency. 5) The basement shall be used strictly as per the provision of building Bye-Laws. 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any. 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs. delhigovt. nic.in DORP

May Kindly peruse letter no. D-481/HD/WZ dated 03-04-2012 received from DHO (WZ), regarding renewal of NOC in r/o D.K. Plaza Restaurant located at A-12 Vishal Enclave Rajouri Garden, New Delhi. Premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa:

1. Name &address of the building : D.K. Plaza Restaurant located at A-12 Vishal Enclave Rajouri

Garden, New Delhi.

2. Type of Occupancy : Class-D (Assembly)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/EH/2006/3341 dated 05-12-2008

5. Fire Safety directives letter No. : Nil

6. Date of inspection : 20/04/2012

7. Name of the Inspecting Officers : Divisional Officer Sunil Chowdhary

8. Name and designation of officers

From the building side : Mr. Kulmohan

Year of Construction

9. Applicant's letter No. : D-481/HD/WZ dated 03-04-2012

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR
1.	Access to building			
	Road width	06 mtrs	20 mtr	M/R
	Gate width	5 mtr	Abutting 20 mtr wide road	M/R
	Width of internal road	N.R.	N.R.	N.R.
2.	Number, Width, Type & Arrangement of Exits			
	a. Number of staircases	2	2	M.R
	Upper Floors	2	2	M.R
	• Basement	2	2	M.R.

b. Width of staircases	2		
• Upper Floors	Not applicable being renewal case	75 cm approx.	M.R.
• Basement	Not applicable being renewal case	75 cm approx.	M.R.
c. Protection of exits	Required	Provided	M.R.
• Fire check door	Required	Provided	M.R.
• Pressurization	N.R.	N.R.	N.R.
d. No. of continuous staircases to terrace	2	2	M.R.
e. Width of Corridor	Halls only	Halls only	M.R
f. Door size	2 mtr	Provided	M.R
Compartmentation.			
Fire check door	Required	Provided	M.R.
Sealing of electrical shafts	N/A	N/A	N.A.
Fire Rating of shaft door	N/A	N.R.	N.A.
Water Curtain	N/R	N/R	N.R.
Fire Dampers	N/A	N/R	N.R.
Smoke Management System.			
Basements	Required	Provided	M.R.
Upper floors	Required	Provided	M.R
Fire Extinguishers			и
Total numbers	12	25	M.R
• Types	ABC & CO ₂	provided	M.R
3.5			M.R
	 Upper Floors Basement Protection of exits Fire check door Pressurization d. No. of continuous staircases to terrace e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers 	Upper Floors Basement Basement Required Fire check door Pressurization N.R. d. No. of continuous staircases to terrace e. Width of Corridor Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Dampers Required N.R. Required N.R. 2 that I was a sequired N.R. Prive check door Sealing of electrical shafts N/A N/A N/A Smoke Management System. Required Required N/A Required N/A Required N/A Smoke Management System.	• Upper Floors • Basement • Basement c. Protection of exits • Fire check door • Pressurization d. No. of continuous staircases to terrace e. Width of Corridor • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers Basements Required Provided Provided Provided Provided N.R. Required Provided N.R. Provided Provided

6.	First-Aid Hose Rees.			1
	Total numbers on each floor	1	Provided	M.R
	• Length of hose reel hose	30 m required	provided	M.R
	Nozzle diameter	5 mm required	provided	M.R
7.	Automatic fire detection and alar	ming system.	a	
	Type of detectors	N.A.	N.A.	M.R renewal case
	Location of Main Panel	N.A.	N.A.	M.R renewal case
	Location of Repeater Panel	N.A.	N.A.	M.R renewal case
	Alternate source of power	N.A.	N.A.	M.R renewal case
	Hooter's Location	N.A.	N.A.	M.R renewal case
8.	MOEFA	Required	Provided	M.R
9.	Public Address System	N.R.	N.R.	N.R
10.	Automatic Sprinkler system			
	Basement	Required	Provided	M.R
	Upper Floor	Required	Provided	M.R
	Sprinkler above false ceiling	Required	Provided	M.R
11.	Internal Hydrants			
	Size of riser/down-comer	100 mm	provided	M.R
	 Number of hydrants per floor 	1	Provided	M.R
	Hose Box	1	Provided	M.R

12.	Yard Hydrants.	52		
	Total number of hydrants	N/R	N/R	N.R.
	Hose Box	N/R	N/R	N.R.
13.	Pumping Arrangements.			9
-	Ground Level			
	> Discharge of main pump	N/R	N/R	N/R
	➤ Head of Main pump	N/R	N/R	N/R
	> Number of main pumps	N/R	N/R	N/R
	> Jockey Pump out put	N/R	, N/R	N/R
	> Jockey pump head	N/R	N/R	N/R
	> Standby pump out put	N/R	N/R	N/R
	> Standby pump Head	N/R	N/R	N/R
	> Auto Starting/Manual stopping	N/R	N/R	N/R
	> Pump Hose Access	Required	Provided	M.R.
	Terrace level			
	> Discharge of pump	450 LPM	Provided	M.R
	➤ Head of the pump	70 mtr	Provided	M.R
	> Power supply	Required	Provided	M.R
	> Auto Starting of pump	Required	Provided	M.R
14.	Captive Water Storage for fire fighti	ng.		
	Underground tank capacity	N/R	N/R	N.R.

	> Draw -off connection	N/R	N/R	N.R.
	➤ Fire service inlet	N/R	N/R	N.R.
	> Access to tank	N/R	N/R	N.R.
	Overhead Tank Capacity	10, 000 ltr	15,000	M.R
15	Exit Signage.	Required	Provided	M.R
16.	Provision of Lifts	, ,		
	Pressurization of Lift Shaft	N/A	N/A	N.R. Renewal Case
	Pressurization of Lift lobby	N/A	N/A	N.R. Renewal Case
	Communication In lift Car	N/A	N/A	N.R. Renewal Case
	Fireman's Grounding Switch	N/A	N/A	N.R. Renewal Case
	Lift Signage	Required	Provided	M.R.
17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area	N.R.	N.R	N.R
	> Total Area	N.R.	N.R.	N.R
	> Location	N.R.	N.R.	N.R
19.	Fire Control Room		,	
	> Detector System Panel	N.R.	N.R.	N.R
	Flow Switch Panel	N.R.	N.R.	N.R
	> PA system Panel	N.R.	N.R.	N.R
	_	N.R.	N.R.	N.R

	> Batter backup	N.R.	N.R.	N.R
	Building Floor plans	9 ° ° 8		
		·		
20.	Special Fire Protection Systems for	N.R.	N.R.	N.R
	Protection of special Risks, if any:			v

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Signature of the Inspection Officer

Name SUMIL CARWARA (2)

Name

Designation 5

Designation