GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No.F6/DFS/MS/2012/1748

Dated: 14/05/12

FIRE SAFETY CERTIFICATE

Issued -14/05//2—at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to:- (1) The Administrative Officer,

Municipal Corporation of Delhi,

Office of the Asstt. Commissioner, South Zone Green Park, New Delhi.

(2) Esso Standard Corporation, Petrol Pump, Bhikaji Kama Place, New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

- 1. Name & address of the building:- M/s Esso Standard Corporation, Petrol Pump, Bhikaji Kama Place, New Delhi.
- Type of occupancy:- Group J Hazardous Building
- 3. Type of case:- Renewal
- 4. Details of previous NOC:- No. F5/(F)/DFS/09/320 dated 25/11/09.
- 5. Fire safety directives No.- N/A.

6. Date of inspection:-

20.4:12

- 7. Name of the inspecting officer:- A.D.O. S.S. Kaushik
- 8. Name & designation of officer setish Sharing
- 9. Year of construction:- N/A
- 10. Applicant's letter No:-Nil. dated 22/09/11 Single Storey Building.

| CN | T | 2 | u u | Old Case | |
|-------|---|-----------------|--------------------------|----------|--|
| S.No. | Minimum Standards on fire | BBL | Provided at | Remarks | |
| _ | Prevention and fire safety U/R 33 | Requirement | site | MR/NMR | |
| 1. | Access to Building | | i i | | |
| | 1) Road width | Yes | Approachable Old Case | MR | |
| | 2) Gate width | Yes | Provided | MR | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Arrange | ment of Exits | | | |
| | A. Number of staircases | | | | |
| | 1. Upper floors | N/A | N/A | N/A | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | | | | |
| | 1. Upper floors | N/A | N/A | N/A | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | | | | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous staircase to terrace | N/A | N/A | N/A | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | Yes | 1 mtr. | MR | |
| 3. | Compartmentation | | | | |
| | 1) Fire check door | N/A | N/A | N/A | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| 4. | Smoke Management System | | | | |
| | 1) Basements | 30 a/c per hour | N/A | N/A | |
| | 2) Upper floors | 12 a/c per hour | N/A | N/A | |
| • | Fire Extinguishers | | | | |
| | 1) Total numbers | ISI Marked | 17 Nos. | MR | |
| 2 | 2) Types | | ABC,Co2,DCP & M.Foam | MR | |
| | 3) ISI marking | | Yes | MR | |
| | First-Aid Hose Reel | | | | |
| | 1) Total number of each floor | N/A | N/A | N/A | |

| | 2) Length of hose reel hose | 30 m | N/A | N/A | |
|-----|---|--------|----------|-----|--|
| | 3) Nozzle diameter | 5 mm | N/A | N/A | |
| 7. | Automatic Fire Detection & Alarming | System | | | |
| 7. | 1) Type of detectors | N/A | N/A | N/A | |
| | 2) Location of main panel | N/A | N/A | N/A | |
| | 3) Location of repeater panel | N/A | N/A | N/A | |
| | 4) Alternate source of power | N/A | N/A | N/A | |
| | 5) Hooter's Location | N/A | N/A | N/A | |
| 3. | MOEFA | Yes | provided | MR | |
|). | Public Address System | N/A | N/A | N/A | |
| 10. | Automatic Sprinkler System | | | | |
| | 1) Basement | N/A | N/A | N/A | |
| | 2) Upper floors | N/A | N/A | N/A | |
| | 3) Sprinkler above false ceiling | N/A | N/A | N/A | |
| 11. | Internal Hydrants | | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A | |
| | 2) Number of hydrants per floor | N/A | N/A | N/A | |
| | 3) Hose box | N/A | N/A | N/A | |
| 12. | Yard Hydrants | | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A | |
| | 2) Hose box | N/A | N/A | N/A | |
| 9 | | | . | | |
| 13. | Pumping Arrangement | | | | |
| | Ground level | N/A | N/A | N/A | |
| | a) Discharge of main pump | N/A | N/A | N/A | |
| | b) Head of main pump | N/A | N/A | N/A | |
| | c) Number of main pump | N/A | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head | N/A | N/A | N/A | |
| | f) Stand by pump output | N/A | N/A | N/A | |
| | g) Stand by pump head | N/A | N/A | N/A | |
| | h) Auto starting/Manual stopping | N/A | N/A | N/A | |
| | 2) Terrace level | N/A | N/A | N/A | |
| | a) Discharge of pump | N/A | N/A | N/A | |
| | b) Head of pump | N/A | N/A | N/A | |
| | c) Power supply | N/A | N/A | N/A | |
| | d) Auto starting of pump | N/A | N/A | N/A | |
| 14. | Captive Water Storage for Fire Fighting | | | | |
| | Under ground tank capacity | N/A | N/A | N/A | |
| | a) Draw-off connection | N/A | N/A | N/A | |
| | b) Fire service inlet | N/A | N/A | N/A | |
| | c) Access to tank | N/A | N/A | N/A | |
| | d) Over head tank capacity | N/A | N/A | N/A | |
| 15. | Exit Signage. | N/A | N/A | N/A | |
| 16. | Provision of Lifts. | N/A | N/A | N/A | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A | |
| | b) Pressurization of lift lobby | N/A | N/A | N/A | |
| | c) Communication in lift car | N/A | N/A | N/A | |
| | d) Fireman's switch | N/A | N/A | N/A | |
| | | A | | | |
| | e) Lift signage | N/A | N/A | N/A | |

| 17. | Stand by Power Supply | N/A | N/A | N/A |
|-----|--|-----|-----|-----|
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | | | MR |
| | Fire Buckets filled with sand, No sm Hindi & English. No lose electric wi | | | |

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010/------

Accordingly DFA is put up please.

Signature of the inspecting officer

Signature of the inspecting officer

Name

Name: - S.S. Kaushik.

Designation

Designation: - Assistant Divisional Officer.

DoSouth