GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2011/ School/188/

Dated: 24/05/12

FIRE SAFETY CERTIFICATE

THE SALET CERTIFICATE	
Certified that the Kendriga Midyalaya Section 25 at of Caraund form Cleant hut animals.) owned/occupied by	with rule 3% of the Delhi Fire e Service on
Issued on at New Delhi.	Muy 3
Copy to:-	Chief Fire Officer Delhi Fire Service
1f. sincikal 	
2	

Note:-Guidelines overleaf may also be taken care of.

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non – functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per BBL.

6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.

	INS	SPECTION REPORT		
1	Name & address of the building:	Kondriva Wide	love (500-25) 9t	Sec-8. Pohin
2	Name & address of the building:	ENO WARD.	Granla but mon	4) Bu
3	3. Type of Case	New Case/ Renewal	(12) you mu www	
4		etter No. No.	Dated	1.
5				
6	Data of	31.10.11		
7	Name of the Inspecting Officers:	Vibrin Kentar	/	
8	Name and designation of officers	· · ·		
	from the building side	Smt yeena.	, AC - 1	
	Year of Construction	2006		2
10	0. Applicant's letter No.	190350/1/2011/6-01	m)/KVS/D.S/13	405-06 M
S.	Minimum Standards on fire	NBC	Provided at site	Remarks
No.	prevention and fire safety U/R 3	Requirement		MR/NMR
1	Access to building			
	 Road width 	Appro challe	Abbrechalde	mle
	Gate width	to Fire units.	Apprexhalde 4.5 mh;	
	 Width of internal road 		4.5 mm;	
2	Number, Width, Type & Arrangen	nent of Exits Locai	ted on GF only	>
	a. Number of staircases			,
	 Upper Floors 	2	,	
	 Basements 			
	b. Width of staircases			
	 Upper Floors 			i [†]
	Basements			
	c. Protection of exits			E
	 Fire check door 		NA	
	 Pressurization 		1.	
	e. No. of continuous staircases to terr	ace		Ī
	g. Width of Corridor	4		×
	h. Door Size	2 No dars for lass	single deer of r	n/a except

3	Compartmentation.	. N.R	
	Fire check door		
	• Fire Rating of shaft door		
	Water CurtainFire Dampers		
4	Smoke Management System.		· p
	Basements	30 a/c per hour	
	Upper floors	12 a/c per hour	
		12 are per nour	
5	Fire Extinguishers		
	Total numbers		
	Types		5 NO: 5163 Cal MIR Pac type
	IS marking	ISI marked	ABC type
6	First-Aid Hose Reels.		// 0
	Total numbers on each floor	N	//R
	 Length of hose reel hose 	30 m	
	Nozzle diameter	5 mm	
7	Automatic fire detection and alarming	system. N	1 p
	Type of detectors		// (
	 Location of Main Panel 		<i></i>
	Location of Repeater Panel		
٠.	Alternate source of power		
	 Hooters' Location 		
8	MOEFA	NR	
9	Public Address System.	N.B	
10	Automatic Sprinkler System.	N	0
	• Basement	// /	

	Upper Floor			
	 Sprinkler above false ceiling 			40
11	Internal Hydrants	NR	·	
2	Size of riser/down-comerNumber of hydrants per floorHose Box			
12	Yard Hydrants.	V.R		
	Total number of hydrantsHose Box	-		
13	Pumping Arrangements.	N.A.		
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access 			
	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 			
14	Captive Water Storage for fire fighting	S. W.	9	
*	Underground tank capacityDraw-off connection	/		3

	 Fire service inlet Access to tank Overhead Tank capacity 	
15	Exit Signage.	
16	Provision of Lifts.	N.R
	Pressurization of Lift Shaft	No lest
	Pressurization of Lift lobby	
	Communication In lift Car	
	• Fireman's Grounding Switch	
	• Lift Signage	
	-68-	
17	Standby power supply	N. R
18	Refuge Area.	
	> Total Area	NR
	> Location	
19	Fire Control Room	
	Detector System Panel	
	Flow Switch Panel	
	PA System Panel	
	Batter backup	
	Building Floor Plans	
20	Special Fire Protection Systems for	2/0 20.010
	Protection of special Risks, if any:	No sull

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers...2(h.).



Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

ilia rantal

Name

Designation Do, NW

Designation

Ivaille