GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110 001**

No. F6/OFS/ms/school/2012/1931 Dated: 28/05/12.

FIRE SAFETY CERTIFICATE

Certified that the Govt.Co.Ed.Sec.School at E-Block, West Vinod Nagar, Delhi-92, comprised of ground plus one upper floor owned/occupied by Govt.Co.Ed.Sec.School have complied with the fire prevention and fire safety requirements in accordance with with the circular issued by the Director of Education dtd.01.03.2011and verified by the officer concerned of Fire Service on 04.05.2012 in the presence of Sh.Rajpal Singh, Vice- Principal, of the school and that the building is fit for occupancy class B' Educational Building' with effect from 28/05//2... for a period of three years , subject to conditions printed overleaf.

Issued on 28/05//2 at New Delhi by

Chief Fire Officer Delhi Fire Service

Principal Govt.Co.Ed.Sec.School E-Block, West Vinod, Delhi-92.

Copy to:-

The Joint Director of Education (Land & Estate) Directorate of Education, Lucknow Road, Delhi -54.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

	1.	Name & address of the building: Cout	- Co-Ed, s	ec. School, W.	est winof					
	2.	2. Type of Occupancy : Educational Magni								
	3.	3. Type of Case : New Case/ Renewal								
	4. Details of previous NOC : Letter No NIL Dated:									
	5.	5. Fire Safety directives letter No: F16 Este Ps ce 21/3298 to 3393 ddd 1.3.11								
	6. Date of inspection									
5	7. Name of the Inspecting Officers: Do Vikendre Singl									
	8. Name and designation of officers									
	from the building side Sh. Lappal Singh (Vice - Principal)									
	9. Year of Construction : 2001									
3). Applicant's letter No.		dtd 20/10/11						
	S.	Minimum Standards on fire	Curcular	Provided at site	Remarks					
	No.	prevention and fire safety U/R 33	Requirement		MR/NMR					
9	1	Access to building			* •					
		Road width		6 M	MR					
A	51	Gate width			,					
		Width of internal road								
-	2	Number, Width, Type & Arrangement of Exits								
		a. Number of staircases	5 No.	3. No.	NMR					
n		Upper Floors	5 No.	3 No	NMR					
		Basements	* * *							
		b. Width of staircases	1.5 M	1.5 M	MR					
		Upper Floors	1.5 M	1.5 M	MR					
		• Basements								
		c. Protection of exits								
		Fire check door								
		• Pressurization								
		e. No. of continuous staircases to terrace								
		g. Width of Corridor	1.5 M	1.5 M	MR					
		h. Door Size	1.0 M	1.5 M	MR					
		•	**							

A-2011-00/72

· 3	Compartmentation.					
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain 					
	Fire Dampers					
4	Smoke Management System.	1				
	BasementsUpper floors	30 a/c per hour 12 a/c per hour				
5	Fire Extinguishers					
e ,	Total numbersTypes	Aloc/Cortylse Prended and ISI marked — do — M.D.				
5	First-Aid Hose Reels.	AST MAIREU				
	Nozzle diameter	30 m 5 mm				
	Automatic fire detection and alarming system.					
	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 					
	MOTERA					
	MOEFA					
	Public Address System.					
	Automatic Sprinkler System. • Basement					
	- doublet					

						3	Ĭ.			
	• Upper Floor		8	<i>i</i>			ſ	-		
	Sprinkler above false ceiling			·						
11	Internal Hydrants	;						L		
	Size of riser/down-comer	10			1		` `			
	 Number of hydrants per floor 						1.			
	• Hose Box	-						F 12		
12	Vand II. 1			-	3		0			
12	Yard Hydrants.	1			r .		n e " "			
	Total number of hydrants			4 Pe P		2 J	7			
10	• Hose Box							11 8		
13	Pumping Arrangements.									,
	Ground Level									
	Discharge of main Pump				Mary.					
	> Head of Main pump						•	-	1	
	> Number of main pumps		1						-	8
	> Jockey Pump out put	-				 -	- I		-	
	> Jockey pump head					1	<u></u>	5	-	
	> Standby Pump out put					 -				
	> Standby Pump Head			= ,	. <u> </u>					
	> Auto Starting/ Manual					l ₂			•	
	stopping	e a	₩			Tay or				
2	> Pump House Access							1	s .	
	Terrace level					1.5				
	> Discharge of pump	· 1					1		1)	
	➤ Head of the pump					. *				
	Power Supply		2							
	> Auto Starting of pump						,	+		
14	Captive Water Storage for fire fighting.	1				3				
	Underground tank capacity	· · · · /	Pie		Taxa					
	> Draw-off connection								-	

11/11/1

	> Fire service inlet
	> Access to tank
	Overhead Tank capacity
15	Exit Signage.
16	Provision of Lifts.
	Pressurization of Lift Shaft
	Pressurization of Lift lobby
-	Communication In lift Car
	• Fireman's Grounding Switch
	• Lift Signage
17	Standby power supply
18	Refuge Area.
	> Total Area
	> Location
19	Fire Control Room
	Detector System Panel
	Flow Switch Panel
	PAi System Panel
	Batter backup
	Building Floor Plans
20	Special Fire Protection Systems for
	Protection of special Risks, if any:

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Signature of the Inspecting Officer Signature of the Inspecting Officer Name Name VIRENDRA SINGH Designation Designation