GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI - 110001

No: F 6/DFS/MS/2012/ School/ 1953 FIRE SAFETY CERTIFICATE

Certified that the McD Primary Circle School P-Block Mangol Pusi comprised of Sand tome upper owned/occupied by McD Roin School Complied with the fire prevention and fire safety requirement in accordance with Director of Education circular Dated:-01/03/2011 and verified by the officer concerned of Fire Service on 15.12. in the presence of Sunt-Scanita Kumaniand that the building/premises is fit for occupancy Educational building with effect from 29/05/12 for a period of ്രാട്ട് in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service

Issued on 29/05/12 at New Delhi.

Chief Fire Officer Delhi Fire Service

Dated: 29/05/12

Copy to:-

2 Ne Addl D'revor (Ech.) MCD Civic Centre Mintoo Road N. Delh. -1

Note:-This fire safety certificate is subject to compliance of the condition printed over leaf.

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non - functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified

from the concerned authorities.

5. Basement shall be used as per NBC

6. This NOC may not be treated in any case for regularizations of unauthorized. construction, if any,

7 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1	Name & address of the building MCD frimary Girls School, 1-18 lock, Mangol Pur, De					
2	Type of Occupancy Educational					
3	. Type of Case	: New Case/ Renewal				
4	Details of previous NOC : Letter	: Letter NoDated:				
5	5. Fire Safety directives letter No F-16/Este/cc/F.Safety/11/3238-3338 off. 13/2012					
6	6. Date of inspection 04 5-12012					
7	. Name of the Inspecting Officers:			-		
8	. Name and designation of officers from the building side :	ncipal-Sun	ita Kumasi			
9	. Year of Construction 200	25				
1 (O. Applicant's letter No. : No.	L dated 10	-2-2012			
S.	Minimum Standards on fire	Direct of Edu	Provided at site	Remarks		
No.	prevention and fire safety U/R 33	Requirement	•	MR/NMR		
1	Access to building	10/2	U.			
	Road width	Accessible	6 m	MIR		
	Gate width	-n-	3.26 m	MIR		
	Width of internal road	-11-	4 m	msR		
Number, Width, Type & Arrangement of Exits						
	a. Number of staircases	2	20	MIR		
	Upper Floors	2	2/	miR		
	Basements	NiL	Mic			
	b. Width of staircases	to Cm	1.52 m pull	M/R 4		
	Upper Floors	1.5 m	1.52 m lace	mia		
	Basements	Na' (NO.			
	c. Protection of exits	1 1	0.1.0			
	 Fire check door 		NIK			
	 Pressurization 					
	e. No. of continuous staircases to terrace	1	1	MIR		
	g. Width of Corridor	R	2.17 m	mile		
	h. Door Size	1 m	1.10 m	MIR		
	1					

-	4			
3	Compartmentation.		NIR	
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 			
4	 Smoke Management System. Basements Upper floors 	30 a/c per hour 12 a/c per hour	NIR	
5	 Fire Extinguishers Total numbers Types IS marking 	300 M 2 covered area for one ABC or CO2(2.5 ISI marked	of 6	MR
6	 First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m 5 mm	MIR	
7	 Automatic fire detection and alarming Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	g system.	NIR	
8	MOEFA		NR	
9	Public Address System. Automatic Sprinkler System. Basement		HIR	

1		
1	Upper FloorSprinkler above false ceiling	
11	Internal Hydrants	A11 A
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	N) A
12	Yard Hydrants.	Λ11 Λ
	Total number of hydrantsHose Box	13111
13	Pumping Arrangements.	NII A
	 Ground Level 	
	Discharge of main Pump	
	Head of Main pump	
	Number of main pumps	
	Jockey Pump out put	
	Jockey pump head	
	Standby Pump out put	
	Standby Pump Head	
	Auto Starting/Manual	
	stopping	
	Pump House Access	
	Terrace level	
	Discharge of pump	
	Head of the pump	
	Power Supply	
	Auto Starting of pump	
14	Captive Water Storage for fire fighting.	NR
	Underground tank capacity	, 1) 0
	Draw-off connection	

11-		
	 Fire service inlet Access to tank Overhead Tank capacity 	
15	Exit Signage.	NR
16	Provision of Lifts.	
	Pressurization of Lift Shaft	N/X
	Pressurization of Lift lobby	
	Communication In lift Car	
	Fireman's Grounding Switch	
	Lift Signage	
17	Standby power supply	NIR
18	Refuge Area.	
	> Total Area	NIA
	> Location	
19	Fire Control Room	XII 0
	Detector System Panel	N/K
	 Flow Switch Panel 	
	 PA System Panel 	
	 Batter backup 	
	Building Floor Plans	
20	Special Fire Protection Systems for Protection of special Risks, if any:	NiL

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

NW.

Defo heutat

(SHYAM LAL)