## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE

No. F6/DFS/MS/EH/2012/198/

Dated: 30/05/12

## FIRE SAFETY CERTIFICATE

Certified that the Clay Oven Restaurant located at D-1, Green Park, Ashirwad Building, New Delhi. comprised of Basement, Ground + 3 Upper Floor but the Restaurant is running on ground Floor only was granted NOC by this department vide letter No.F6/MS/DFS/EH/2009/1680 dated 08/06/09 The premises was re-inspected by the officer concerned of this department on 15/05/12 in the presence of Mr. D.S. Kalsi and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Group – D Assembly Building with effect from——30/01/L—for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued 30/05/12-at New Delhi by.

Chief Fire Officer Delhi Fire Service

ofe of

- Copy to:- (1) The D.E.O. (Restt.), Govt. Of NCT of Delhi, Office of the Commissioner of Excise, Entt. & Tax Department, L & J Block, I.P. Estate, Vikas Bhawan, New Delhi.
  - (2) Clay Oven Restaurant,D-1, Green Park, Ashirwad Building, New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

- 1 Name & address of the building:- Clay Oven Restaurant, D-1, Green Park, Ashirwad Building, New Delhi.
- Type of occupancy:- Group D Assembly Building

Type of case:- Renewal 3.

4. Details of previous NOC:-No. F6/MS/DFS/EH/2009/1680 dated 08/06/09

5. Fire safety directives No.- No

- 6. Date of inspection:- 15/05/12
- 7. Name of the inspecting officer:-A.D.O. S.S. Kaushik
- 8. Name & designation of officer From the building side:- Mr. D.S. Kalsi.
- 9. Year of construction:- 1998

10 Applicant's letter No:-Nil dated 15/03/12 Basement, Ground + 3 Upper Floor but the restaurant is running on ground floor only.

|  | restaurant is running on ground floor only.                 |                                    |                     |                     |  |
|--|---|------------------------------------|---------------------|---------------------|--|
| S.No.  | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement                        | Provided at         | Old Case<br>Remarks |  |
| 1.   | Access to Building  | NBC/BBL                            | site                | MR/NMR              |  |
|  | 1) Road width   | 15                                 |                     |                     |  |
|  | 2) Gate width   | 4.5 mtr.<br>N/A                    | 12 mtr.             | MR                  |  |
|  | 3)Width of internal road                                    |                                    | N/A                 | N/A                 |  |
| 2.   | Number Width Town 8 A                                       | N/A                                | N/A                 | N/A                 |  |
|  | Number, Width Type & Arrang A. Number of staircases         | ement of Exits                     |                     |                     |  |
| A SAME COMPANY   | 1. Upper floors   |                                    | 1                   |                     |  |
|  | 2. Basements  | N/A                                | N/A                 | N/A                 |  |
| 7  | B. Width of staircase                                       | 2 Nos.                             | 2 Nos.              | MR                  |  |
| -  | 1. Upper floors   |                                    |                     |                     |  |
|  | 2. Basements  | N/A                                | N/A                 | N/A                 |  |
|  |   | 1.25 & 93 cms.                     | 1.25 & 93<br>cms.   | MR 600              |  |
|  | C. Protection of exits                                      |                                    |                     |                     |  |
|  | 1. Fire check door  | N/A                                | N/A                 | N/A                 |  |
|  | 2. Pressurization   | N/A                                | N/A                 | N/A                 |  |
|  | D. No. of continuous staircase to terrace                   | One                                | one                 | MR                  |  |
|  | E. Width of corridor  | N/A                                | N/A                 | 27/4                |  |
|  | F. Door size  | 1 mtr.                             | 1 mtr.              | N/A<br>MR           |  |
|  | Compartmentation  |                                    |                     |                     |  |
|  | 1) Fire check door  | N/A                                | 2211                |                     |  |
|  | 2) Sealing of electrical shafts                             | N/A                                | N/A                 | N/A                 |  |
| A CANADA  | 3) Fire rating of shaft door                                | N/A                                | N/A                 | N/A                 |  |
|  | 4) Water curtain  | N/A                                | N/A                 | N/A                 |  |
|  | 5) Fire Dampers   | N/A<br>N/A                         | N/A                 | N/A                 |  |
|  | Smoke Management System                                     | N/A                                | N/A                 | N/A                 |  |
|  | 1) Basements  | 20 -/- 1                           |                     |                     |  |
| To the state of th | 2) Upper floors   | 30 a/c per hour<br>12 a/c per hour | Exhaust fan         | MR                  |  |
|  | Fire Extinguishers  | 12 a/c per nour                    | Exhaust fan         | MR                  |  |
|  | 1) Total numbers  |                                    | 00.00               | 10 10               |  |
|  | 2) Types Thamense   | -                                  | 08 Nos.             | MR                  |  |
|  |   | ISI Marked                         | ABC, Co2 &<br>W.Co2 | MR                  |  |

11, -4/5-

| •   | a) Pressurization of lift shaft                    | N/A             |               |       |  |  |
|-----|--|-----------------|---------------|-------|--|--|
| •   | · · · · · · · · · · · · · · · · · ·                |                 |               |       |  |  |
|     | Provision of Lifts.                                | Yes             | Provided      | MR    |  |  |
| - 4 | Exit Signage.                                      | 5,000 ltrs.     | 5,000 Ltr.    | MR    |  |  |
|     | d) Over head tank capacity                         | N/A             | N/A           | N/A   |  |  |
|     | c) Access to tank                                  | Yes             | Provided      | MR    |  |  |
|     | b) Fire service inlet                              | N/A             | N/A           | N/A   |  |  |
|     | Under ground tank capacity     Draw-off connection | N/A             | N/A           | N/A   |  |  |
|     | Captive Water Storage for Fire Fighting            |                 |               |       |  |  |
|     |  | Yes             | Provided      | MR    |  |  |
|     | FF-J   | Yes             | Provided      | MR    |  |  |
|     | P P  | 35 mtr. each.   | 35 mtr. each. | MR    |  |  |
|     | b) Head of pump                                    | LPM             | 180 LPM       | IVIIX |  |  |
|     | a) Discharge of pump                               | 450 LPM & 180   | 450 LPM &     | MR    |  |  |
|     | 2) Terrace level                                   |                 | - 1/2 2       | INA   |  |  |
|     | h) Auto starting/Manual stopping                   | N/A             | N/A           | N/A   |  |  |
|     | g) Stand by pump head                              | N/A             | N/A           | N/A   |  |  |
|     | f) Stand by pump output                            | N/A             | N/A           | N/A   |  |  |
|     | e) Jockey pump head                                | N/A             | N/A           | N/A   |  |  |
|     | d) Jockey pump out put                             | N/A             | N/A           | N/A   |  |  |
|     | c) Number of main pump                             | N/A             | N/A           | N/A   |  |  |
|     | b) Head of main pump                               | N/A             | N/A           | N/A   |  |  |
|     | a) Discharge of main pump                          | N/A             | N/A           | N/A   |  |  |
|     | 1) Ground level                                    | N/A             | N/A           | N/A   |  |  |
|     | Pumping Arrangement                                |                 |               |       |  |  |
| 3.  | Dumming  |                 | 1             | 11/// |  |  |
|     | 2) Hose box  | N/A             | N/A           | N/A   |  |  |
|     | 1) Total number of hydrants                        | N/A             | N/A           | N/A   |  |  |
|     | 1) Total www.l. Cl. i                              |                 |               |       |  |  |
| 12. | 9, 16 / 20   | Yes             | 1 Nos.        | MR    |  |  |
|     | 3) Hose box  | Yes             | 1 Nos.        | MR    |  |  |
|     | 2) Number of hydrants per floor                    | Yes             | 100 mm.       | MR    |  |  |
|     | 1) Size of riser/down-comer                        | ***             |               |       |  |  |
| 11. | Internal Hydrants                                  | N/A             | N/A           | N/A   |  |  |
|     | 3) Sprinkler above false ceiling                   |                 | Provided      | MR    |  |  |
|     | 2) Upper floors                                    | Yes             | Yes           | MR    |  |  |
| 0:  | 1) Basement  | Yes             | 77            |       |  |  |
| 10. | Automatic Sprinkler System                         | IVA             | N/A           | N/A   |  |  |
| 9.  | Public Address System                              | N/A             | Provided      | MR    |  |  |
| 8.  | MOEFA  | Yes             | N/A           | N/A   |  |  |
|     | 5) Hooter's Location                               | N/A             | N/A           | N/A   |  |  |
|     | 4) Alternate source of power                       | N/A             | N/A           | N/A   |  |  |
|     | 3) Location of repeater panel                      | N/A             | N/A           | N/A   |  |  |
|     | 2) Location of main panel                          | N/A             | N/A           | N/A   |  |  |
|     | 1) I Vne of detectors                              |                 |               |       |  |  |
| 7.  | Automatic Fire Detection & Alarm                   | ing System      | ies           | MR    |  |  |
|     | 3) Nozzle diameter                                 | 5 mm            | Yes           | MR    |  |  |
|     | 2) Length of hose reel hose                        | 30 m            | floor<br>Yes  | MD    |  |  |
|     |  | One at each flo |               | MR    |  |  |
|     | 1) Total number of each floor                      |                 |               |       |  |  |
| 6.  | First-Aid Hose Reel                                |                 | Yes           | MR    |  |  |
|     | 3) ISI marking                                     |                 |               |       |  |  |

~H/6-

|      | Pressurization of lift lobby Communication in lift car | N/A | N/A | N/A        |
|------|--|-----|-----|------------|
|      | communication in fift car                              | N/A | N/A | NT/A       |
| d) I | Fireman's switch                                       | N/A | N/A | N/A<br>N/A |

|     | e) Lift signage                      | N/A               | N/A                     | N/A |
|-----|--------------------------------------|-------------------|-------------------------|-----|
| 17. | Stand by Power Supply                |                   |                         |     |
| 18. | Refuge Area                          |                   | Provided                | MR  |
|     | Total area location                  | N/A               | N/A                     | N/A |
| 19. |                                      | N/A               | N/A                     | N/A |
| 19. | Fire Control Room                    | N/A               | N/A                     | N/A |
|     | a) Detector system panel             | N/A               | N/A                     | N/A |
|     | b) Flow switch panel                 | N/A               | N/A                     | N/A |
|     | c) PA system panel                   | N/A               | N/A                     | N/A |
|     | d) Battery backup                    | N/A               | N/A                     |     |
| -   | e) Building floor plan               | . N/A             | N/A                     | N/A |
| 20. | Special Fire Protection System for I | Protection of     | IN/A                    | N/A |
|     | 1 Total Control System for I         | Totection of spec | i special Risk, if any: | N/A |
| 8   |                                      |                   |                         |     |

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010/-----

Accordingly DFA is put up please.

Signature of the inspecting officer

Signature of the inspecting officer

Name

Designation

Name: - S.S. Kaushik.

Designation:- Assistant Divisional Officer.

DD South

\$2/8/8/h