GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2012/ School / 419

Dated: 07/02/12

FIRE SAFETY CERTIFICATE

TIKE SAFETT CERTIFICATE	
Certified that the Ryan Shalom Montessori Block-A-3	
Certified that the Ryan Shalom Montessori Block-A-3 Sech-16 Rohm Now Delhi 110085 comprised of Ground + one floor only - owned/occupied by Ryan different	rival
Shoup of Australia (and and tire complied with the fire prevention and fire	
safety requirement in accordance with Director of Education circular Dated:-01/03/2011 and verified by the officer concerned of Fire Service on (2-1-1-12) in the presence of	
MY Sam and that the building/premises is fit for occupancy for a period of o3/ears in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under	,
Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.	
Issued on	No.
ley	
,	6

Copy to:-

Me kincipal
Ryan Shalom Montersori
Block - A-3 Sectt-16
Rohmi Delin 1100 65.

2 The A Record College Rely.

Kushmere Juse Deem.

Chief Fire Officer Delhi Fire Service

De Jour

Note:-This fire safety certificate is subject to compliance of the condition printed over leaf.

1. All the means of escape shall be kept free of all type of obstruction all the time is

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non — functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per MG

6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.

The owner occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1.	. Ivaille & address of the building	RYAN	SHALOMMON	FESSORI. MOUN	-A-3, Sec.
2	Type of Occupancy		1 (Educationa		ini, selni
3	Type of Case		ase/ Renewal	47 me only	
4	Details of previous NOC	: Letter 1	Vo	Date	ed:
5	Fire Safety directives letter No	:	-		
6	. Date of inspection	: ,	12-1-12		
7	Name of the Inspecting Officers	3: n	o when ronte	и.	
8	Name and designation of officer	TS			
	from the building side	:	m-Sam	¥ **	
9	Year of Construction	:		F	
10	D. Applicant's letter No.	:			
S.	Minimum Standards on fi	ire	Circular 1-3-11	Provided at site	Remar
No.	prevention and fire safety U	/R 33	Requirement		MR/NN
1	Access to building				,
	Road width		2	10	
	Gate width		ACC 498 Was		m/R,
	Width of internal road		N-A	2.54 mbs	-
	:		N.A.		
2	Number, Width, Type & Arran	gement	of Exits		
	a. Number of staircases			*	
	 Upper Floors 		ne if meets	le cone	meets to
	 Basements 		Ø. A		-
	b. Width of staircases				
	 Upper Floors 			150	100 (0
}	• Basements		Isocm	150 cm	MIR
	c. Protection of exits				-
	Fire check door				
ы	 Pressurization 		~ A		
	e. No. of continuous staircases to	torrata	NA		
		terrace		one	-
	g. Width of Corridor		100cm dan for	Single door of	mir
	h. Door Size		111000 (411 112101 2001 1		

		i i		
	Compartmentation.	. NA		, s
	Fire check door			
	Sealing of electrical shafts	. /		
	Fire Rating of shaft door			
	Water Curtain			
	Fire Dampers	/	1	
1	Smoke Management System.		N-A	
	Basements	30 a/c per hour		х
	Upper floors	12 a/c per hour		
	. 8			,
5	Fire Extinguishers			
	 Total numbers 	Deplipe-248.	PYNO	MIR
	• Types	Deptype-268 Every 300m2are	a Deptype	-y -
	IS marking	ISI marked		2 ×
6	First-Aid Hose Reels.	<u> </u>	i ·	T
	Total numbers on each floor	MR	P	-
	Length of hose reel hose	30 m	-	
	Nozzle diameter	5 mm		
7	Automatic fire detection and alarming	system.	A	_
	Type of detectors			
	Location of Main Panel	/	35	
	Location of Repeater Panel			
	Alternate source of power			
	Hooters' Location			
8	MOEFA		P	
9	Public Address System.	NA		
10	Automatic Sprinkler System.	2/: A		
	Basement		/ /	

	• Upper Floor
	Sprinkler above false ceiling
11	Internal Hydrants
	Size of riser/down-comer
	 Number of hydrants per floor Hose Box
12	Yard Hydrants.
	Total number of hydrants
	Hose Box
13	Pumping Arrangements.
	Ground Level
	> Discharge of main Pump
	> Head of Main pump
	> Number of main pumps
	> Jockey Pump out put
	> Jockey pump head
	> Standby Pump out put
	> Standby Pump Head
	> Auto Starting/ Manual
	stopping
	> Pump House Access
	Terrace level
	> Discharge of pump
	> Head of the pump
	> Power Supply
	> Auto Starting of pump
14	Captive Water Storage for fire fighting.
	Underground tank capacity
	> Draw-off connection

	> Fire service inlet	N.A
	> Access to tank	
	Overhead Tank capacity	
15	Exit Signage.	
16	Provision of Lifts.	6/10
	Pressurization of Lift Shaft	
	Pressurization of Lift lobby	
	Communication In lift Car	
	• Fireman's Grounding Switch	
	• Lift Signage	
17	Standby power supply	
18	Refuge Area.	N//
	Total AreaLocation	N. A.
19	Fire Control Room	
	Detector System Panel	NA
	Flow Switch Panel	
	PA System Panel	
	Batter backup	
	Building Floor Plans	
20	Special Fire Protection Systems for	Labortary
	Protection of special Risks, if any:	sign exist at
		present.
	and the second s	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safe required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Del Fire Service Rules 2010/ issue shortcomings as noted at serial numbers......

Signature of the Inspecting Officer Signature of the Inspecting Officer Name Designation Dowal Designation