GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI-110001

No. F6/MS/DFS/GH/2012/ 2014

Dated: 01/06/12

FIRE SAFETY CERTIFICATE

Certified that the Shivlok Palace Guest House located at 4648-4650, Shora Kothi, Pahar Ganj, New Delhi-110055 comprised of ground floor (reception + 04 guest rooms + 01 store), 1st floor to 3rd floor (07 guest rooms at each floor) and terrace (Temp. Shed and DG set) total 25 guest rooms was granted NOC by this department vide letter No. F6/DFS/MS/GH/2009/1743 dated 11-06-2009. The premises was re-inspected by the officer concerned of this department on 25-05-2012 in the presence of Sh. Vijay Nagpal (owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of 25 guest rooms with effect from ...o.l.[.9.6]....2012 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued at New Delhi by.

CHIEF FIRE OFFICER
DELHI FIRE SERVICE

Copy to :-

- 1. The Addl. Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi 110049
- 2. Sh. Vijay Nagpal M/s Shivlok Palace, 4648-4650, Shora Kothi, Pahar Ganj, New Delhi-110055.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPECTION REPORT

Name & address of the building: Shive Type of Occupancy Type of Case	11.01	7	
2. Type of Occupancy	LOK Talace Gu	rest House, 4648-1	1650. Shara Kathi
3.00	dging House		Ne
Details of previous NOC : Letter 1	use/Renewal		To the same of the
Fire Safety directives letter No.	NO. F6/DPs/ms/GH	1/2009/1743 Date	d: 11-06-2000
The poet of the same of the sa			17 00 4609
Name of the Inspecting Officers	25-05-2012		
	Dis. Yadav	ADO	And the state of t
HUIII The build!			
2. Year of Construction	h. Vijay 1	tagpal (Own	99)·
O Applicant's letter No.			
Minimum Standards on fire	NIL Date	ed 14/05/12	
prevention and fire safety U/R 33	NBC	Provided at site	Remarks
Access to building	Requirement	P.S.S. Area	MR/NMR
		TIFC4	Old Cose
Road width	N.A.	- N.A -	
Gate width			MA
• Width of internal road	- XIA -	- NA -	NA
Number, Width, Type & Arrangement of	NA -	- NA -	NA
a. Number of staircases	DAMS		
 Upper Floors 			
* Basements		0)	MR
b. Width of staircases			
• Upper Floors			244
* Basements		119 Cms to 125 Cms	MR
c. Protection of exits	MA	XXA	NA
The state of the s		7	/ 4/1
• Fire check door	AIA	4.4	
^o Pressurization	NA	NA	NA
c. No. of continuous staircases to terrace	.NA	NA 01	NA
g. Width of Corridor	J 1 A		MK
h. Door Size	MA	NA	NA .
	1414	NA	esta:

_			h ₂	•
$ \frac{C}{C}$	ompartmentation.		,	
	 Fire check door 			
	 Sealing of electrical shafts 		NA	
	 Fire Rating of shaft door 		NA	
	 Water Curtain 			
	• Fire Dampers			
5	Smoke Management System.			
	• Basements	30 a/c per hour	NA	NA
	 Upper floors 	12 a/c per hour	NA Natural vestilas	is as. R
			MA	MA
	Fire Extinguishers			
	 Total numbers 		16	MR
	 Types 		Water Coz & DCP	MR
	• IS marking	ISI marked	Yes	MR
j - -	First-Aid Hose Reels,			
	· Total numbers on each floor	01	01	mR
	• Length of hose reel hose	30 m	Yes	MR
7	• Nozzle diameter	5 mm	Yes	mR
	Automatic fire detection and alarmiz	ig system.		
	• Type of detectors			
	Location of Main Panel			
	Location of Repeater Panel			
	• Alternate source of power		NA	
	Hooters' Location		and the state of t	
-	AND TOOLING			
8	MOEFA	Yes	Yes	MR
9	Public Address System.	Yes	yes	MR
10	Automatic Sprinkler System.			
N	• Baselment	NA	NA	MA

	• Upper Floor			
	Sprinkler above false ceiling	NA	NA	111
1.1	Internal Hydrants	NA	NA	NA
	 Size of riser/down-comer Number of hydrants per floor Hose Box 		NA	NA
12	Yard Hydrants.			
2	 Total number of hydrants Hose Box 			3
13	Pumping Arrangements.		XA	
	* Ground Level			
	Discharge of main Pump			1
and the state of t	Head of Main pump			./
	Number of main pumps		The second secon	
	> Jockey Pump out put			
	> Jockey pump head		MA	
	Standby Pump out put			
	Standby Pump Head	/		
	> Auto Starting/ Manual			
- B	stopping			
	> Pump House Access	/		
	* Terrace level			
	: > Discharge of pump	225 LPM	225 LPM	mr.
	Head of the pumpPower Supply	*	30 MAs.	mR.
	Auto Starting of pump	Yes	Bovided	MR
(Captive Water Storage for fire fighting.		Switch Provided at G. F	m K.
	• Underground		The same of the sa	
	 Underground tank capacity Draw-off connection 	NA	NA	NA
	or connection	XA	NA	NA

	Fire service inlet			
	Access to tank	MA	NA	MA
	• Overhead Tank capacity	MA	MA	MA
	Exit Signage.	2500 Citers	2500 Citers.	MR
)	Provision of Lifts.	Yes	Provided	MR
- > W	Pressurization of Lift Shaft			
	Pressurization of Lift lobby			
	Communication of Lift lobby			
	Communication In lift Car			
	Fireman's Grounding Switch	•	MA	
	* Lift Signage			
1	Standby power supply			
9	Refuge Area.		Yes	
	> Total Area		1.03	mk
. 0	> Location			
)	Vire Control Room		XIA	The state of the s
	Detector System Panel			
	Flow Switch Panel			/
	PAi System Panel			was a superior to the superior
	* Balter backup		NA	
	* Building Floor Plans			
	Special Fire Protection Systems for			
	Protection of special Risks, if any:	NA	KIA.	A

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Ecoping in view the substantial compliance of the minimum standards on fire prevention and lire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Shivlok Palace Gruest House, 4648-4650, Shora Kothi, Pahar Ganj, New Delhi. (5 8 25 m 5-2012 Signature of the Inspecting Officer Signature of the Inspecting Officer Name Name Dhaem vie srope yadan Designation Designation Aristont surround

Africal

Lantase) Do . Kenterly