GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE NEW DELHI-110 001.

No. F6/0F5/MS/School/2012/2089 Dated:7/6/12

FIRE SAFETY CERTIFICATE

Certified that the M.C. PRIMARY SCHOOL (Co-ed.) located at Sector-26, Rohini, Delhi-110 085, comprised of ground floor only and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Directorate of Education Circular No. F.16/Estate/Fire Safety/CC/2011/3298-3398 dated 01.03.2011 and verified by the officer concerned of fire service on 11.05.2012 in the presence of Smt. Hashmat, Principal and that the building/ premises is fit for occupancy class Educational class with effect from 7/6/12 for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on _______ at New Delhi by

Chief Fire Officer Delhi Fire Service 90

Smt. Hashmat, Principal, M.C. PRIMARY SCHOOL (CO-ED), Sector 26, Rohini, Delhi-110 085.

Copy to:

The Director. Dte. Of Education, Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering nonfunctional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

May kindly see the letter No Nil dated 15.02.2012 received from Principal, M.C. Primary School (Co-ed), Sector-26, Rohini, Delhi-110 085 from fire safety point of view. Premises was inspected by the ADO (Bawana) on 10.05.2012 & observed that the building is comprised of ground floor only and having plot area 4047 sq/ meter and covered area is 1600 sq. meter.

The point wise compliance Dte, of Education circular No. F.16/Estate/Fire Safety/CC/2011/3298-3398 dated 01.03.2011, are given below:

INSPECTION REPORT

1.	Name &address of the building	;	M.C. Primary School (loved) Sec-26
2.	Type of Occupancy	:	School (Education Bode) (if My
3.	Type of Case	:	New Case
4.	Details of previous NOC	:	_ N. A
5.	Fire Safety directives letter No.	:	f-16 Estate fise Safety c.c. 12011 3248-3398-1/3/2011
6.	Date of inspection	:	10.05.2012
7.	Name of the Inspecting Officers	:	SHRI RAJMAL KHOKHAR ADO
8.	Name and designation of officers	:	Smt. Hashmat
9.	From the building side	:	Psincipal
10.	Year of Construction	:	2000
11.	Applicant's letter No.	:	NºL dated 15.02.2012.

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks
1.	Access to building			MR/NMR
	Road widthGate width	Accessoble	Acceredou	md.
	Width of internal road	- uc	- EU -	-tec
2.	Number, Width, Type & Arrange	ment of Exits	-	
	a. Number of staircases	- VA AJANUS		
	Upper Floors	·		
	Basement	2	•	.*
	b. Width of staircases		_	*
	Upper Floors		_	~
	Basement	E	-	9
o .	c. Protection of exits	•		h
	Fire check door	-		
	Pressurization	~	~	~
	Fressurization		-	

d. No. of continuous staircases to terrace	'7		
e. Width of Corridor	_		~
f. Door size		CZ-	MR
Compartmentation.	eith		
Fire check door		266	
• Sealing of electrical shafts	*	5	6
• Fire Rating of shaft door		ent)	-
• Water Curtain	6		3m
• Fire Dampers	_	_	-
Smoke Management System.		NA	
	~	•	0
• Upper floors	<u>_</u>	V	. •
Fire Extinguishers			
Total numbers	6	6	mR
	t .	ABC TYPE	
	ISI marked	151 Marked	<u> </u>
Einst Aid Hose Door			
6. First-Aid Hose Rees.		NA	
Total numbers on each floor		t p-	*7
• Length of hose reel hose	30 m	}~	3
Nozzle diameter	5 mm	L	
Automatic fire detection and alar	NA		
Type of detectors	. •		
Location of Main Panel	°	"	-
Location of Repeater Panel	÷	-	,
Alternate source of power	~		
Hooter's Location	9		•
MOEFA		107	
	e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Rees. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alar Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power	e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Comoke Management System. Basements Upper floors Total numbers Types IS marking First-Aid Hose Rees. Total numbers on each floor Length of hose reel hose Nozzle diameter Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooter's Location	e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Comoke Management System. Basements Upper floors Total numbers Types ISI marked ISI marked ISI marked ISI marked ISI marked ISI marked Total numbers on each floor Length of hose reel hose Nozzle diameter Type of detectors Location of Repeater Panel Alternate source of power Hooter's Location

	ublic Address System.	O · N'A		
		Repursed 1/4.	Provided	may
	Automatic Sprinkler system	,	NA	
	Basement	700		• 7
	Upper Floor	_	~	gas.
	 Sprinkler above false ceiling 	<u>.</u> .	_	_
11.	Internal Hydrants		NA	
	Size of riser/down-comer			
	Number of hydrants per	¢9	•	
	floor	^	~	<u>~</u>
	Hose Box	ten .	_	~
12.	Yard Hydrants.		NA	
	Total number of hydrants	7	4 7)	0
	Hose Box	~	e	-
13.	Pumping Arrangements.		NA	
	Ground Level			
	Discharge of main pump	*		
	Head of Main pump	*	· .	^
s	Number of main pumps	•	2	
	Jockey Pump out put	-		p
		8	-	
	> Jockey pump head	, ,	-	•
	Standby pump out put		-	-
	Standby pump Head	~		+
	Auto Starting/Manual stopping	_		-
	Pump Hose Access	-	-	~
	Terrace level		4	_
**	Discharge of pump	~	•	-
	➤ Head of the pump		<u></u>	
	> Power supply	1	1	
	➤ Auto Starting of pump	-	_	_

	Captive Water Storage for fire fi	ohtina			
	T state state for the fi	NA			
	Underground tank capacity	ñ		6	
	Draw -off connection	-	-	0	
	Fire service inlet	ę	^	-	
	Access to tank	en en	,		
	Overhead Tank Capacity	_			
15	Exit Signage.	Repuised N.A	Provided	- MA.	
16	. Provision of Lifts	NA NA			
	Pressurization of Lift Shaft	7	-		
	Pressurization of Lift lobby	_			
	Communication In lift Car	-		-	
	Fireman's Grounding Switch	.	6	t-	
	Lift Signage	1	_		
17.	Standby power supply		NA		
18.					
	> Total Area		10 15		
		9		~	
10	> Location	_	-	-	
19.	Fire Control Room		No		
	Detector System Panel	₩			
	Flow Switch Panel	,	~	5	
	➤ PA system Panel	-			
8	➤ Batter backup		~		
	➤ Building Floor plans	_		~	
20.	Special Fire Protection Systems for Protection of special Risks, if any:	v	v	U	
	or special relates, it ally:				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial number

Signature of the Inspection Officer

Signature of the Inspection Officer

Name SHRI RAJMAL KHOKHAR

Name

Designation

Disignation

on Asst. DIV. OFFICER