GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : CONNAUGHT LANE NEW DELHI-110 001.

No. F6/965/ms/school/2012/2239

Dated: 22/06/12

FIRE SAFETY CERTIFICATE

Certified that the M.L. Govt. Boys Sr. Sec. School located at Narela, Delhi-110 040, comprised of two blocks A& B. A block is ground plus one upper floor and B block is ground floor only, have complied with the fire prevention and fire safety requirement in accordance with Directorate of Education Circular No. F.16/Estate/Fire Safety/CC/2011/3298-3398 dated 01.03.2011 and verified by the officer concerned of fire service on 01.06.2012 in the presence of Dr. Chander Singh, Principal and that the building/ premises is fit for occupancy class Educational class with effect from 22/06/12 for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on _____at New Delhi by

Chief Fire Officer
Delhi Fire Service

Dr. Chander Singh, Principal, M.L. Govt. Boys Sr. Sec. School, Narela, Delhi-110 040.

Copy to:

The Director,
Dte. Of Education,
Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

May kindly see the letter No MLGBSSS/NRL/2011/1413 dated 23.02.2012 received from Principal, M.C. Primary School, G-Block, Sector-16, Rohini, Delhi-110 089 from fire safety point of view. Premises was inspected by the ADO (Bawana) on 010.06.2012 & observed that the building is comprised of two blocks A & B. A Block consist of ground and one upper floor and B block consist ground floor only and having plot area 12000 sq/ meter and covered area is 4400 sq. meter.

The point wise compliance Dte. of Education circular No. F.16/Estate/Fire Safety/CC/2011/3298-3398 dated 01.03.2011, are given below:

INSPECTION REPORT

1.	Name &address of the building	:	School (Para blocks) A Blk - grad + 1 uppuflow
2.	Type of Occupancy	:	School (Paro blocks) ABIK - grand + lupraflow
3.	Type of Case	:	New Case
4.	Details of previous NOC	:	MA.
5.	Fire Safety directives letter No.	:	F.16 Estate Fin Safety (cc 2011 3298-3398 01.).3.11
6.	Date of inspection	:	01.06.2012
7.	Name of the Inspecting Officers	:	Sheri Ragmel Kholdun. ADD
8.	Name and designation of officers	:	Dr Chandler Sugh
9.	From the building side	:	Principal
10.	Year of Construction	:	2017
11	Applicant's letter No		MICASSINIPLI 2011/1413 At. 23.02.12

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building				
	Road width	Accemble	Accerentate	MR	
	Gate width	<u>—и —</u>	-u-	—ei ——	
	Width of internal road				
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	Two	Two	MR	
	Upper Floors			-u_	
	Basement	_		-	
	b. Width of staircases	150 cms each	150 Cm each	mn	
	Upper Floors		-u-	-u-	
_	Basement	-		~	
	c. Protection of exits		_	•	
	Fire check door		_	-	
	Pressurization	_		•	

d. No. of continuous staircases to terrace	Inoil	TWO	ml		
e. Width of Corridor	1/2 melis	2 melns	mr.		
f. Door size	Double Don	Double Day	mn		
Compartmentation.					
		1411			
			`		
Sealing of electrical shafts	-		-		
Fire Rating of shaft door	_	^	~		
Water Curtain	1.	-	-		
Fire Dampers	~	-			
Smoke Management System.		NA			
 Basements 					
			^		
o opper noors	-	-	-		
Fire Extinguishers					
Total numbers	12	22 -	mr		
• Týpes	3	12 Arse -	ma.		
IS marking	ISI marked	151 Marked	ma		
First-Aid Hose Rees.		NA	,		
Total numbers on each floor		_	~		
Length of hose reel hose	30 m		~		
Nozzle diameter	5 mm	_			
Automatic fire detection and alar	ming system.	NA	1		
Type of detectors	-	6	_		
Location of Main Panel	1-	_	_		
Location of Repeater Panel	·	-	_		
Alternate source of power		-	-		
Hooter's Location	15	-	-		
MOEFA	~	-	-		
	e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Rees. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alar Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooter's Location	to terrace e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers IS marking First-Aid Hose Rees. Total numbers on each floor Length of hose reel hose Nozzle diameter Type of detectors Location of Repeater Panel Alternate source of power Hooter's Location	to terrace e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Total numbers Types ISI marked First-Aid Hose Rees. NA Total numbers on each floor Length of hose reel hose Nozzle diameter Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooter's Location Tound Double Dank Double Dank Double Dank Dank Dank Dank Dank Dank Dank Dank		

J.	Public Address System.		AM		
10.	Automatic Sprinkler system				
10.	,	_	MA	_	
	Basement	,	-	~	
	Upper Floor	~	-	, ^	
	Sprinkler above false ceiling	_		-	
11.	Internal Hydrants		NA		
	Size of riser/down-comer	-			
	Number of hydrants per floor	^	_	•	
	Hose Box	•	_	_	
12.	Yard Hydrants.		NA		
	Total number of hydrants	3	^		
	Hose Box	-	-	_	
13.	Pumping Arrangements.		NA ,		
	Ground Level		,		
	Discharge of main pump		,	,	
	➤ Head of Main pump		•		
	Number of main pumps				
	➤ Jockey Pump out put	-		-	
	Jockey pump head	~		•	
	Standby pump out put	3		-	
	Standby pump Head			•	
	Auto Starting/Manual		1	-	
	stopping	~	,		
×	Pump Hose Access	•	•	<u> </u>	
	Terrace level			٠	
	> Discharge of pump	-	,		
	➤ Head of the pump		-		
	Power supply		,	-	
	> Auto Starting of pump	3	•		
		-		L	

14.	Captive Water Storage for fire figh	ting.	NA	
	Underground tank capacity		^	^
	> Draw -off connection	^	_	^
	➤ Fire service inlet		•	-
	> Access to tank	~		
	 Overhead Tank Capacity 	3	-	_
15	Exit Signage.	•	NA	_
16.	Provision of Lifts		NA	, -
	Pressurization of Lift Shaft		-	•
	Pressurization of Lift lobby	ř	1	-
	Communication In lift Car	•	· ·	۷
	Fireman's Grounding Switch	-	/	
	Lift Signage	±	-	-
17.	Standby power supply	*	NA	_
18.	Refuge Area	-	MH	,
	> Total Area	100	/	-
	> Location	-		_
19.	Fire Control Room	٠	NA	-
	Detector System Panel	·	/	
	> Flow Switch Panel		/	_
	> PA system Panel	_	¥ *	-
	➤ Batter backup	-	~	,
	Building Floor plans	_	~	_
20.	Special Fire Protection Systems for Protection of special Risks, if any:			L.

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial number

Signature of the Inspection Officer

Signature of the Inspection Officer

Name

SHRI RAJMAL KHIKHAR

Name

Designation

Disignation