## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI-110001

No.F6/DFS/MS/GH/2012/227 6

## Dated : $\frac{25}{96} / 2$

## **FIRE SAFETY CERTIFICATE**

Certified that the Shiv Guest House located at H-2, Green Park Ext., New Delhi. comprised of Basement, Ground + 2 Upper Floors (15 guest room) but the guest house is running on 1<sup>st</sup> & 2<sup>nd</sup> floor only was granted NOC by this department vide letter No.F6/MS/DFS/GH/09/2199 dated 21/07/09 The premises was re-inspected by the officer concerned of this department on 11/06/12 in the presence of Mr. Biju and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Lodging or Rooming House of Group – A with effect from 25 / 06 / 12 — for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 subject to conditions printed below.

Issued  $\frac{25/06/12}{}$  at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to:- (1) The Addl. Commissioner of Police, (Lic.), First Floor, PS Defence Colony, New Delhi

V

(2) Shiv Guest House, H-2, Green Park Ext., New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

H14-

## **INSPECTION REPORT**

- 1. Name & address of the building:- Shiv Guest House, H-2, Green Park Ext., New Delhi.
- 2. Type of occupancy:- Lodging or Rooming Houses Group-A.
- 3. Type of case:- Renewal
- 4. Details of previous NOC:-F6/MS/DFS/GH/09/2199 dated 21/07/09
- 5. Fire safety directives No.- No
- 6. Date of inspection: 11/06/12
- 7. Name of the inspecting officer:- A.D.O. S.S. Kaushik
- 8. Name & designation of officer:-From the building side:- Mr. Biju
- 9. Year of construction:- 1996
- 10. Applicant's letter No:- 31522-23/Addl.C.P./Lic./(H) dated 28/05/12 Basement, Ground + 2 Upper Floors (15 guest room) but the guest house is running on 1<sup>st</sup> & 2<sup>nd</sup> floor only.

CNL	16:			Old Case
S.No.	Minimum Standards on fire	BBL	Provided at	Remarks
	Prevention and fire safety U/R 33	Requirement	site	MR/NMR
l.	Access to Building	D 21 4 / 6 w 2 2		
	1) Road width		Provided	MR
STANCON MICH.	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arrange	ement of Exits		Bit 68907107
	A. Number of staircases			
AND THE PROPERTY OF THE PROPER	1. Upper floors	2 Nos.	Provided	MR
	2. Basements	N/A	N/A	N/A
N. C.	B. Width of staircase			1011
Standard Control of Co	1. Upper floors	oldrase	101 cms. & 81 cms.	MR old case
and the same of th	2. Basements	N/A O ISC	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	one	one	MR
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1 mtr.	1 mtr.	MR
	Compartmentation	A* 17*_ 1		
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
The state of the s	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
	Smoke Management System			
	1) Basements	30 a/c per hour	N/A	N/A
	2) Upper floors	12 a/c per hour	Exhaust fan	MR
	Fire Extinguishers	•		
	1) Total numbers		10 Nos.	MR
	2) Types	- N	ABC &W.Co2	MR

	2) ISI morbins	· Comment	a av			
6.	3) ISI marking	ISI Marked	Yes	MR		
v.	First-Aid Hose Reel					
	1) Total number of each floor	One	1 at each floor	MR		
	2) Length of hose reel hose	30 m	Yes	MR		
7	3) Nozzle diameter	5 mm	Yes	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
8.	5) Hooter's Location	N/A	N/A	N/A		
9.	MOEFA	Yes	Provided	MR		
9. 10.	Public Address System	N/A	N/A	N/A		
LU.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
11.	3) Sprinkler above false ceiling	N/A4arked	N/A	N/A		
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per floor	N/A	N/A	N/A		
12.	3) Hose box	N/A	N/A	N/A		
4.	Yard Hydrants		§.	or of the same of		
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
3.	Pumping Away gament	M/A	1 0.76			
-	Pumping Arrangement		~	The second secon		
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual stopping	N/A	N/A	N/A		
	2) Terrace level			2		
	a) Discharge of pump	450 LPM	450 LPM	MR		
	b) Head of pump	0.5	Provided			
	b) Head of pump	35 mtr.	35 mtr.	MR		
	c) Power supply	Yes	Provided	100		
	d) Auto starting of pump	Yes	Provided	MR		
ļ.,	Captive Water Storage for Fire Fightin	103	Yes	MR		
	1) Under ground touls and 't larte					
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	Yes	Provided	MR		
	d) Over head tank capacity	N/A	N/A	N/A		
	Exit Signage.	2,500 ltrs.	5,000 ltrs.	MR		
•	Provision of Lifts.	Yes	Provided	MR		
•	e _ 4	8- / n	20 - 20			
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A		N/A		
			TAILE	11//1		

pump,

	c) Communication 190					
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	Yes	Provided	MR		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Yes	D.G. Set	MR		
18.	Refuge Area	N/A	N/A	and the same of th		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
-	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A N/A	N/A		
	c) PA system panel	N/A		N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System for I	IN/A	N/A	N/A N/A		
Keeping in v	view of the substantial compliance of the man desired with the building we view of the substantial compliance of the man desired with the rules it is recommended to grant Fires 2010/  Accordingly DFA is put up pl	ninimum standard e Safety Certifica				
Signature of	the inspecting officer	Signature of the	e inspecting officer			
Name		Name:- S.S.Kau	MINICAL STATE OF THE STATE OF T	_		
Designation	and the state of		Assistant Divisional O			

DoSouth

Finnce of the manning standard