GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2012/School / 23/5

Dated:-27/06/12

		- 111 O7 11 E1	CENTILICATE			
		Λ	\mathcal{O}			
Certified	that	the Bellhwar 1	lemorial Fu	blic School	6-	Ble

FIRE SAFETY CERTIFICATE

Soleshirs Collection Lociety. Complied with the fire prevention and fire safety requirement in accordance with Director of Education circular Dated:-01/03/2011 and verified by the officer concerned of Fire Service on 1990 in the presence of the Carlonal and that the building/premises is fit for occupancy of Syears in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 27/06/12 at New Delhi.

Chief Fire Officer Delhi Fire Service

Copy to:-

1 The Head Master

Belesheror Memor d

fub. Jehool G-black frem 1790 I

Delen 1100 41

2 Me Descor of Col.
Sout of Delhi
old lett Dolu

Note:-This fire safety certificate is subject to compliance of the condition printed over leaf.

1. All the means of escape shall be kept free of all type of obstruction all the time size.

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non - functional of fire safety measures, management

shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per ਜਿਸਟ

6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any,

4 The owner occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

1

INSPECTION REPORT

Nome & address of the heilding P) 1 D10		. D			
 Name & address of the building Ba Type of Occupancy 	leshwer tubbic	School, G-Block	(1801) Deflar			
		Cr	1807) Delles-			
	4. Details of previous NOC : Letter No					
		111/3298-3398 OF	7, 1-3-2011			
1	12	1.				
or the inspecting officers. II.	DO-SHYAM LA		(
8. Name and designation of officers Sh. from the building side :	Shambu Nath	Bhagar (H.M.)			
0.37	2 (G+1)					
	- dated 20 -	2-7017				
S. Minimum Standards on fire			Remarks			
No. prevention and fire safety U/R 33	Director of Ed	Provided at site	MR/NMR			
	[3 20]		TVREV/ I VIEW			
Access to building	1 2016	0074	mlP			
 Road width 	Accessible	03.7M	MIR			
• Gate width	-do-	03 m	MR			
Width of internal road	-do-	N)R	-			
Number, Width, Type & Arrangemen	nt of Exits					
a. Number of staircases	2	2	MIR			
Upper Floors	2	2	MIR			
Basements	Níz	- Noice				
b. Width of staircases			mir			
 Upper Floors 	1-5 m	1.5 m & 95 cm				
• Basements	1.5 m	-do -	mlR			
c. Protection of exits	Mil	Mic	-			
• Fire check door		NR				
Pressurization		7				
e. No. of continuous staircases to terrace		1				
g. Width of Corridor						
	R	1.5	MIR			
h. Door Size	1 m	1 m -	MSR			

Compartmentation.		N110	
• Fire check door		1911	
Sealing of electrical shafts			
Fire Rating of shaft door			
Water Curtain			
• Fire Dampers			
Smoke Management System.		NID	
 Basements 	30 a/c per hour	1 1 0	
 Upper floors 	12 a/c per hour		
	300 m2 rovered	a -	mID
	area for one	8 /	MIR
	ABC OF COZRISH)	
	151 marked 2x7.		
		NIR	
V	30 m		
	5 mm		
Automatic fire detection and alarmin	g system.	NCI 1	
		////	7.5 (M. 100) 1.5 (
			2
 Location of Repeater Panel 			
Alternate source of power			
Hooters' Location			
MOEFA		NIR	
		NIR	
Automatic Sprinkler System.		A P 1 A	
 Basement 		NIR	
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarmin Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System.	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system. Type of detectors Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Fire Rating of electrical shafts 30 a/c per hour 12 a/c per hour 20 a/c per hour 12 a/c per hour 12 a/c per hour 13 av m Covered area for one 12 a/c per hour 13 av m Covered area for one 13 av m Covered area for one 15 mm Automatic fire detection and alarming system.	• Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers Smoke Management System. • Basements • Upper floors • Total numbers • Types • IS marking • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarming system. • Type of detectors • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Public Address System. Automatic Sprinkler System.

Upper FloorSprinkler above false ceiling	
Internal Hydrants	A 11 P
 Size of riser/down-comer Number of hydrants per floor Hose Box 	NIK
Yard Hydrants.	X(IA)
Total number of hydrantsHose Box	/4/0
Pumping Arrangements.	N11 D
 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access 	
 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	
Captive Water Storage for fire fighting.	A . 1 O
Underground tank capacityDraw-off connection	NIK
	 Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity

Baleshwar Mamorial Public Sch

?		
	 Fire service inlet Access to tank Overhead Tank capacity 	
15	Exit Signage.	NR
16	Provision of Lifts.	0111
	 Pressurization of Lift Shaft Pressurization of Lift lobby 	
	Communication In lift Car	
	Fireman's Grounding SwitchLift Signage	
7	Standby power supply	NIR
18	Refuge Area.	- 0.0
	Total AreaLocation	MA
19	Fire Control Room	
	Detector System Panel	NIK
	Flow Switch Panel	
	PA System Panel	
manufur most control and controlled	 Batter backup 	
	Building Floor Plans	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Mic

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

D.O(HW)

Shortcerning at SiNO. 2 (b) composited by school por 1 mittell

(SHYAMLAL)
ASSIH. Divn office