## GOVERNMENT OFNATIONAL CAPITAL TERRITORY OFDELHI HEADQARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F6/DGS/as/Cinema/2012/2317

Dated: 27/06/12

## FIRE SAFETY CERTIFICATE

Certificate that the **Mini Theater cum Commercial Complex** located at A-1-S. Part (S-26). Ajay Enclave, New Delhi comprised of Lower basement, Upper basement except Cinema Complex ground plus four upper floors, using Lower Basement and Upper Basement as parking & services, Ground floor as shops, First & second floor- vacant, third & fourth floor- vacant (for 02 Mini Theaters/Auditoriums with double height) owned / occupied by Management of Mini Theater cum Commercial Complex have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of Fire Service on 08.06.2012 in the presence of Sh.Vikas Lal Sh. Arvind Yadav. The building / premises is fit for occupancy class Group D assembly building Sub-Division D-6 w.e.f. the date of issue of this certificate for a period of **three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 27/66/12 at New Delhi by

Copy to:-

1. The Manager Mini Theater cum Commercial Complex A-1-S, Part (S-26), Ajay Enclave, New Delhi

2. The Executive Engineer (B) Hqrs. MCD Building Department, Civic Centre, Mento Road, New Delhi- 110002

CHIEF FIRE OFFICER DELHI FIRE SERVICE

Afr Mw Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

	1. Name & address of the ball !!	CTION REPORT				
	<ol> <li>Name &amp; address of the building</li> <li>Type of Occupancy</li> <li>Type of Case</li> </ol>	: Mini Theater Cu,	m Commercial Com	blex, A-1-S PortCs		
	3. Type of Case	Group D. S.	Ceb Div D-6	Ajay Enclave, NI.		
	4. Details of Previous NOC	New Case/Renewal				
	5. Fire Safety directives letter No.	: Letter No.	MIA	Date,		
	6. Date of inspection	C8: 06: 2012				
	7. Name of Inspecting Officer					
	8. Name and designation of officers	By. CFO Santokh	Singh D.O. H.L. Ar	nya BA.D.O P.S.Dal		
	From the building side			4		
	9. Year of Construction	Mr. Vikash lat, Sh. Arvind Yadav				
	10. Applicant's letter No.					
S.	Minimum Standards on fire	Nil das	ted 29.03.201.	2		
No.	prevention and fire safety U/R 33	NBC/BBL	Provided at	Remarks		
1.	Access to building	Requirement	site	MR/NMR		
	Road width					
	• Gate width	Accessible	18 mtr	MR		
	a so	06 mtr	06.20 mtr (Two)	MR		
2.	• Width of internal road	06 mtr	06 mtr	MR		
4.	Number, Width, Type & Arrangement	t of Exits				
	a. Number of staircases					
	• Upper Floors	Fire	Five	200		
	Basements		63 Nos + 02 Ramp	mR		
	b. Width of staircases	- One roung	63 NOS TOX RUMP	MR		
	Upper Floor	200 Cms 150 cms	one - 200 cms Four - 150 cms each			
	• Basements	1 Coome Pari	one-200 cmp Two Rom Two - 150 cmp each	MR		
	c. Protection of exits	130cmp (4ch	Two - 150 cms each	mR		
	<ul> <li>Fire check door</li> </ul>	Page	0			
	• pressurization	requirea	Provided	mR		
	d. No. of continuous staircases to	-00-	-do-	mR		
	terrace					
	e. Width of Corridor		Three			
	f. Door Size		212 cms, 335 cms	-		
3,		_	92 cms x 202 cms			
3,	Compartmentation		To comp K 40 % Cmp			
	Fire check door	0				
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	Provided	MR		
12 12 12 13 14 14 14 14 14 14 14 14 14 14 14 14 14	Fire Rating of shaft door	- do -	Sealed	MR		
	7701					
	Water Curtain	The same of the sa		1		
	W 1000 W					
4	• Fire Dampers	Required	Pravided	ma 2		
4.	Fire Dampers     Smoke Management System	Required	Provided	mR		
4.	<ul> <li>Fire Dampers</li> <li>Smoke Management System</li> <li>Basements</li> </ul>	/	Provided Exhaust Ducts	mr		
4.	Fire Dampers     Smoke Management System	Required  30 a/c per hour		m <sub>R</sub>		

w e e			8 8	_			
		12 a/c per hour					
5.	Fire Extinguishers						
	<ul> <li>Total numbers</li> </ul>	12 Nos at each floor	0				
	<ul> <li>Types</li> </ul>	Coz, WCoz, ABC	Provided - do -	me			
	<ul><li>IS marking</li></ul>	ISI marked	181 marked	mR			
6.	First-Aid Hose Reels		131 Marked	mr			
	<ul> <li>Total numbers on each floor</li> </ul>	7000	Provided	MR			
	<ul><li>Length of hose reel hose</li></ul>	30 m	- do -	MR			
	<ul> <li>Nozzle diameter</li> </ul>	5 mm	-do-	MR			
7.	Automatic fire detection and alarming	system					
	<ul> <li>Type of detectors</li> </ul>	Required	Provided (Smoke)	000			
l l	<ul> <li>Location of Main Panel</li> </ul>	,	At Ground Floor	MR.			
	<ul> <li>Location of Repeater Panel</li> </ul>	•	- do -	mR			
	<ul> <li>Alternate source of power</li> </ul>		D.G. Set of 160 KVA	m <sub>R</sub>			
	<ul> <li>Hooters' Location</li> </ul>		In Staircage	MAR			
	MOEFA	Required	Provided	MR			
	Public Address System	- do -	-do-				
10.	Automatic Sprinkler System						
	• Basement	Required	Provided	mR			
	<ul> <li>Upper Floor</li> </ul>	- do-	-do-	MR			
	<ul> <li>Sprinkler above false ceiling</li> </ul>	- do -	-do-	mR			
11.	Internal Hydrants						
	<ul> <li>Size of riser/down-comer(Both)</li> </ul>	Required	150 m.m	MR			
8. 9. 10.	<ul> <li>Number of hydrants per floor</li> </ul>	-	Too	MR			
	<ul> <li>Hose Box</li> </ul>		Two	MR			
12.	Yard Hydrants		j.				
	<ul> <li>Total number of hydrants</li> </ul>	-	09 Nos	MR			
	Hose Box	6.	09 Nos	MR			
13.	Pumping Arrangements						
	Ground Level						
	Discharge of main Pump	2850 CPM	2850 LPM	MR			
	Head of Main pump	GOM	.60 M	MR			
	Number of main pumps	700	Two	MR			
	<ul><li>Jockey Pump out put</li><li>Jockey pump head</li></ul>	450 LPM	450LPM	MR			
	> Standby Pump out put	60 M	70 M	MR			
	> Standby Pump Head	2850 LPM	28 SOLPM	MR			
	<ul><li>Auto Starting/Manual</li></ul>	GOM	70 M	MR			
	stopping		Both	MR			
To Produce the second			10011	)'/K			

A-1-S, Part (S-26), Ajoy Enclave, N.D.

	J						
	Pump House Access	Required	Provided	MR			
	Terrace level	/					
	Discharge of pump	-	4.SO LPM	mR			
	> Head of the pump		30 M	MR			
	Power Supply	Required	Provided	mR.			
de	Auto Starting of pump		-				
14.	Captive Water Storage for fire fighting						
	Underground tank capacity	200000 Ur	200000 Ltr	MR			
	Draw-off connection	Required	Provided	mR			
	Fire service inlet	-do-	- do -	mR			
	Access to tank	- do-	-do-	mR.			
	<ul> <li>Overhead Tank capacity</li> </ul>	20000 Ltr	20000 Ctr	mR			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.						
	Pressurization of Lift Shaft	Pontained	Provided	MR			
	<ul> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> </ul>	Required	-do-	•			
		-do-		mR			
		- do -	-do-	MR			
	Lift Signage	- do-	-do-	mr			
		-do-	-do-	MR			
17.	Standby power supply	Required	Provided	mr			
18.	Refuge Area.						
	Total Area		S	-			
	> Location	100	At 4th Floor	-			
19.	Fire Control Room						
19.	Detector System Panel	Required	Provided	mR			
	<ul> <li>Flow Switch Panel</li> <li>PA System Panel</li> <li>Batter backup</li> <li>Building Floor Plans</li> </ul>	-do-	-do-	me			
		- do -	-do-	mR			
		-do -	-do-	me			
		- 00	-CIV-	///			
20.	Special Fire Protection System for	MIA					
	Protection of special Risks, if any:	14/11		-			
	,						

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers.

Note: The Mini Theater Cum Commercial Complex comprised of Lower basement, Upper Basement, Ground Floor Blus Four cepter Floors. The height of the Building is 19.95mlr as per Cetter No F.6/ms/DFs/BP/Cinema/2003/907 dated 18.04.2003 lessing Basement as services and parking, G.f as Shops, F.f & S.F are vacant, third & Forth Floor with double height as two audi. Clying vacant). The entire building facilated with sprinkler syptem.

Signature of inspecting Officer

Name H.L. Aneja

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation AssH. Divisional Officer