GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DLEHI-110 001.

No. F.6/DFS/MS/School/2012/ 2357

Dated: 03/07/12

FIRE SAFETY CERTIFICATE

Certified that the **Nursery School of Krishna Geetanjali Foundation Society** (**Regd.**) located at Sec-10, Phase-I, Dwarka, New Delhi-110075 comprised of basement, stilt, ground floor plus two upper floors, having total 21 Rooms (Including Class Rooms, Staff Room, Office, Reception, Sports Room & Store etc.) owned/occupied by the Management of Krishna Geetanjali Foundation Society (Regd.) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of fire service on 30.06.2012 in the presence of Sh. V.P. Tandon (President). The building/ premises is fit for occupancy class educational w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

CHIEF FIRÉ OFFICER For DIRECTOR DELHI FIRE SERVICE

Copy to:-

1. Sh. V.P. Tandon (President), Krishna Geetanjali Foundation Society (Regd.), Sec-10, Phase-I, Dwarka, New Delhi-110075. (Ref. No. KGFS 2550 dated 09.05.2012.) Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non- functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

| | INSP | ECTION REPORT | An analysis of the second seco | | | |
|---|--|--|--|------------------|--|--|
| | Name & address of the building | g: Nursery School | of Krishna Goota | riali for date a | | |
| | 2. Type of Occupancy | School) Sec-10, | Ph-I, Dwarka NIN | | | |
| | 3. Type of Case | : New Case/Rene | The state of the s | | | |
| | 4. Details of Previous NOC | : Letter No | MA | Date | | |
| | 5. Fire Safety directives letter No | | . Letter NO M/A Date | | | |
| | 6. Date of inspection | 30.06 | 30.06.2012 | | | |
| rame of hispecting Officer . A. a. L. C | | | | | | |
| | 8. Name and designation of offic | ers | 7 / 11: Di 0 7 | 3. Banga | | |
| | From the building side | Sh. V. P. | Tondan | | | |
| | 9. Year of Construction | 2011 - 21 | | | | |
| | 10. Applicant's letter No. | | dated 09.05.1 |) | | |
| S. | Minimum Standards on fire | NBC/BBL | Provided at | Remarks | | |
| No. | prevention and fire safety U/R 33 | Requirement | THE RESIDENCE OF THE PARTY OF T | MR/NMR | | |
| 1. | Access to building | | | TALLY TATALLY | | |
| | Road width | Accessible | 12 mtr | MR | | |
| | Gate width | | 06mtr | MR | | |
| | Width of internal road | | | ///K | | |
| 2. | Number, Width, Type & Arrangeme | ent of Exits | | | | |
| | a. Number of staircases | The state of the s | | | | |
| | • Upper Floors | 7600 | Two | MR | | |
| | Basements | do - | -do-1 | MR | | |
| | b. Width of staircases | -do- | -do- | MR | | |
| | Upper Floor | 10 | | | | |
| 100 mm | Basements | 150 cms | 151cms, 90cms | MR | | |
| | c. Protection of exits | Colonia (agree) (agree | 160 cms, 123 cms | MR | | |
| | Fire check door | | - | | | |
| | pressurization | N/A | Page and | (Manus) | | |
| | d. No. of continuous staircases to | MIA | | - 427 | | |
| | terrace | | | | | |
| | e. Width of Corridor | January | One - | - | | |
| | f. Door Size | ~ | 150cms - | | | |
| | | | 110 cm & x 210 cm p | | | |
| 3. | Compartmentation | | THE CHIP FATO CMB | | | |
| | Fire check door | | | | | |
| | Sealing of electrical shafts | MIA | | _ | | |
| | Fire Rating of shaft door | | Sealed | 49 | | |
| | Water Curtain | MA | - | | | |
| | • Fire Dampers | MA | | | | |
| 1 | Annual Control of the | MIA | | | | |
| 4. | Smoke Management System | | | | | |
| | Basements | 30 a/c per | Exhaust fans | | | |
| | Upper flcors | hour | are Provided | mR | | |
| New Commission Street, | | | Matural Ventilation | m R | | |

| 14 | | | | |
|-----|--|-------------------|-------------------|-------|
| | | 12 a/c per | | |
| | | hour | | |
| 5. | Fire Extinct L | | | - |
| | Fire Extinguishers | | | |
| | rocarmumpers | Three at each Flo | or Parisi | |
| | • Types | A.B.C | Provided | mR |
| 6. | IS marking | ISI marked | -do- | MR |
| | First-Aid Hose Reels | | 131 marked | MR |
| | Total numbers on each floor | One | P | |
| | Length of hose reel hose | 30 m | Provided | MR |
| | Nozzle diameter | 5 mm | -do- | MR |
| 7. | Automatic fire detection and alarming | system | -do'- | MR |
| | Type of detectors | MIA | | |
| i i | Location of Main Panel | | | |
| | Location of Repeater Panel | MIA | | - |
| | Alternate source of power | MA | - | |
| | Hooters' Location | - | D.G.Set of 195KVA | MR |
| 8. | MOEFA | - | | |
| 9. | Public Address System | NIR | | |
| 10. | Automatic Sprinkler System | MIR | Provided 1 | MR |
| | Basement | | | 724 |
| | • Upper Floor | Required | Provided | me |
| | | MIA | | |
| 11. | Sprinkler above false ceiling | MIA | | |
| | Internal Hydrants | | | |
| | Size of riser/down-comer | | 100 m.m | |
| | Number of hydrants per floor | - | One | MR |
| 12 | • Hose Box | | | mR |
| 12. | Yard Hydrants | | One | In R |
| | Total number of hydrants | | J. | 1 |
| 10 | Hose Box | hamer . | | |
| 13. | Pumping Arrangements | | | |
| | Ground Level | | | 1 × 2 |
| | Discharge of main Pump | hala | | |
| | Head of Main pump | MA | | |
| | Number of main pumps | MA | _ | |
| | Jockey Pump out put | MA | | |
| | Jockey pump head | NIA | | . – |
| | Standby Pump out put | MIA | _ | _ |
| | Standby Pump Head | MA | - 1 | - |
| | Auto Starting/Manual | MA | | |
| | stopping | MIA | | |
| | | | | |

| | Pump House Access | NIA | _ | - | | | |
|--|---|-----------------------|------------|----------|--|--|--|
| | Terrace level | | | | | | |
| | Discharge of pump | 02 Nos 450 LPM Each | - Provided | MR | | | |
| | > Head of the pump | 30M Each | - do - | | | | |
| | Power Supply | Required (| - do- | MR MR | | | |
| | Auto Starting of pump | | Both | - | | | |
| 14. | Captive Water Storage for fire fighting | | | | | | |
| | Underground tank capacity | NIA | | | | | |
| | Draw-off connection | NIA | | | | | |
| | Fire service inlet | NIA | Provided - | M.R. | | | |
| | Access to tank | NIA | 1 FOVIMED | MIK | | | |
| | Overhead Tank capacity | | 100001100 | n. a | | | |
| | | 13000 GY | 15000 Ur / | MR | | | |
| 15. | Exit Signage. | 15000 ltr Required | Provided | mR | | | |
| 16. | Provision of Lifts. | | | | | | |
| | Pressurization of Lift Shaft | | | Ale Cont | | | |
| | Pressurization of Lift lobby | | | No Cift | | | |
| | Communication In lift Car Fireman's Grounding Switch | | - | _ ole - | | | |
| | | - | | - do - | | | |
| man of the control of | Lift Signage | | - | -do - | | | |
| | 0 101 | - | | -do - | | | |
| 17. | Standby power supply | Required | Provided | mR | | | |
| 18. | Refuge Area. | | | | | | |
| 10. | > Total Area | | | | | | |
| | > Location | MIA | | - | | | |
| | Location | NIA | - | <u> </u> | | | |
| 19. | Fire Control Room | | | | | | |
| | Detector System Panel | NIA | - | | | | |
| | Flow Switch PanelPA System Panel | MA | | | | | |
| | | NIA | Y | | | | |
| The state of the s | Batter backupBuilding Floor Plans | Required | Provided | - MR | | | |
| | Panding Hoor Fidits | NIA | 1 | | | | |
| 20. | Special Fire Protection System for Protection of special Risks, if any: | MA | | | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of Inspecting Officer

Name H.L. Aneja

Designation Divisional Officer

Name P. S. Dahiya

Designation ABAH. Divisional Officer.