GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DLEHI-110001.

No. F.6/DFS/MS/GH/2012/ 2 3.53

Dated: 03/67/12

FIRE SAFETY CERTIFICATE

Certified that the **Guest House South Indian** located at 10211-16, Padam Singh Road, Karol Bagh, New Delhi-110005 comprised of Basement, Ground Floor plus four upper floors, using basement as Hall/Storage, Ground Floor as reception, office, shops & hall, first, second & third floor each having ten guest rooms respectively (Total Thirty guest rooms) and forth floor having five rooms for staff use & a staff pantry. Above guest house was issued NOC vide this office letter No.F.6/DFS/MS/GH/2009/2371 dated 31/07/2009 owned/occupied by Sh. S. Murli Mani have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of fire service on 26.06.2012 in the presence of Sh. Balan Mani. The building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

CHIEF FIRE OFFICER
For DIRECTOR
DELHI FIRE SERVICE

Copy to:-

- 1. The Addl. Commissioner of Police (Lic.)

 1st floor, P.S., Defence Colony, New Delhi.

 (Re. No.28238/Addl. C.P./Lic.(H), Dated 11.05.2012)
- Mr. S. Murli Mani(Owner)
 G.H South Indian,
 10211-16, Padam Singh Road,
 Karol Bagh, New Delhi 110005.

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

| | 1 Name & address Lil Name & | TION REPORT | | | | | | |
|-----|---|--|------------------------------|--|--|--|--|--|
| | 2. Type of Occupancy | Name & address of the building: G. H South Indian, 18211-16, Padam Singh Rd, Karol Bag Type of Occupancy Residential (Gyest House) N.D. as | | | | | | |
| | 3. Type of Case | N.D-05 | | | | | | |
| | 4. Details of Previous NOC | : New Case/Renewal : Letter No. f. 6/DFS/ms/GH/09/2371 Date 31:07. | | | | | | |
| | 5. Fire Safety directives letter No | | | | | | | |
| | 6. Date of inspection | | NA | | | | | |
| | 7. Name of Inspecting Officer : | Look. 2012 D.O H.L. Aneja & A.D.O P.S. Dahiya. icers Sh. Balan Mani Before 1986 | | | | | | |
| | 8. Name and designation of officers | | | | | | | |
| | From the building side . | | | | | | | |
| | 9. Year of Construction | | | | | | | |
| | 10. Applicant's letter No. | 28238 Add1. C | P/LIC(H) dat | ad trans | | | | |
| S. | Minimum Standards on fire | NBC/BBL | Provided at | | | | | |
| No. | prevention and fire safety U/R 33 | Requirement | | Remarks | | | | |
| 1. | Access to building | The state of the s | Jite | MR/NMR | | | | |
| | Road width | Accessible | 09mtr | Me | | | | |
| | Gate width | Trace Soldie | 117cm8 | MR | | | | |
| | Width of internal road | | ITTEMB | mR | | | | |
| 2. | Number, Width, Type & Arrangement | | | | | | | |
| | a. Number of staircases | and the same of th | | | | | | |
| | • Upper Floors | 1000 | Two | MR | | | | |
| | Basements | -do- | -do- | MR | | | | |
| | b. Width of staircases | -do- | -do - | MR | | | | |
| | Upper Floor | | | | | | | |
| | | | 125cmp. 118cms | MR, Being Old Ca | | | | |
| | Basementsc. Protection of exits | | 116cms, 100cms | - do - | | | | |
| | | | Trocing, Too Cmp | 06 - | | | | |
| | Fire check door | MIA | | and the second s | | | | |
| | • pressurization | MIA | | | | | | |
| | d. No. of continuous staircases to | | | | | | | |
| | terrace e. Width of Corridor | | 7600 | :. | | | | |
| | f. Door Size | | 207cms, 265cms | | | | | |
| 3. | | - | 8-6cm x 207 cm 8 | | | | | |
| J. | Compartmentation | | | | | | | |
| | Fire check door | NIA | _ | | | | | |
| | • Sealing of electrical shafts | | Sealed | 2 2 | | | | |
| | Fire Rating of shaft doorWater Curtain | MIA | Ocaren | - | | | | |
| | | MIA | | | | | | |
| | • Fire Dampers | MIA | | | | | | |
| 4. | Smoke Management System | 14/4 | | | | | | |
| | Basements | 20 2/5 | ENLALET PA | and an advantage of the second | | | | |
| | Upper floors | 30 a/c per hour | Exhaust fans are Provided | MR | | | | |
| | | HOUF | Matural Ventilati | | | | | |

| | | | | (Appli | | |
|-----|--|--------------------|----------------------|----------------|--|--|
| | | 12 a/c per hour | | | | |
| 5. | Fire Extinguishers | | | | | |
| | Total numbers | Two afeach floor | 0 1 1 | | | |
| | Types | Co, Water Co, | Provided | MR | | |
| | IS marking | ISI marked | -do- | MR | | |
| 6. | First-Aid Hose Reels | | 151 Marked | MR | | |
| | Total numbers on each floor | One | Provided | b 0 | | |
| | Length of hose reel hose | 30 m | - do - | MR | | |
| | Nozzle diameter | 5 mm | - do: | m _R | | |
| 7. | Automatic fire detection and alarming | system | - 00 - | MR | | |
| | Type of detectors | NIA | | | | |
| | Location of Main Panel | MIA | | | | |
| | Location of Repeater Panel | MA | | | | |
| | Alternate source of power | _ | D. G Set of 82.5 KVA | | | |
| | Hooters' Location | MIA | 5 4,5C1 1, 64.5 KVA | | | |
| 8. | MOEFA | Required | Provided | MR | | |
| 9. | Public Address System | - do - | -do - | m R | | |
| 10. | Automatic Sprinkler System | | | | | |
| | Basement | Required. | Provided | me | | |
| | Upper Floor | NOIA | 1 | | | |
| 11 | Sprinkler above false ceiling | NIA | 1 | | | |
| 11. | internal Hydrants | | | | | |
| | Size of riser/down-comer | MA | | | | |
| | Number of hydrants per floor | NIA | | - | | |
| 17 | • Hose Box | MIA | : | | | |
| 12. | Yard Hydrants | | j. | | | |
| | Total number of hydrants | MIA | | | | |
| 13. | * Hose Box | NIA | | + | | |
| LJ. | Pumping Arrangements | | | | | |
| | Ground Level Discharge of main Pump | | | * | | |
| | and go of main rump | N/A | | | | |
| | Head of Main pumpNumber of main pumps | NIA | - | <u>.</u> | | |
| | > Jockey Pump out put | NIA | | | | |
| | > Jockey pump head | N/A | - | _ | | |
| | Standby Pump out put | NIA | | - | | |
| | Standby Pump Head | MIA | | | | |
| | Auto Starting/Manual | NIA | į. | | | |
| | stopping | NIA | | _ | | |
| | | | | | | |

| | Pump House Access | NIA | | _ | | |
|-----|--|--|-------------------|--|--|--|
| | Terrace level | | | | | |
| | Discharge of pump | 450 LPM | 450 LPM | MR | | |
| | Head of the pump | The state of the s | 30 M | MR | | |
| | Power Supply | 30 M Required | Provided | mR | | |
| | Auto Starting of pump | | | | | |
| 14. | Captive Water Storage for fire fighting | | | | | |
| | Underground tank capacity | NIA. | | _ | | |
| | Draw-off connection | MIA | - | - | | |
| | Fire service inlet | MIA | | _ | | |
| | Access to tank | MIA | | | | |
| | Overhead Tank capacity | ~ · · | 10000 Ctr | MR | | |
| 15. | Exit Signage. | Required | Provided | mR | | |
| 16. | Provision of Lifts. | | | | | |
| | Pressurization of Lift Shaft | NIA | | 10 | | |
| | Pressurization of Lift lobby | | | **** | | |
| | Communication In lift Car Fireman's Grounding Switch Lift Signage | MIA | 0 | Manual Control of the | | |
| | | _ | Provided | MR | | |
| | | - | - | Oldlift | | |
| | | Required | Provided | MR | | |
| 17. | Standby power supply | Required Required | Provided Provided | mR | | |
| 18. | Refuge Area. | | | | | |
| | > Total Area | A | 27 21 | | | |
| | Location | MIA | | | | |
| | | NIA | ← | _ | | |
| 19. | Fire Control Room | | | | | |
| | Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans | MIA | | - | | |
| | | NIA | | 2 | | |
| | | MIA | | | | |
| | | | Provided | MR | | |
| | | Required | rovided | ///\ | | |
| | | MIA | - | _ | | |
| 20. | Special Fire Protection System for Protection of special Risks, if any: | MIA | | | | |
| | | | 20 | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

Signature of Inspecting Officer

Name H.L. Ang'a

Designation Divisional Officer

Name P.S. Dahiya

Designation ASSH. Divisional Officer.