GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE

NEW DELHI-110 001.

No. F6/OFS/ons/school/2012/2376

Dated: 04/07/12

FIRE SAFETY CERTIFICATE

Certified that the B.N.N. G.S.K. Vidyalaya located at Khera Kalan, Delhi-110082, comprised of two blocks of ground floor only, have complied with the fire prevention and fire safety requirement in accordance with Directorate of Education Circular No. F.16/Estate/Fire Safety/CC/2011/3298-3398 dated 01.03.2011 and verified by the officer concerned of fire service on 12.06.2012 in the presence of Dr. Raj Rani Bansal, Principal and that the building/ premises is fit for occupancy class Educational class with effect from _oq/o//12_ for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ______at New Delhi by

J. J. Chief Fire Officer Delhi Fire Service

ole

Dr. Raj Rani Bansal, Principal, B.N.N.G.S.K. Vidyalaya, Khera Kalan, Delhi-110 082.

Copy to:

The Director, Dte. Of Education, Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering nonfunctional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

May kindly see the letter No DSIIDC/PD(Education)/2011-12/1059 dated 28.04.2012 received from Project Director (Education) regarding the issue of NOC for B.N.N.G.S.K. Vidyalaya, Khera Kalan, Delhi-110082 from fire safety point of view. Premises was inspected by the ADO (Bawana) on 11.06.2012 & observed that the building is comprised of two blocks of ground floor only and having plot area 43835 sq/ meter and covered area is 4297 sq. meter.

The point wise compliance Dte. of Education circular No. F.16/Estate/Fire Safety/CC/2011/3298-3398 dated 01.03.2011, are given below:

INSPECTION REPORT

1.	Name &address of the building	:	B. N. N. G. S. K. Vidyelaye, Khela Kalan,		
2.	Type of Occupancy	:	School (Education) The Blocks - G		
3.	Type of Case	:	New Case		
4.	Details of previous NOC	:	NA.		
5.	Fire Safety directives letter No.	:	F.16 Estate Fue Safety CC 2011 3298-3398 D+ 1-8-2011		
6.	Date of inspection	:	12.06.2012		
7.	Name of the Inspecting Officers	;	Sher Rapual Chokhur Ano		
8.	Name and designation of officers	:	Dr. Ry Ram. Bansul		
	from the building side	:	Principal		
9.	Year of Construction	;	1965		
10. Applicant's letter No. :		:	DSIIDC/PD/ Eduration 2011-12/1019 Dt 28.4-12		
S.	Minimum Standards on fire		meetor of NBC Edu Cicula Provided at site Remarks		
No	Prevention and fire safety U/R 33		MR/NMR MR/NMR		
1.	Access to building				
	Road width		Acceptable Acceptable MM		

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	onector of NBC Edu Cica	Provided at site	Remarks MR/NMR
1.	Access to building			
	Road width	Acceriable	Accersion	mu
	Gate width	- w-	w	-u-
	Width of internal road	_	_	_
2.	Number, Width, Type & Arrange	ement of Exits		
	a. Number of staircases	-	-	
	Upper Floors	^	-	
	Basement	_	_	
	b. Width of staircases	~		~
	Upper Floors	_	_	
	Basement	~		~
	c. Protection of exits			4
	Fire check door	`	4	_
	Pressurization	3 _ 6	Y	ı
				in the second se

d. No. of continuous staircases			-
d. No. of continuous staircases to terrace	•		-
e. Width of Corridor	-	-	
	Double Door 100	105 2 100 CM	mn
f. Door size Compartmentation.	ems even	NA	
Fire check door		_	_
Sealing of electrical shafts	^	c	· _
Fire Rating of shaft door			~
Water Curtain	^ .	-	-
Fire Dampers		-	
. Smoke Management System.		AN	
Basements			~
Upper floors	-	-	
5. Fire Extinguishers	3		J
	15	25	mp
Total numbersTypes		12 ABCTYPE 6 COL TYPE 7 HATEN CAN TYPE	m
IS marking	ISI marked	151 marked	mn
6. First-Aid Hose Rees.		WA	
Total numbers on each flo	or	_	
Length of hose reel hose	30 m	~	, -
Nozzle diameter	5 mm	-	
7. Automatic fire detection and a		or o	
Type of detectors		-	-
Location of Main Panel			
Location of Repeater Pan	el	~	
Alternate source of power	er -	-	
Hooter's Location	_	-	-
8. MOEFA	_	-	_

Public Address System. Automatic Sprinkler system	7	~	~
Automatic Sprinkler system			
Automatic Sprinker System	,	AU	
• Basement	-	~	
Upper Floor		_	
Sprinkler above false ceiling		~	<u></u>
Internal Hydrants		Au	1
Size of riser/down-comer			6
Number of hydrants per floor	-	^	~
	-		
		4 10	
	-		
	~	-	-
	1	NA	
2000 Section 1990			
2		-	,
	-	-	_
	_	_	-
> Number of main pumps	-	-	-
Jockey Pump out put	_	-	
Jockey pump head	-	-	-
> Standby pump out put	_		-
> Standby pump Head		-	
 Auto Starting/Manual stopping 		/	
> Pump Hose Access		L .	
Terrace level	-		•
Discharge of pump	_	~	-
➤ Head of the pump	-	~	,
> Power supply	_		_
> Auto Starting of pump	_	-	_
	 Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby pump out put Standby pump Head Auto Starting/Manual stopping Pump Hose Access Terrace level Discharge of pump Head of the pump Power supply 	• Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants. • Total number of hydrants • Hose Box Pumping Arrangements. Ground Level > Discharge of main pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby pump Head > Auto Starting/Manual stopping > Pump Hose Access Terrace level > Discharge of pump > Head of the pump > Power supply	• Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants. • Total number of hydrants • Hose Box Pumping Arrangements. Ground Level > Discharge of main pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby pump Head > Auto Starting/Manual stopping > Pump Hose Access Terrace level > Discharge of pump > Head of the pump > Head of the pump > Head of the pump > Power supply

	Captive Water Storage for fire figh	ting.	MA	
	Underground tank capacity	∞ ,	S	
	> Draw -off connection	_	gh	
	Fire service inlet	4	-	-
	Access to tank	4	-	~
	Overhead Tank Capacity	7	-	<u></u>
15	Exit Signage.			,
			NA	
16.	Provision of Lifts	~	-	₩.
	Pressurization of Lift Shaft			_
	Pressurization of Lift lobby			-
	Communication In lift Car		_	
	Fireman's Grounding Switch			
	Lift Signage	-	-	
17.	Standby power supply	-	NA	3
18.	Refuge Area	-	N V	-
	> Total Area		-	-
	> Location	-	_	
19.	Fire Control Room		NA	
	> Detector System Panel	-		
	> Flow Switch Panel	-	-	~
	> PA system Panel	_	~	:
	> Batter backup		-	
	Building Floor plans	-	_	-
20	. Special Fire Protection Systems for Protection of special Risks, if any:		~	_

The fire protection systems provided in the building were test chec	ked and found functional at the time of
inspection.	
Keeping in view the substantial compliance of the minimum stand	dards on fire prevention and fire safety
required under the rules it is recommended to grant Fire Safety Ce	rtificate under rule 35 of the Delhi Fire
Service Rules 2010/ issue shortcomings as noted at serial number .	
	2
Signature of the Inspection Officer	Signature of the Inspection Officer
Name RAJ MAL KHOKHAR	Name
Designation A 2.0	Disignation

SO (Ny)
CFOIT

lentet/12-22/6/12