GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI-110001

No.F6/DFS/MS/GH/2012 /2 428

Dated :----

FIRE SAFETY CERTIFICATE

Issued $-\frac{6/7/12}{}$ at New Delhi by.

Chief Fire Officer Delhi Fire Service

ore

Copy to:- (1) The Addl. Commissioner of Police, (Lic.), First Floor, PS Defence Colony, New Delhi

1

(2) A Seventeen Guest House, A-17,Defence Colony,New Delhi-110024.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

- 1. Name & address of the building:- A Seventeen Guest House, A-17, Defence Colony, New Delhi-110024.
- 2. Type of occupancy:- Residential Lodging or Rooming Houses.
- 3. Type of case:- Renewal
- 4. Details of previous NOC:-F6/MS/DFS/GH/09/1955 dated 03/07/09
- 5. Fire safety directives No.- Nil.
- 6. Date of inspection: 17/06/12.
- 7. Name of the inspecting officer:- A.D.O. S.S. Kaushik
- 8. Name & designation of officer

From the building side:- Mr. R.K. Singh.

- 9. Year of construction:- 1959.
- 10. Applicant's letter No:-31223/Addl.C.P./Lic.(H) dated 25/05/12 ground +2 upper Floors(14

| S.No. | M: | guest rooms) Old case | | | |
|--|---|-------------------------|--------------------|---------|--|
| S.INO. | Minimum Standards on fire | As per old NOC | | Remarks | |
| 1 | Prevention and fire safety U/R 33 | Required | site | MR/NMR | |
| 1. | Access to Building | | al His a said | 11/2 | |
| | 1) Road width | Approachable | Approachabl | e MR | |
| | 2) Gate width | N/A | Approachabl N/A | N/A | |
| | 3) Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Arrange | ment of Exits | | 14/11 | |
| | A. Number of staircases | | | | |
| STATE OF THE PERSON NAMED IN COLUMN NAMED IN C | 1. Upper floors | 2 Nos. | 2 Nos. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | Kaiste | 14/11 | IVA | |
| | 1. Upper floors | Required as per old NOC | 106 cms. & 96 cms. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | N/A | N/A | N/A | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous staircase to terrace | One | one | MR | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | 1 mtr. | 1 Mtr. | MR | |
| | Compartmentation | | | | |
| | 1) Fire check door | N/A | N/A | N/A | |
| B | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| | Smoke Management System | | | | |
| | 1) Basements | 30 a/c per hour | N/A | N/A | |
| | 2) Upper floors | 12 a/c per hour | N/A | N/A | |
| | Fire Extinguishers | - 114.2 | 14/11 | | |
| | 1) Total numbers | | 7 Nos. | MR | |
| | 2) Types | 1 | ABC. | MR | |
| | 3) ISI marking | ISI Marked | Yes | MR | |
| | First-Aid Hose Reel | | - 40 | 14117 | |

| | 1) Total number of each floor | | | |
|-----|---|-------------|-------------------|------------|
| | | | One at each floor | MR |
| | 2) Length of hose reel hose | 30 m | | |
| | 3) Nozzle diameter | 5 mm | Yes | MR |
| 7. | Automatic Fire Detection & Alarm | ing System | Yes | MR |
| | 1) Type of detectors | N/A | 1 / . | |
| | 2) Location of main panel | | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA | N/A | N/A | N/A |
| 9. | Public Address System | N/A | N/A | N/A |
| 10. | Automatic Sprinkler System | N/A | N/A | N/A |
| | 1) Basement | 77/1 | | |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false ceiling | N/A | N/A | N/A |
| 11. | Internal Hydrants | N/A | N/A | N/A |
| | 1) Size of riser/down-comer | | | |
| | 2) Number of hadrant | N/A | N/A | N/A |
| | 2) Number of hydrants per floor3) Hose box | N/A | N/A | N/A |
| 12. | | N/A | N/A | N/A |
| 14. | Yard Hydrants | 1.3 | | 11/21 |
| | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | N/A |
| 13. | D | | 1471 | IN/A |
| 15. | Pumping Arrangement | * . | *. | |
| | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main pump | N/A | N/A | |
| 12 | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual stopping | N/A | N/A | N/A |
| | 2) Terrace level | | N/A | N/A |
| | a) Discharge of pump | 450 LPM | 450 LPM | |
| | b) Head of pump | 30 mtr. | | MR |
| | c) Power supply | N/A | 30 Mtr. | MR |
| | d) Auto starting of pump | N/A N/A | N/A | N/A |
| l. | Captive Water Storage for Fire Fightin | IN/A | N/A | N/A |
| | Under ground tank capacity | | | |
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | N/A | N/A | N/A |
| | Exit Signage. | 2,500 Ltrs. | 2,500 Ltrs. | MR |
| | Provision of Lifts. | Yes | Provided | MR |
| | | N/A | N/A | N/A |
| | a) Pressurization of lift shaft | N/A | N/A | |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A N/A |
| | d) Fireman's switch | - 1 6 A | | I INT / A |

| 7 | e) Lift signage | N/A | N/A | 127/4 |
|-----|--|--------------|-----|-------|
| 17. | Stand by Power Supply | N/A | | N/A |
| 18. | Refuge Area | | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| 231 | | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| 3 | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | |
| | d) Battery backup | N/A | | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for | Protection 6 | N/A | N/A |
| | Special Fire Protection System for Protection of special Risk, if any: | | | N/A |

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010

Accordingly DFA is put up please

Signature of the inspecting officer

Signature of the inspecting officer

Name:-

Designation:-

Name: - S.S. Kaushik

Designation: - Assistant Divisional Officer