GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F6/DFS/MS/ school/2012/2524.

Dated: 13/07/12

FIRE SAFETY CERTIFICATE

Certified that Govt Boys Senior Secondary School No-3, Tughlakabad Extn., New Delhi (School ID-1925049), comprised of ground Plus one upper floor Owned/Occupied by Govt Boys Senior Secondary School No-3 have complied with the fire prevention and fire safety requirements in accordance with Circular No. F-16 /Estate/CC/Fire Safety/2011/3298–3398 dated 01/03/2011 & Rule 33 of the Delhi Fire Service Rules, 2010 and verified by officer concerned of Delhi Fire Service on 12.06.2012 in the presence of Mrs. Juhi Aggarwal, Principal of the school and that the building / premises is fit for occupancy class- "Educational building" with effect from 13/07/12 for a period of 03 years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule 2010.

Issued on -----13/07/12 at New Delhi by

CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy To: -

1. The Directorate of Education, Govt. of NCTD, Old Secretariat, Delhi

2. The Principal, Govt Boys Senior Secondary School No-3, Tughlakabad Extn., New Delhi-19

Conditions for the validity of fire safety Certificate

- All the Fire Safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities nonfunctional shall be the responsibility of the management.
- Building Sanctioning Authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- 4. The Basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

| 1. | Name and address of the building | : Gout : Tugh | Boys Senior Lakabad Beka | Secondary Senson, New | Dolli. 19 | |
|-----|---|------------------|-----------------------------|-----------------------|--------------------------------|--------|
| 2. | Type of Occupancy | : Edu | eatinal | | | |
| 3. | Type of Case | : New | ě | | | |
| 4. | Details of previous NOC | : NoU | • | | | |
| 5. | Fire Safety Directives letter No | : Nul | | dated | | |
| 6. | Date of Inspection | : 12.0 | 6.2012 | | | |
| 7. | Name of the Inspecting Officer | : Rayor | n Madelia | Asett. Da. | Officer (MRS) | |
| 8. | Name and designation of the Officers from the building side | : <u>Mro-</u> | July Aggar | | eipel) | , |
| 9. | Year of Construction | : Neil | 00 | | d plan on up -2 Blocks & 10 | per fl |
| 10. | Applicant's letter No. | : Nil | | Consista | -2 Blocks & 10 | Pota |
| S. | Minimum Standards on Fire Prev | ention | NBC | Provided at | Remarks | 1 |
| No | and Fire Safety U/R 33 | | Requirement | site | MR/NMR | |
| 1 | Access to building | | | | | |
| | D 1 '1/1 | | | | | 7 |

| S. No. | Minimum Standards on Fire Prevention and Fire Safety U/R 33 | NBC Requirement | Provided at site | Remarks MR/NMR |
|-----------|---|--------------------|------------------|-------------------|
| 1 | Access to building | | - | 2 |
| | Road width | 9 M45 | 9 Mts | MIR |
| | Gate width | 9 Mts Reguned | 5 M/s | MIR |
| | Width of internal road | NA | NA | NA |
| 2 | Number, Width, Type & Arrangement of Exi | ts | | |
| | Number of Staircase | | a? * | |
| | Upper floors | t | BIK-II - 2 | MIR |
| | > Basement | NA | NA | NA |
| | Width of Staircase | | | |
| | > Upper floors | 1,5 M+s | 1.5 mts ede | h MIR |
| | > Basement | NA | NA | NA |
| | Protection of Exits | NA | | |
| | Upper floors | | | |
| | > Basement | | | |
| | No of Continuous Staircases to terrace | NA | NA | NA |
| | Width of Corridor | NA | NA | MA |
| | Door Size | 1.0 Mts | 1.0 mts | MIR |

| 3 | Compartmentation | | | |
|----------|---|--|---------------------|-----|
| 3 | | | NA | |
| * | Fire check door | | | |
| | Sealing of electrical shafts | | | |
| | Fire rating of shaft door | | | |
| | Water curtain | | | |
| | Fire Dampers | | | |
| 4 | Smoke Management System | | NA | |
| | Basements | 30 a/c Per hour | | |
| | Upper Floors | 12 a/c Per hour | | |
| 5 | Fire Extinguishers | | * | |
| | Total Number | One/300 m 2 | 14 Nos. | MIR |
| | • Types | ABE & CO2 | 14 Nos. Parvided | MIR |
| | IS marking | ISI mark | yes | MIE |
| 6 | First-Aid Hose Reels | and the second control of the second control | NA | , |
| | Total Number on each floor | /Per Floor | | |
| | Length of hose reel hose | 30 m | | |
| | Nozzle diameter | 5mm | | |
| 7 | Automatic Fire Detection and Alarmin | g System | NA | |
| | Type of detectors | / | 1 / | 1 |
| | Location of Main Panel | | | / |
| | Location of Repeater Panel | | | / / |
| | Alternate source of power | | | |
| | Hooter's Location | | 1 | / |
| 8 | MOEFA | | NA | |
| 9 | Public Address System | | NA | |
| 10 | Automatic Sprinkler System | | NA | |
| | Basement | | | / |
| | Upper Floor | | | |
| e | Sprinkler above false ceiling | | | |
| 11 | Internal Hydrant | | NA | |
| | | | | |
| | Size of riser/down comer | | | |
| | Size of riser/down comerNumber of hydrants per floor | | | |
| | | | | |
| 12 | Number of hydrants per floor | | NA | |
| 12 | Number of hydrants per floorHose Box | | NA | |

| 13 | Pumping Arrangements | | , |
|----|--|-----|-------|
| 63 | Ground Level | | NA |
| | ➤ Number of main pump | | |
| | Discharge of main pump | | |
| | ➤ Head of main pump | | |
| | ➢ Jockey pump out put | . / | |
| | ➢ Jockey pump Head | / | |
| | ➢ Standby pump out put | / | |
| | > Standby Pump Head | | |
| | Auto Starting/Manual stopping | | |
| | ➤ Pump House Access | | |
| | Terrace level | / | NA |
| | ➢ Discharge of pump | | |
| 9 | ➤ Head of the pump | | |
| | ➤ Power Supply | | |
| | > Auto starting /Manual stopping | | |
| 14 | Captive Water Storage for Fire Fighting | | NA |
| | Underground tank capacity | / | |
| | Draw-off connection | | |
| | ➤ Fire service inlet | | |
| | Access to tank | | |
| | Overhead tank capacity | | |
| 15 | Exit Signage | | NA |
| 16 | Provision of Lifts | н | NA |
| | Pressurization of Lift Shaft | | |
| | Pressurization of Lift lobby | | 1/2 / |
| | Communication in lift Car | | |
| | Fireman's Grounding Switch | | |
| | Lift Signage | | |
| 17 | Standby Power Supply | | NA |
| 18 | Refuge Area | | NA |
| | Total Area | | |
| | • Location | | |
| 19 | Fire Control Room | | NA |
| | Detector System Panel | | |
| | Flow Switch Panel | | |
| | PA System Panel | | |
| | Battery back up | | |
| | Building Floor Plans | | |

| Water Control of the | 20 | Special Fire Protection System for Protection of special risk, if any | NA | NA | NA | |
|---|-----|--|----|----|----|--|
| ton | · V | | | | | |

The Fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules , It is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / issue shortcomings as noted at serial Number.

DO (Søuth)

4171/2

Signature of Inspecting Officer
Name : RAJAN WADEHRA

Designation: ASST. DIV. OFFICER