## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/ 2 554

Dated: 17/07/12

#### FIRE SAFETY CERTIFICATE

Certified that Shree Delhi Gujrati Samaj located at 2, Raj Niwas Marg, Civil Lines, Delhi comprised of ground floor (Reception + 18 guest rooms + 01 dormitory), first floor (27 guest rooms + 01 dormitory), second (32 guest rooms + 02 dormitory) & third floor (21 guest rooms + 05 dormitory) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/09/1376 dated 19-05-2009. The premises was re-inspected by the officer concerned of this department on 23-06-2012 in the presence of Kamal Bhatnagar, Asstt. Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 10 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 17/67/12 at New Delhi by.

Chief Fire Officer for Director Delhi fire service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1<sup>st</sup> floor, New Delhi

2. The Manager, Shree Delhi Gujrati Samaj, 2, Raj Niwas Marg, Civil Lines, Delhi

## Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

#### **INSPECTION REPORT**

1	. Name & address of the building: Shree.  Type of Occupancy: Lod	Delhi Gujrati	Samaj, 2 Rajne	was plang, cein'l lis			
2	. Type of Occupancy : Lod	ging House.		Delhe.			
3	. Type of Case : New C	ase/ Renewal					
4	Details of previous NOC : Letter No. F6/DF2/MS/GH/09/1376 Dated: 19/5/2009						
5	5. Fire Safety directives letter No :						
6	6. Date of inspection : $23/6/2012$						
7. Name of the Inspecting Officers: N.K. Chatto badhy cy, ADO (HQ)							
8	. Name and designation of officers		<b>"</b>				
9. Year of Construction : Mr. Samul Pohat nagar, AssH. Manages							
							10
S.	Minimum Standards on fire	NBC	Provided at site	Remarks			
No.	prevention and fire safety $U/R$ 33	Requirement		MR/NMR			
1	Access to building						
	<ul> <li>Road width</li> </ul>	-	12 mt	MR			
	• Gate width	-	3.65 mr	me being			
	<ul> <li>Width of internal road</li> </ul>		3.65 mt	MR being old			
2	Number, Width, Type & Arrangement	of Exits					
	a. Number of staircases	-	-				
	• Upper Floors		02	MR			
	• Basements	_					
	b. Width of staircases	-	-				
	• Upper Floors	-	1.20mt, 1.36mt	MR			
	• Basements						
	c. Protection of exits	-		*			
	<ul> <li>Fire check door</li> </ul>	Not required	_				
	<ul> <li>Pressurization</li> </ul>	Not required		_			
	e. No. of continuous staircases to terrace	_		1			
	g. Width of Corridor	-	1.46mt	MR			
	h. Door Size	_	1.0mt	MR			
			-	_			
3.	Compartmentation.	Not required	_	_			

GF - Reception + 18 Gustroom +01 Dormilory Ist floor - 27 Gust nows + 01 dormilory and floor - 32 Gust nows + 02 dormilory 3rdfloor - 21 Gust now + 05 dormitory

7

				1	
	• Fire check door				
	<ul> <li>Sealing of electrical shafts</li> </ul>				
	• Fire Rating of shaft door				
	Water Curtain				
	• Fire Dampers			9	
4	Smoke Management System.	required			
	<ul> <li>Basements</li> </ul>	30 a/c per hour		-	
	<ul> <li>Upper floors</li> </ul>	12 a/c per hour			
5 Fire Extinguishers					
	• Total numbers 48	. ABC - 08	provided provided	MR	
	· Types water CO2, ABC, CO2	CO2 - 20 Walter CO2 - 20		MR	
	IS marking	ISI marked	provided	MR	
6	First-Aid Hose Reels.		,		
	Total numbers on each floor	02	provided	MR	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	pourded	MR	
	Nozzle diameter	5 mm	provided	MR	
7	• Total numbers on each floor • Length of hose reel hose • Nozzle diameter  • Nozzle diameter  Automatic fire detection and alarming system.  • Total numbers on each floor  30 m  provided  MR  provided  MR  provided  MR  provided  MR  provided  MR  provided  MR  provided  MR				
	Type of detectors		/		
	<ul> <li>Location of Main Panel</li> </ul>				
	<ul> <li>Location of Repeater Panel</li> </ul>				
				7	
	Alternate source of power			i i	
	Hooters' Location				
8	MOEFA	Not required		-	
9	Public Address System.	Required	provided	MR	
10 Automatic Sprinkler System. Not required.					
	<ul> <li>Basement</li> </ul>				
	Upper Floor				
	Sprinkler above false ceiling				
	La L	required			
11	Internal Hydrants Not	required			
	Size of riser/down-comer				

7

Shree Delhi Gujrati Samaj, 2, Raj Nivas Mang Civillines, Delli-54

	- Trificos,	Della - 5 9	×	U
	<ul> <li>Number of hydrants per floor</li> </ul>		4	
	Hose Box			
12	Yard Hydrants. Not Roge	'u'red'		
12		Дүев		
	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>			
13				
13	Ground Level			/
	Discharge of main Pump			
	Head of Main pump			
	Number of main pumps			
	Jockey Pump out put			
	Jockey pump head			,
	Standby Pump out put			
	Standby Pump Head			
	Auto Starting/ Manual			
	stopping			· ·
	Pump House Access			
	Terrace level			
	<ul><li>Discharge of pump</li></ul>		450 LPM 35mt	MR
	Head of the pump	_	35mt	MR
	Power Supply	Requis	provided	MR
	Auto Starting of pump	_	Starting Switch	MR
14	Captive Water Storage for fire fighting	<u> </u>		
	<ul> <li>Underground tank capacity</li> </ul>			
	> Draw-off connection			
	Fire service inlet			
	Access to tank			
	Overhead Tank capacity		25000 16.	MR
15	Evit Cianage	Required	provided	MR
16	Exit Signage.  Provision of Lifts.		Reft pourda	
10		1		
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	Not require	<u> </u>	



# Shree Delhi Gujoato Samaj, 2. Raj Nius Marg, Cévil Lines, Delhi-54

	Pressurization of Lift lobby	Hot required	-		
	Communication In lift Car	Required	provida	MR	
	Fireman's Grounding Switch	Reguerred	provided	MR	
	Lift Signage	Required	provided	MR	
17	Standby power supply	Roquira	16 KUA	MR	
18	Refuge Area.	quired'			
	> Total Area	1			
	> Location				
19	Fire Control Room Not requeited				
	Detector System Panel				
	Flow Switch Panel				
	<ul> <li>PA System Panel</li> </ul>				
	Batter backup				
	Building Floor Plans				
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	02 CO, lyte fire exterposter provided hear \$1 paner	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

1 1.1

Signature of the Inspecting Officer

Name

Designation

Name (M.K.CHATTOPADHYAY)

Designation ADO (HQ)