GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6 / DFS / MS / 2012 / GH / 2565

Dated 18/07/12

FIRE SAFETY CERTIFICATE

Certified that the "Mohan International" Guest House, located at 8574, Arakashan Road, Pahar Ganj, New Delhi, comprised of Ground + Five upper floors having 43 guest rooms (Ground floor has Reception + 06 guest rooms + 01 office + Lobby, First to third floor has 10 guest rooms at each floor, Fourth floor has 07 guest rooms, Fifth floor having 02 staff rooms sealed) was granted NOC by this department vide letter No F 6 / DFS / MS / GH / 2009/ 2315 dated 28.07.2009. The premise was re-inspected by the officer concerned of this department on 11.07.2012 in the presence of Mr. Daljeet found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 1.8./.o.7./.l.2. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ./.8/.97././2..... at New Delhi.

Chief Fire Officer
Delhi Fire Service

Copy to: -

- 1. The Owner, Mohan International" Guest House, located at 8574, Arakashan Road, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

PSS PLGREA

		SPECTION RE	PORT		
	1. Name & address of the building:	m/sMoham =	Linterdal	300al, 8574, A. K	. Road
		Pangy (1907 A	el Delli	
	2. Type of Occupancy	Residential	(Gueste	OUSE)	
	3. Type of Case	old (Re	rewal)		
5- 8	4. Details of previous NOC	Letter No folos	lms/4H/20	09/2315 date 26	107/09
	5. Fire Safety directives Letter No.				/ /
	6. Date of inspection :	09/7/12			
	7. Name of the Inspecting Officer:	ATU	GARG		
	8. Name and designation of Officer	MrC	hadda.		
	from the building side				
	9. Year of Construction	Before &	1000 (A.	spectory)	
J	10. Applicant's letter No.: 4062	G/Ad/CP/LICI	r date	d 29/01/1	
×			,		
S	Minimum standards on fire	BBL		, a	
No	prevention and fire safety U/R 33	Requirements .	Provided at site	Remarks MR/NMR	
	Access of building	1	1.8105		
	 Road width 	NIA	on la	10.0	
	• Gate width	11///	3 /145	MR	
		N/A			
	Width of internal road	N/A	Note that the same of the same		
	Number, width, Type & Arrangemen	nts of exits			
	a. Number of staircases	one	one	anolmo	
	 Upper floors 	Comp	mae	Or of MR	
		1/10	Oloc	one/mp	
	BasementsWidth of staircases	NA	NA	WA	
	Upper floors	0 0			
	opport moors	0.8mb	1.20mg	m L	
	Basements	NA			
	c. Protection of exits				
	 Fire check door 	N/A	. 16		
	Pressurizationd. No of continuous staircase	N/A			
	to terrace	000	1 - 0		
		Uluc	000	MD	

e. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain	
3. Compartmentation • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door	
• Fire check door • Sealing of electrical shafts • Fire Rating of shaft door	
• Fire check door • Sealing of electrical shafts • Fire Rating of shaft door	
Sealing of electrical shafts Fire Rating of shaft door	
• Fire Rating of shaft door	
• Fire Rating of shaft door	\$
λ/Λ	
λ/Λ	
λ/Λ	
• Water Curtain	
4/10	
• Fire Dampers	
A A A	angement and the statement of the profession of the profession of the statement of the stat
4. Smoke managements System	
Basements 30 a/c per hour	
Upper floors 12 a/c per hour	The state of the s
5. Fire Extinguishers	
Total numbers / Noc (Alleen	
1) Nos tetteen	MP
* Types	
	mo
ISI marked Dee	
IS marking.	MD
6. First – Aid Hose Reels	
The Frost reeds	
Total numbers on each floor	m n
Length of hose reel hose	m O
3014)	10/12
Nozzle diameter	m 6
7. Automatic fire detection and alaysis a seed	10) R
variation and anathing system	A second control of the second control of th
Type of detectors	
	, "
Location of Main Panel	
Location of Repeater Panel h// n	
\mathcal{N}/\mathcal{H}	: #
Alternate source of power	*
power power	
* Hooters' Location	
	The second secon
8. MOEFA	
9. Public Address System	M
10. Automatic Sprinkler System	MP
* Basements	
• Upper Floor	
	* ·

<u> </u>		110		
-	 Sprinkler above false ceiling 	NA	The second of th	
7!!.	Internal Hydrants	-		
2	 Size of riser/down- comer 	100 mon	YS.	MR.
	 Number of hydrants per floor 	one	48	MR
10	* Hose Box	one	YS.	MR
12:	Yard Hydrants		— <i>(/ /</i>	J
	 Total number of hydrants 	NA		
	* Hose Box	NA	The state of the s	1
13.	Pumping Arrangements		The state of the s	The contract of the contract o
	Ground Level	1		
	Discharge of main pump	N/A		
	Head of main pump	WA		
	> Number of main pumps	WA		
	Jockey pump out put	NA		
	Jockey pump head	N/A		
	Standby Pump out put	NA		<u> </u>
	Standby Pump Head	NA		
*	Auto Staring/Manual stopping	WA		
3	Pump House Access	NA		*
8	 Terrace level 	ASOLOM	ys.	m R
2 2	Discharge of pump	80 M	ys !	m R
	> Head of the pump	ys !	ys	m R
WI .	Power supply	ye	UR	MR
	Auto starting of pump	1/	1	
14	Captive water Storage for fire fighting	5	<i>U</i>	
	 Under ground tank capacity 	N/A		•
× ×	Draw of connection	NIA		
5 g	Fire service inlet	NA		
	Access to tank	WA	1 ₁₁	
· POT THE SECOND	Overhead Tank capacity	25000	45	MR

15	Exit Signage	UR	110	T NO P
16.	Provision of Lifts	· ·		
	Pressurization of Lift Shaft	1/10		
	Pressurization of lift lobby	11/07		
	Pressurization of lift lobby	NA		
	Communication in lift Car	1110		
		0/1		
	Fireman's Grounding	WKN		9
	Switch	177		
	▶ Lift Signage	WA		
17.	Standby power supply	the	UK	m a
18.	Refuge Area	1		11/1/
	> Total area	d/ (n		a contraction of the contraction
	> Location	N/OF		
	Document	NXD		The second secon
19.	Fire control room	7 7		
	Detector system panel Flow Switch Panel	x2/0		and the second s
	Flow Switch Panel	1 V / H		
	PA System Panel	WA		2
	and and			
	Batter backup	N/D		* *
	Date of the base o	NIN		
	Building Floor Plans	N/H		9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9
				0
20.	Special Fire Protection Systems for			
	Protection of special Risks, if any;	N/A		2 2
	•	0/01		2.4

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Signature of the Inspecting Officer

Name And A

Signature of the Inspecting Officer

Name Dholon vi singly yelow

Designation

Designation Apolo-c/