GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2012/ GH/2708

Dated 24/07/12

FIRE SAFETY CERTIFICATE

Certified that the "Mini Yes Please" Guest House, located at 2026/7, Rajguru Road, Chuna Mandi, Pahar Ganj, New Delhi, comprised of Basement + Ground + Four upper floors having 14 guest rooms (Basement is vacant, Ground floor has Reception + 01 guest room, First to Third floor has 04 guest rooms at each floor, Fourth floor has 01 guest rooms + 01 staff Kitchen found sealed) was granted NOC by this department vide letter No F 6 / DFS / MS / GH / 2009/ 2011 dated 07.07.2009. The premise was re-inspected by the officer concerned of this department on 16.07.2012 in the presence of Mr. Vinod found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 2.4/27/12. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on . 24./.67./...... at New Delhi.

Chief Fire Officer Delhi Fire Service

17

Copy to: -

3

- 1. The Owner, Mini Yes Please" Guest House, located at 2026/7, Rajguru Road, Chuna Mandi, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. This NOC is for Guest Rooms only.

old Cal

W.L.	DIECTION KE	PORT		. 1
1. Name & address of the building	100000000000000000000000000000000000000	The street with the street was a street was a street with the street was a	2016/7 Ch.	m m m l l
, ,		ima n. M.	1) (1)	yeingia
2. Type of Occupancy	Residential	(GULST 100)	&C)	
3. Type of Case	old tren	enal)		
4. Details of previous NOC	Letter No. FG/04		009/2011	dated 7/07/
5. Fire Safety directives Letter No.		1 / 1/0	7	
6. Date of inspection	16/07/12		The sec are pure use	
7. Name of the Inspecting Officer:	ADO/ya	dav		
8. Name and designation of Officer	MVV	nod		# # # # # # # # # # # # # # # # # # #
from the building side			1	
9. Year of Construction	Befor 20	V7 (148/	of open	
10. Applicant's letter No.: 3770	13 /Add (P/)	14/4/ 000	1/1/1-	
phoant stetter INO.	1 JATUA (1 / 1)	C(11) dold	6/6/12	
				192
Minimum standard C		*		
Standards on tire	BBL	Provided at	B	
- 1 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	Requirements .	site	Remarks MR/NM	R
Access of building		1.000		
 Road width 	NIA	CAN		
	13/1	6MA	MR	
• Gate width	0/10			
	10/17			
Width of internal road	N/A	Commence and the second	The second secon	
Number, width, Type & Arrangemen	nts of orite			
a. Number of staircases				
	one	ane	MR	
* Upper floors	ane	one	MR	
 Basements 	me	mar	m P	
b. Width of staircases	010		(0)	
• Upper floors	The state of the s		The second secon	The second secon
Spher moors	O' Som	0.00m		
Basements		901	MR	
	O Sord	0-90M	m e	
c. Protection of exits	X ₁₀			
 Fire check door 	d/n.			
	(V/1-)			
Pressurization	NICh			
d. No of continuous staircase to terrace	(1)			
	one	one	MR	

	NY TI COS			
	e. Width Of Corridor	NA	. A	2
	f. Door Size	NIA		*
3.	Compartmentation			
	• Fire check door			The second secon
	The check dool	NA		
	 Sealing of electrical shafts 	////		
	and of electrical sharts	NA		
	 Fire Rating of shaft door 			
	S of shart door	n/ ra		
	 Water Curtain 	/V///		
		A/1A		
	 Fire Dampers 	11/11	e k	
		N/A	· 2- (1-)	 Another and another and another and another and another and another another and another another and another another and another a
4.	Canala	10///		
-1.	Smoke managements System			
	• Basements	30 a/c per hour	NIA	
	the YIman O			
	[♥] Upper floors	12 a/c per hour	N/A	The state of the s
5.	Fire Extinguishers		147//	0 * * * *
	Total numbers			
	- Total littingers	12	A (Musler)	MK
	Types		W.57	
	2 9 170/3	ISI marked	101,62	MR
	• IS marking	1.31 marked		
			ys.	MR
6.	First - Aid Hose Reels			
	 Total numbers on each floor 	000 0	111	
		OINE	95	m R
	 Length of hose reel hose 	30 mg		A CONTRACTOR OF THE PROPERTY O
		30 10	9	MR.
	 Nozzle diameter 	5 mm	146	m O
7.	Automotic E I.		P	MR
1	Automatic fire detection and alarming	g system		
	 Type of detectors 	NIA		
	V Acation of Main Donal	- / /		9. s
	 Location of Main Panel 	NIA		
	Location of Donoston in			
11.	 Location of Repeater Panel 	NA		
	 Alternate source of power 	hlip		
	Thernate source of power	14/17	3 0	
	 Hooters' Location 	2/10		
0		NA		PA Chamber Top No. 31
8.	MOEFA	ye	CK .	M D
9.	Public Address System	y	GK.	m R
10.	Automatic Sprinkler System			MR
	Basements	43	y	67.0
	 Upper Floor 		(1)	NIR
		NA	NA	en y
	•			

.

	h.	* Sprinkler shave file '!'	1 10
7	11.	Sprinkler above false ceiling Internal Hydrants	N/H
		Size of riser/down-comer	
		512c of fiser/down- comer	N/A
		 Number of hydrants per 	
İ		floor	NA
			1.00
	5 1	* Hose Box	\mathcal{N}/\mathcal{A}
	12.	Yard Hydrants	
		 Total number of hydrants 	6/10
		* Hose Box	2/12
	13.	Pumping Arrangements	0 0 7 7 1
		Ground Level	
	,	 Discharge of main pump 	A / M
-	2		1.0/4
		Head of main pump	h / ()
	100	Number of main pumps	NA
		> Jockey pump out put	, / , /
1		Jockey pump out put	NA
-		Jockey nump head	- / / /
		Jockey pump head	NIA
		Standby Pump out put	
		- tando y 1 tamp out put	N/N
		Standby Pump Head	1 / / 7
-		T	\mathcal{N}/\mathcal{A}
		Auto Staring/Manual	
	22	stopping	NA
			1/10
design of the same		Pump House Access	N/H
		Towns 1	•
		 Terrace level 	as the contract
		Discharge of pump	225 lep of ml
		bischarge of pump	30/AP ys MR
		> Head of the pump	SUNTIL TO THE
		kamp	ys ys mr
		Power supply	
	12		CIR 110 mm
		Auto starting of pump	
	[c].	Captive water Storage for fire fighting	J. T.
		 Under ground tank capacity 	v I/A
			MA
-		Draw of connection	NA
		Eiro comica i Li	
		Fire service inlet	N/A
	-	Access to tank	, 1(1)
		2 LOCOSS TO THIN	
	The state of the s	Overhead Tank capacity	SOVELS YS MR
t		s. s. moud rank capacity	SOULS 95 MR

15	Exit Signage	Y	UK	1
16.	Provision of Lifts			MR
	Pressurization of Lift Shaft	NA		10
	Pressurization of lift lobby Communication in lift Car	NA		
	Communication in lift CarFireman's Grounding	NO		
	Switch	NA		
1 27	> Lift Signage	NA		* * * * * * * * * * * * * * * * * * * *
17. 18.	Standby power supply Reference Assets	K	48	mo
10.	Refuge Area > Total area		The same of the sa	
	> Location	N/A		
19.	Fire control room			
	Detector system panel Flow Switch Panel	N/D		
	PA System Panel	MA		
	> Batter backup	NA		
	> Building Floor Plans	N/H		
20		(Y)		.• • • • •
20.	Special Fire Protection Systems for Protection of special Risks, if any;	ND		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Name Dhalm vil singh yadou

Designation DUC

Designation ADO(C.C)