GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI**

No F 6/DFS/MS/2012/54/2667

Dated 23/07/12

FIRE SAFETY CERTIFICATE

Certified that the Shivam Deluxe Guest House, located at 8261, Arakashan Road, Pahar Ganj, New Delhi, comprised of Ground + Four upper floors having 09 guest rooms (Ground floor has Reception, First to Third floor has 03 Guest rooms at each floor, Forth floor has 01 staff room) was granted NOC by this department vide letter No F 6 / DFS / MS / GH / 2009 / 1384 dated 19.05.2008. The premise was re-inspected by the officer concerned of this department on 01.05.2012 in the presence of Mr. Sunil Maggo found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 23/07/12 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .2.3/.0.7.//2..... at New Delhi.

Delhi Fire Service

Copy to: -

1. Sh. Sunil Maggo, Shivam Deluxe Guest House, located at 8261, Arakashan Road, Pahar Ganj, New Delhi.

2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.

3. All the staff members must know the correct method operation of fire fighting system.

4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.

5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.

The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on 7. This NOC is for Guest Rooms only.

I	NSPECTION REPO	RT		
1. Name & address of the building	M/S Chivar	m Delu	xe, 829/6,	
2. Type of Occupancy	Residental C	Guestra	or Ganz Dahi.	i i
3. Type of Case	old	, , , , , , , , , , , , , , , , , , , ,		
4. Details of previous NOC	I COLOGO	(hackare)	0 9/00 1 1	1.7
5. Fire Safety directives Letter No.	Letter No. FG/OFS/	1115/4H/c	2008/1384 data	9/0
	16/07//2	الله ومن فيلو شدو خلو منه منك فيما تنبو ليما ويدو فيما ينبو من فيلو من من يندو يندو	•	
ar and a second		9000	a day	
7. Name of the Inspecting Officer3. Name and designation of Officer	· · · · · · · · · · · · · · · · · · ·	20-5-6	jeido v	
from the building side	MR Sum	16		
9. Year of Construction	Do Graveron	18 / 4.	1600	
· ·	BEFOREYAU	2 (AS	before Rush)	
10. Applicant's letter No. : N/L	dulid 5	17/12		
DA:				
Minimum standards on fire prevention and fire safety U/R 33	BBL P	rovided at	Remarks MR/NMR	
Access of building	Requirements · si	te		
 Road width 	N/A	001		
2 Cate width	N/A	6/14	MR	
• Gate width	NIA	61/6		
Width of internal road	11/7	NA	N/A	
Number width Type & A	N/A	NA	41/0	
Number, width, Type & Arrangeme	ents of exits		N/A	
staircases	ore -	mar !	MR	
* Upper floors	000	200	000	
	0109	Olde	1x1 K	
* Basements	NA	NA	01.0	
b. Width of staircases		14/41	NA	
 Upper floors 			The second secon	
			Market Company of the	
	0.80 m/s	0.80mg	MR	
Basements	0.80 m/s	0.8ons	MR	
	N/A	0.8ons	MR	
c. Protection of exits	0.80 m/s	0.8ons N/A	MR N/A	
	N/A	0.8ons N/A	MR N/A	
c. Protection of exits Fire check door	N/A N/A	0.8ons N/A	MR N/A	
 c. Protection of exits Fire check door Pressurization d. No of continuous staircase 	N/A N/A N/A	0.8ons N/A	MR N/A	
c. Protection of exits Fire check door	N/A N/A N/A ONE	0.8ons N/A	MR N/A	

g arrange our	Mis Swivan le	14xe, 826116	1 A-RiRa	
E	e. Width Of Corridor	NA		
- 1	f. Door Size	11/00		
3.	Compartmentation	N/A		
	The check goor	NA		
	 Sealing of electrical shafts 	1//0		6
	 Fire Rating of shaft door 	MA		
	• Water Curtain	NA		-
	• Fire Dampers	NA		
		NA	And the last and an executable column of the party as a color-defended. Under the color-defended in Stewar	A segment assessment of the reformation works and sedest from the deformation of the same size to be a second of the second of t
4.	Smoke managements System			Procedures and the second seco
	Basements	30 0/0 000 1		
	•	30 a/c per hour	N/A	
	♥ Upper floors	12 a/c per hour	WA	
5.	Fire Extinguishers	•	///	
	 Total numbers 	12	11011	la - C
			1st truly	MR
	Types	ISI marked	WT, COS, DLP	MQ
	IS marking.		YK	MR
6.	First - Aid Hose Reels	The state of the particular and the state of	//	
	 Total numbers on each floor 			
		one	one	MD
	 Length of hose reel hose 	30 nt	45	MP
	 Nozzle diameter 	5 mm	4	100 0
7.	Automatic fire detection and alarming	Ø system		001
	Type of detectors	4/		
		N/A		,
	Location of Main Panel	NA		
	Location of Repeater Panel	NID		
	 Alternate source of power 	NO		
1 h	 Hooters' Location 	4/10		
8.	The state of the property of the state of th	11/4)		
9.	MOEFA			
10.	Public Address System	YS	45	MR
10.	Automatic Sprinkler System			1,11
	Basements	NA		
	 Upper Floor 	NIT		
		11/11		* **

MLs Shiran Daluxe, 8261/6/A-K. Road

	Sprinkler above false ceiling	N/A		
11.	Internal Hydrants			
	 Size of riser/down~ comer 	N/A		
	 Number of hydrants per floor 	NIA		
	• Hose Box	N/A		
12.	Yard Hydrants			
	 Total number of hydrants 	NA	÷	
	• Hose Box	WA	9	The second secon
13.	Pumping Arrangements			A CONTRACTOR OF THE PROPERTY O
	Ground Level			
	 Discharge of main pump 	NA		
	Head of main pump	NA		
	> Number of main pumps	NA		
	Jockey pump out put	NA		
	> Jockey pump head	NA		6
	Standby Pump out put	NA		
	> Standby Pump Head	NIA	di a	*
	Auto Staring/Manual stopping	NA		
	> Pump House Access			•
8 9	Terrace level	450 lpm	ye	19 8
	 Discharge of pump 	30 NBM	ys.	MR
	> Head of the pump	W/	y	MQ
E _N	Power supply	(10	112	(h) ()
	Auto starting of pump		4	
14.	Captive water Storage for fire fighting	g		
2	 Under ground tank capacity 	NA		
	> Draw of connection	N/A		9
	Fire service inlet	N/A	2 4	
	Access to tank	WA	1x., 7	12
	Overhead Tank capacity	2500/4	1 /3	MR

	Evit Ciana M/S SN	van Delux	11016	, T
15	Lean Dignage	YK	4	MR
16.	Provision of Lifts	1		MR
	Pressurization of Lift Shaft	NA		
	Pressurization of lift lobbyCommunication in lift Car	NA		
	Fireman's Grounding Switch	N/A		
1.77	Lift Signage	WIA		•
17. 18.	Standby power supply	V9	yr	MR
10.	Refuge Area		0.	
	Total areaLocation	N/A W/A		•
9.	Fire control room	/ /		
	Detector system panel Flow Switch Panel	NA		
	➤ PA System Panel	NA		
	> Batter backup	NA	9	
	> Building Floor Plans	NA		
20.	Special Fire Protection Systems for Protection of special Risks, if any,	NA		•

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Service Rules 2010/issue shortcomings noted serial numbers

Signature of the Inspecting Officer

ATLIGHRI Name

Signature of the Inspecting Officer

Name I falm vil singh yalow

Designation Ado (c-c)

Designation DD/CC.